

JVC

SERVICE MANUAL

STEREO HEADPHONES

HA-NC80-J/C/E

The " Product Exchange System" is applicable to this product.
For limited spare parts, refer to the parts list.



SPECIFICATION

Frequency response	10Hz - 22,000Hz
Noise reduction	more than 12 dB at 300Hz(WIDE mode) more than 8 dB at 120Hz(LOW mode)
Sensitivity	103dB/1mW (power- ON), 105dB/1mW (power- OFF)
Input impedance	27Ω (power- ON), 42Ω (power- OFF)
Power supply	AAA battery (DC 1.5V) × 1
Battery life	approx. 25 hours* (using Manganese AAA battery), approx. 50 hours* (using Alkaline AAA battery) • Varies depending on operating conditions. *Without ambient noise.
Cord length	1.5m (4.9ft) (from mini plug to the left channel of the headphone)
Mass	165g (5.82oz) (incl. cord and battery) 140g (4.94oz) (excl. cord and battery)
Accessories	carrying pouch × 1, Manganese AAA battery (R03) × 1, dual plug adapter(for in-flight use) × 1

Design and specifications subject to change without notice.

Parts list

[M][1][M][M]

Δ	SYMBOL	PARTS NO.	PARTS NAME	Q'TY	DESCRIPTION
	1	J47938-001	Ear Pad	2	
	2	LNT0076-001A	INST.BOOK	1	J,C
	2	LNT0077-001A	INST.BOOK	1	E
	2	LNT0079-001A	INST.BOOK	1	E
	3	-----	WARRANTY CARD	1	J, BT-51007-7C
	3	-----	WARRANTY CARD	1	C, BT-52006-2

* Parts marked (Δ) are safety parts. When replacing, be sure to use the specific one.

JVC

Victor Company of Japan, Limited
ACCESSORIES CATEGORY 1644, Shimotsuruma, Yamato, Kanagawa 242-8514, Japan

(No.XC050)