



**POWER AMPLIFIER SECTION**  
**POWER OUTPUT**  
 75 watts per channel minimum RMS, at 8 ohms, from 20 Hz to 20,000 Hz with no more than 0.03% total harmonic distortion.

**PRE AMPLIFIER SECTION**  
 Input Sensitivity/Impedance: Signal to Noise Ratio (IHF-A)  
 Phono 1: 2.5 mV/50 ohms/85 dB  
 Phono 2: 1.5 mV/50 ohms/85 dB  
 Tuner: 150 mV/50 ohms/110 dB  
 AUX: 150 mV/50 ohms/110 dB  
 Maximum Input Level for Phono 1: 250 mV (RMS), 1.0 dB, 0.02% at 1,000 Hz  
 Input Impedance: 100 k ohms  
 Speaker Impedance: 16 ohms

**GENERAL**  
 Power Consumption: 600 watts at full power  
 Dimensions: W 16.51" (419 mm), H 5.71" (145 mm), D 15.18" (384 mm), 33.0 lbs (14.5 kg), 32.6 lbs (14.8 kg)  
 Weight: (Net) 32.6 lbs (14.8 kg), (Gross) 33.0 lbs (14.5 kg)

Note: This listing is a copy of continuous measurements in development. For this reason specifications may be changed without notice.

- 2SA1747 ZSC1116
- 2SA841 ZSC1681
- 2SA850 ZSC1735
- 2SA489 ZSC789
- 2SA755 ZSC1419
- 2SA913 ZSC1913
- 2SB595 ZSD525
- 2SC1345
- 2SA899 ZSC1567
- 2SC1567 ZSC1904
- 2SA673 ZSC1213A
- 2SC1213A ZSC1940
- 2SA640 ZSA872
- 2SA733 ZSA912
- 2SA750 ZSC828
- 2SA763 ZSC945
- 2SC1980 ZSC1980
- 2SA858 ZSC1222
- 2SC2089 ZSC1400
- 2SA620WL
- LPAS3H
- 2SK68