



POWER AMPLIFIER SECTION
POWER OUTPUT
 75 watts per channel minimum RMS, at 8 ohms, from 20 Hz to 20,000 Hz with no more than 0.03% total harmonic distortion.

PRE AMPLIFIER SECTION
 Input Sensitivity/Impedance: Signal to Noise Ratio (IHF-A)
 Phono 1: 2.5 mV/50 ohms/85 dB
 Phono 2: 150 mV/50 ohms/85 dB
 Tuner: 150 mV/50 ohms/110 dB
 AUX: 250 mV/100 ohms/110 dB
 Maximum Input Level for Phono 1: 250 mV (RMS), 1.0 dB, 0.02% at 1,000 Hz
 Output Impedance: 160 ohms/250 ohms
 Frequency Response: 10 Hz to 50,000 Hz, -0.2 dB, -1.5 dB
 Bass: 7 Hz to 100,000 Hz, -10 dB, -1 dB
 Tone Control: (Turnover at 180 Hz) 1.75 dB at 50 Hz, 1.75 dB at 100 Hz, 1.75 dB at 20,000 Hz
 Treble: (Turnover at 3 kHz) 1.75 dB at 100 Hz, 21.6 dB at 31.6 Hz, 21.6 dB at 31.6 Hz
 Loudness Control: (Turnover at 6 kHz) 1.75 dB at 100 Hz, 21.6 dB at 31.6 Hz, 21.6 dB at 31.6 Hz
 Gain Control: (Turnover at 100 Hz) 1.75 dB at 100 Hz, 21.6 dB at 31.6 Hz, 21.6 dB at 31.6 Hz
 Sustain Filter: 40 Hz, 12 dB/oct
 High Filter: 8 kHz, 12 dB/oct

GENERAL
 Power Consumption: 600 watts at full power
 Dimensions: W 16.51" (419 mm), H 5.71" (146 mm), D 15.18" (384 mm), 33.0 lbs (14.5 kg), 32.6 lbs (14.8 kg)
 Weight: (Net) 32.6 lbs (14.8 kg), (Gross) 33.0 lbs (14.5 kg)

Note: This listing is a copy of continuous measurements in development. For this reason specifications may be changed without notice.

- 2SA1747 ZSC1116
- 2SA841 ZSC1681
- 2SA850 ZSC1735
- 2SA489 ZSC789
- 2SA755 ZSC1419
- 2SA913 ZSC1913
- 2SB595 ZSD525
- 2SC1345
- 2SA899 ZSC1567
- 2SC1567 ZSC1904
- 2SA673 ZSC1213A
- 2SC1940
- 2SA640 ZSA872
- 2SC1439
- 2SA733 ZSA912
- 2SC1775
- 2SA750 ZSC828
- 2SC1885
- 2SA763 ZSC945
- 2SC1980
- 2SA858 ZSC1222
- 2SC2089
- 2SC1400
- 2SA620WL
- LPAS3H
- 2SK68