



**System** ..... Super-Low Frequency Drive System

**Mounted Speakers**

Driver ..... 200 mm ( 8 inch) Cone Type x 1  
 Passive Cone ..... 400 mm (16 inch) Cone Type x 1

**Mounted Amplifier**

Power Output ..... 40 watts minimum RMS, 8 ohms at 20 Hz with no more than 0.8% Total Harmonic Distortion  
 More than 10k ohms

**Input Impedance**

Input Sensitivity ..... 1 volt  
 Output Sensitivity ..... 96 dB/W at 1 m (Volume Level MAX)

**Cut off Frequencies**

50 Hz, 100 Hz, 150 Hz, (12 dB/oct)

**Additional Features**

Level Control with 10 LED Level Indicators and 1 LED Peak Indicator  
 Locked type Casters

**Power Requirements**

120/240V (Switchable), 50/60 Hz

**Power Consumption**

40 watts at full power  
 W 477 mm (18-25/32")  
 H 545 mm (21-7/16")  
 D 327 mm (12-7/8")

**Dimensions**

Weights (Net) ..... 24.0 kg (52.8 lbs)  
 (Packed) ..... 26.5 kg (58.5 lbs)

**Weights (Net)**

24.0 kg (52.8 lbs)  
 (Packed) ..... 26.5 kg (58.5 lbs)

(Kenwood follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.)