

KD-2044



SPECIFICATIONS

MOTOR and TURNTABLE

Drive System	Belt Drive System
Motor	4-pole Synchronous Motor
Turntable Platter	30 cm (12") diameter Aluminum Alloy Die-Cast
Speeds	2 Speeds, 33-1/3 and 45 rpm
Wow and Flutter	JIS Less than 0.06% (WRMS) DIN $\pm 0.08\%$
Signal to Noise Ratio (Rumble)	JIS Better than 49 dB DIN unweighted Better than 43 dB DIN weighted Better than 63 dB

TONEARM

Type	Static-Balance Type, S-Shaped Pipe Arm, EIA Plug-in Connector
Effective Arm Length	215 mm (8-7/16")
Over-Hang	9.5 mm (3/8")
Tracking Error	± 1.5 degree
Stylus Pressure Variable Range	0 to 4 grams
Usable Cartridge Weight	4 to 10 grams

CARTRIDGE

Type	Moving Magnet Type [V-39 MKII]
Frequency Response	20 ~ 20,000 Hz
Channel Separation	Better than 25 dB (1,000 Hz)
Output Voltage	3 mV (1,000 Hz, 5 cm/sec)
Output Balance	1.5 dB (1,000 Hz, 5 cm/sec)
Load Impedance	50 Kohms
Stylus	0.5 mil Diamond
Stylus Pressure	2 ± 0.25 grams
Compliance	7×10^6 cm/dyne
Replacement Stylus	N-39 MKII

MISCELLANEOUS

Power Requirements	<ul style="list-style-type: none">• AC 220V, 50 Hz.(L)• AC 220~240V, 50 Hz.(T)• AC 110~120/220~240V 50/60 Hz.(W)
Power Consumption	11 watts (W, L), 7 watts (T)
Dimensions	W: 480 mm (18-7/8") D: 360 mm (14-3/16") H: 165 mm (6-1/2")
Weight	6.5 kg (14.3 lbs)
Special Features	Auto-Return Mechanism, Auto-Cut Mechanism, Pause Elevation (Variable speed), Return Speed Adjusting Mechanism, Anti-Skating Device, Stylus Pressure Direct-Readout Counter, Insulators, Free-Stop Action Dust Cover
Supplied Accessories	EP Adaptor, Motor Lubricating Oil, Over-Hang Gauge, Motor Pulley and Screw Driver (W type)
Destination	(W) (T) (L)