

KD-2055



SPECIFICATIONS

MOTOR and TURNTABLE

Drive System:	Belt drive system
Motor:	4 pole synchronous motor
Turntable Platter:	30 cm (12") diameter Aluminum alloy die-cast
Speeds:	2 speeds, 33-1/3 and 45 rpm
Wow and Flutter:	Less than 0.06% (WRMS) DIN \pm 0.08%
Signal to Noise Ratio (Rumble):	JIS: Better than 50 dB DIN unweighted: Better than 44 dB DIN weighted: Better than 65 dB

TONEARM

Type:	Static-balance type, S-shaped pipe arm, EIA plug-in connector
Effective Arm Length:	215 mm (8-7/16")
Over-Hang:	9.5 mm (3/8")
Tracking Error:	\pm 1.5 degree
Stylus Pressure Variable Range:	0 to 3 grams
Usable Cartridge Weight:	4 to 13 grams (Supplied head snell 7 grams balance weight 4 grams)

CARTRIDGE

Type:	Moving magnet type (V-39 MK II)
Frequency Response:	20 ~ 20,000 Hz
Channel Separation:	Better than 25 dB (1,000 Hz)
Output Voltage:	3 mV (1,000 Hz, 5 cm/sec)
Output Balance:	1.5 dB (1,000 Hz, 5 cm/ sec)
Load Impedance:	50k ohms
Stylus:	0.5 mil diamond
Stylus Pressure:	2 \pm 0.25 grams
Compliance:	7 \times 10 ⁻⁶ cm/dyne
Replacement Stylus:	N-39 MK II

MISCELLANEOUS

Power Requirements:	AC 120V, 60 Hz — K.P. AC 220V, 50 Hz — L AC 220 ~ 240V, 50 Hz — T.X.S. AC 110~120/220~240V, 50/60 Hz — M.U.W.
Power Consumption:	9.5W (U.S.A. and Canada) 14W (Other Nations)
Dimensions:	W 480 mm (18-7/8") D 363 mm (14-5/16") H 146 mm (5-3/4")
Weight:	11.7 kg (25.8 lbs)
Special Features:	Auto-In Mechanism, Auto-Cut Mech- anism, Auto-Return Mechanism, Auto-Repeat Mechanism, Manual Operating Mechanism, Disc Size Selector, Pause Elevation, Anti-Skat- ing, Insulator, Head Shell Stand, Pilot Lamp, Free-Stop Action Dust Cover, Low Capacity Audio Cord with PIN Plug.
Supplied Accessories:	EP adaptor, Motor lubricating oil, Over-hang gauge Motor pulley and screw driver — M.U.W.