

KD-3033



SPECIFICATIONS

MOTOR and TURNTABLE

| | |
|------------------------------|---|
| Drive System | Belt Drive System |
| Motor | 4-pole Synchronous Motor (for turntable). 24-pole Synchronous Gear Motor (for automatic operation). |
| Turntable Platter | 30 cm (12 ") diameter Aluminum Alloy Die-Cast |
| Speeds | 2-Speeds, 33-1/3 and 45 rpm |
| Wow and Flutter | Less than 0.06% (WRMS) |
| Signal to Noise Ratio | More than 49 dB |

TONEARM

| | |
|--|---|
| Type | Static-Balance Type, S-Shaped Pipe Arm, with Lateral Balancer, EIA Plug-in Connector |
| Effective Arm Length | 215 mm (8-7/16") |
| Over-Hang | 9.5 mm (3/8") |
| Tracking Error | ±1.5 degree |
| Stylus Force Variable Range | 0 to 4 grams |
| Usable Cartridge Weight | 4 to 13 grams |

CARTRIDGE

| | |
|---------------------------|-----------------------------------|
| Type | Moving Magnet Type [V-39 MKII] |
| Frequency Response | 20 ~ 20,000 Hz |
| Channel Separation | More than 25 dB (1,000 Hz) |
| Output Voltage | 3 mV (1,000 Hz, 5 cm/sec) |
| Output Balance | 1.5 dB (1,000 Hz, 5 cm/sec) |
| Load Impedance | 50 Kohms |
| Stylus | 0.5 mil diamond |
| Stylus Force | 2±0.25 grams |
| Compliance | 7 × 10 ⁻⁶ cm/dyne |
| Replacement Stylus | N-39 MKII |

MISCELLANEOUS

| | |
|---------------------------|---|
| Power Requirements | ○ AC 120V, 60Hz K.P ○ AC 220V, 50Hz L ○ AC 220 ~ 240V, 50Hz T.X.S ○ AC 110 ~ 120V/ 220 ~ 240V 50/60Hz M.U.W |
| Power Consumption | 14 Watts |
| Dimensions | W 480 mm (18-29/32 ") D 350 mm (13-25/32 ") H 168 mm (6-5/8 ") |
| Weight | 7 kg (15.4 lbs) |

SPECIAL MECHANISM

| | |
|-----------------------------|---|
| (Additional Feature) | Auto-In Mechanism, Auto-Cut Mechanism, Auto-Return Mechanism, Auto-Repeat Mechanism, Manual Operating Mechanism, Disc Size Selector, Pause Elevation, Anti-Skating Device, Head Shell Stand, Insulator, Free-Stop Action Dust Cover, Low Capacity Audio Cord with PIN Plug, Pilot Lamp |
|-----------------------------|---|

ACCESSORIES

| | |
|-------------------|--|
| (Supplied) | EP Adaptor Motor Lubricating Oil Over-Hang Gauge Motor Pulley and Screw Driver M U W |
|-------------------|--|