

KD-4033



SPECIFICATIONS

MOTOR & TURNTABLE

Drive System	Belt drive system
Motor	4-pole synchronous motor (for turntable) 24-pole synchronous Gear motor (for automatic operation)
Turntable Platter	30 cm (12") diameter Aluminum alloy die-cast
Speeds	2-speeds, 33-1/3 & 45 rpm
Wow & Flutter	Less than 0.06% (WRMS)
Signal to Noise Ratio	More than 49 dB

TONEARM

Type	Static balance type S-shaped pipe arm with lateral balancer EIA plug-in connector
Effective Arm Length	215 mm (8-7/16")
Over-Hang	9.5 mm (3/8")
Tracking Error	± 1.5 degree
Stylus Force Variable	
Range	0 to 4 grams
Usable Cartridge	
Weight	4 to 13 grams

CARTRIDGE

Type	Moving magnet type [V-39 MK II]
Frequency Response	20 ~ 20,000 Hz
Channel Separation	More than 25 dB (1,000 Hz)
Output Voltage	3 mV (1,000 Hz, 5 cm/sec)
Output Balance	1.5 dB (1,000 Hz, 5 cm/sec)
Load Impedance	50 kohms
Stylus	0.5 mil diamond
Stylus Force	2±0.25 grams
Compliance	7 x 10 ⁻⁶ cm/dyne
Replacement Stylus	N-39 MK II

MISCELLANEOUS

Power Requirements	AC 110 ~ 120V/ 220 ~ 240V/ 50/60 Hz
Power Consumption	14 watts
Dimensions	W 18-29/32" (480 mm) D 13-25/32" (350 mm) H 6-5/8" (168 mm)
Weight	7 kg (15.4 lbs.)

SPECIAL MECHANISM

(Additional Feature)	Auto-in mechanism Auto-cut mechanism Auto-return mechanism Auto-repeat mechanism Manual Operating mechanism Disc size selector Pause elevation Anti-skating device Head shell stand Insulator Free-stop action dust cover Low capacity audio cord with PIN plug Pilot lamp
-----------------------------	---

ACCESSORIES

(Supplied)	EP adaptor Motor lubricating oil Over-hang gauge Motor pulley & screw driver
-------------------	---