

KP-1022



SPECIFICATIONS

Drive System:	Belt drive system.
Motor:	4-pole Synchronous Motor.
Turntable:	12 inch (30 cm) diameter aluminum alloy die-cast,
Speeds:	2 Speeds, 33-1/3 and 45 rpm.
Wow-Flutter:	Less than 0.07%
Signal to Noise Ratio:	More than 47 dB.
Tonearm:	Static-Balance Type, S-Shaped Pipe Arm, EIA Plug-in Connector
Tracking Error:	±1.5 degree.
Stylus Pressure Variable Range:	0 to 4 grams.
Usable Cartridge Weight:	4 to 10 grams.
CARTRIDGE	
Type:	Moving Magnet Type (V-39 MK-II).
Freq. Response:	20 ~ 20,000 Hz.
Channel Separation:	More than 25 dB (1,000 Hz).
Output:	3 mV (1,000 Hz, 50 mm/sec).
Output Balance:	1.5 dB (1,000 Hz, 50 mm/sec).
Load Impedance:	50 k ohms.
Stylus Pressure:	2 ±0.25 grams.
Stylus:	0.5 mil diamond.
Compliance:	7 x 10 ⁻⁶ cm/dyne.
Replacement Stylus:	N-39 MK-II
Special Mechanism:	Variable Speed Pause Elevation. Anti-Skating Device. Stylus Pressure Direct-Readout Counter.
Supplied Accessories:	EP Adaptor, Motor Lubricating Oil, Over-Hang Gauge, Motor Pulley (except U.S.A. and Canada Market), Screw Driver (except U.S.A. and Canada Market).
Power Consumption:	11 watts.
Dimensions:	W 17-9/16" (446 mm), H 6-7/8" (175 mm), D 13-15/16" (354 mm).
Weight:	13.2 lbs (6 kg).