

KP-2022A



SPECIFICATIONS

DRIVE:	Belt drive system.
MOTOR:	4 pole synchronous motor.
TURNTABLE:	12 inch (30 cm) solid die-cast aluminum alloy type.
SPEED:	2 speeds, 33-1/3, and 45 rpm.
WOW-FLUTTER:	Less than 0.08% (WRMS).
SIGNAL TO NOISE RATIO:	More than 45 dB.
TONEARM:	Static balance type, tapered pipe arm. slide-locked EIA plug-in connector. Direct-reading stylus pressure.
TRACKING ERROR:	±1.5 degree.
STYLUS PRESSURE VARIABLE RANGE:	0 to 4 grams.
USABLE CARTRIDGE WEIGHT:	5 to 10 grams.
CARTRIDGE:	
TYPE:	Moving magnet type. (N-39).
CHANNEL SEPARATION:	More than 25 dB (1,000 Hz).
FREQUENCY RESPONSE:	20 to 20,000 Hz.
OUTPUT:	5 mV (1,000 Hz, 50 mm/sec).
SPECIAL MECHANISM:	Geared elevation, auto-return, auto-cut, pause elevation.
POWER REQUIREMENT:	AC 110 to 120 V / 220 to 240 V, 50/60 Hz.
POWER CONSUMPTION:	8 watts.
DIMENSIONS:	W 17-9/16" (446mm), H 6-11/16" (170mm), D 13-5/8" (346mm).
WEIGHT:	14.3 lbs. (6.5 Kg).