

KP-2022



SPECIFICATIONS

DRIVE:	Belt Drive System
MOTOR:	4 Pole Semi-Synchronous Motor
TURNTABLE:	12 inch Solid die-cast aluminium alloy type.
SPEED:	Two Speed 33-1/3 & 45 rpm
WOW & FLUTTER:	Less than 0.08%
SIGNAL TO NOISE RATIO:	More than 45 dB
TONE ARM:	Static Balanced Pipe Arm. 4-terminal plug-in type, Lateral Balancer
TRACKING ERROR:	± 1.5 degrees
STYLUS PRESSURE VARIABLE RANGE:	0 to 4 g
CARTRIDGE:	Moving Magnet type
FREQUENCY RESPONSE:	20 to 20,000 Hz
OUTPUT BALANCE:	Within ± 1 dB
CHANNEL SEPARATION:	More than 25 dB at 1,000 Hz
IMPEDANCE:	5 k Ω
OUTPUT VOLTAGE:	5 mV (1,000 Hz, 5 cm/sec.)
LOAD IMPEDANCE:	50 k Ω
RECOMMENDED STYLUS PRESSURE:	3 g
STYLUS:	0.7 mil Diamond Stylus.
COMPLIANCE:	7 x 10 ⁻⁶ cm/dyne
REPLACEMENT STYLUS:	TYPE N-34
SPECIAL MECHANISM:	Auto-return, Auto-cut, Arm elevation.
SUPPLIED ACCESSORIES:	EP Adaptor, Motor oil
POWER REQUIREMENTS:	AC 110-120 V/220-240 V 50/60 Hz
POWER CONSUMPTION:	8 W
DIMENSIONS:	6-11/16" (H) x 17-9/16" (W) x 13-5/8" (D)
WEIGHT:	14.3 lbs.