

KP-3021A



SPECIFICATIONS

DRIVE: Belt Drive System

MOTOR: Semi-synchronous motor

TURNTABLE: 12 inch (30 cm) Solid die-cast aluminum alloy type

SPEED: Two Speed, 33-1/3 and 45 rpm

WOW & FLUTTER: Less than 0.08 %

SIGNAL TO NOISE RATIO: More than 45 dB

tone ARM: Static Balanced Pipe Arm, 4-terminal plug-in type, Lateral Balancer

TRACKING ERROR: ± 1.5 degrees

STYLUS PRESSURE VARIABLE RANGE:

0 to 4 grams

CARTRIDGE: Moving Magnet type

FREQUENCY RESPONSE: 20 ~ 20,000 Hz

OUTPUT BALANCE: within ± 1 dB

CHANNEL SEPARATION: More than 25 dB at 1,000 Hz

IMPEDANCE: 5 k Ω

OUTPUT VOLTAGE: 5 mV (1,000 Hz, 5 cm/sec.)

LOAD IMPEDANCE: 50 k Ω

RECOMMENDED STYLUS PRESSURE:

3 ± 0.5 grams

STYLUS: 0.7 mil Diamond Stylus

COMPLIANCE: 7×10^{-6} cm/dyne

REPLACEMENT STYLUS: Type N-34

SPECIAL MECHANISM:

Auto-in-Auto-cut, Auto-repeat, disc size selector manual-in system, 24 pole synchronous gear motor for arm drive, Elevation Lever.

SUPPLIED ACCESSORIES: EP Adaptor, Motor oil

POWER REQUIREMENTS: AC 100 - 120V/220-240V 50/60 Hz

POWER CONSUMPTION: 60 Hz 14W, 50 Hz 15.5W

DIMENSIONS: H7" (175) x W 18-1/8" (460) x D16-1/8" (410) mm

WEIGHT: 14.3 lbs.