

KP-3021



SPECIFICATIONS

Drive	Belt Drive System
Motor	Outer-rotor hysteresis synchronous
Turntable	12 inch (30 cm) Solid die-cast aluminum alloy type
Speed	Two Speed, 33-1/3 and 45 rpm
Wow and Flutter	Less than 0.08%
Signal to Noise Ratio	More than 45 dB
Tonearm	Static Balance Pipe Arm, 4-terminal plug-in type, Lateral Balancer
Tracking Error	± 1.5 degrees
Stylus Pressure Variable Range	0 to 4 grams
Cartridge	Moving Magnet type
Frequency response	20 to 2,000 Hz
Output balance	Within ± 1 dB
Channel separation	More than 25 dB at 1,000 Hz
Impedance	5k ohms
Output voltage	5 mV (1,000 Hz, 5 cm/sec)
Load impedance	50k ohms
Recommended stylus pressure	3 ± 0.5 grams
Stylus	0.7 mil Diamond Stylus
Compliance	7×10^{-6} cm/dyne
Replacement stylus	TYPE N-34
Special Mechanism	Auto-in-Auto-cut, Auto-return, Auto-repeat, disc size selector manual-in system, 24 pole synchronous gear motor for arm drive
Supplied Accessories	Plug-in head, EP Adaptor, Motor oil
Power Requirements	AC 110 ~ 120V/220 ~ 240V, 50/60 Hz
Power Consumption	60 Hz 14W, 50 Hz 15.5W
Dimensions	H 17" (175) \times W 18-1/8" (460) \times D 16-1/8" (410) (mm)
Weight	14.3 lbs.