



SPECIFICATIONS

Power output
 65 watts* per channel minimum RMS, both channels driven, at 5 ohms from 20 Hz to 20,000 Hz with no more than 0.03% total harmonic distortion.

Distortion
 Both Channels Driven: 70:1 THD at 1,000 Hz
 83:1 THD at 100 Hz

Total Harmonic Distortion
 20 Hz to 20,000 Hz: 0.03% at rated power into 8 ohms
 AFD input to SPEAKER output: 0.03% at rated power into 8 ohms

PHONO input to SPEAKER output: 0.03% at rated power into 8 ohms
 Input Impedance: 100,000 ohms (resistor network)
 Frequency Response: 20 Hz - 20,000 Hz (±1 dB)

Damping Factor: 100
 50, 20 Hz - 20,000 Hz into 8 ohms

Transient Response: 1.0 μs
 Rise Time: 4.100 μs
 Slew Rate: 5 Hz to 40,000 Hz at 0.03% THD, 100 ohms: 100 V/μs
 Speaker Impedance: Accept 4 ohms to 16 ohms

Input Sensitivity/Impedance: 3.0 mV/100 ohms
 Tuner, AUX, Tape A, B: 100 mV/50 ohms
 Signal to Noise Ratio (IHF, A): 98 dB for 3.5 mV input
 92 dB for 1.0 mV input
 88 dB for 0.3 mV input

Tuner, AUX, Tape A, B: 100 ohms for 1.0 mV input
Output Level/Impedance: 200 mV/100 ohms
THD: 0.03% at 1,000 Hz
THD: 0.03% at 100 Hz

Frequency Response for Phono: RIAA standard curve, ±0.3 dB
 20 Hz to 20,000 Hz

Tone Control: ±10 dB at 100 Hz
Bass: ±10 dB at 10,000 Hz
Treble: ±10 dB at 10,000 Hz
Logic Control: ±10 dB at 100 Hz - 30 dB VOLUME LEVEL

GENERAL
Power Consumption: 3.5 A ILL per CSA
 4.20 W IEC
 270 W (8 ohms at rated power)
A.C. Outlet: Switched 2, Unswitched 1
Dimensions: W 440 mm (17.3103")
 H 100 mm (3.9370")
 D 487 mm (19.1731")
Weight (Net): 10.7 kg (23.6 lbs)
 * Measured pursuant to Federal Trade Commission's True Regulation for Power Output Claim for Amplifier in U.S.A.

Note: Kenwood follows a policy of continuous advancements in developments. For this reason specifications may be changed without notice.