



- NOTES UNLESS OTHERWISE SPECIFIED:
- ALL RESISTORS ARE IN OHMS, $\pm 5\%$, 1/4W.
 - ALL NON-ELECTROLYTIC CAPACITORS ARE IN μF , $\pm 5\%$, 100V. TOLERANCE ON ELECTROLYTIC CAPACITOR VALUES IS $\pm 50\%$, -10% .
 - LOCATED ON 215-1009-100 HEAT SINK ASSEMBLY.
 - OUTLINE INDICATES 145-1006-100 INDUCTOR ASSEMBLY.
 - Q201 THRU Q204 AND Q301 THRU Q304 ARE SELECTED FOR NOISE LEVEL.
 - ALL S201 DECKS SHOWN AS VIEWED FROM SHAFT END WITH SWITCH IN EXTREME C.C.W. (MIC) POSITION.
 - SYMBOL \otimes REPRESENTS WIRE TERMINATION POINT.
 - SYMBOL \boxtimes REPRESENTS SOLDERED MATING CONNECTORS.
 - PART OF A6 JACK BOARD ASSEMBLY.
 - VOLTAGES SPECIFIED ARE DC VOLTS TO GROUND, MEASURED ON A TYPICAL UNIT.

Model 120
console stereo amplifier
SCHEMATIC