

DV6001

Single Disc DVD Player



Quality universal players are difficult to find. But the DV6001 combines universality and quality in a uniquely Marantz fashion. It handles movie DVDs, DVD-As, SA-CDs, conventional music CDs, recordable CD-R/RWs, VCD 2.0 discs, MP-3 and WMA audio discs, even JPEG picture discs! The Marantz audio tradition now includes internal Dolby Digital and DTS decoders. Six 192 kHz/24-bit digital-to-analog converters make everything sound exceptionally lifelike. Shut off the DV6001's video circuitry completely for the purest audio signal path possible. Internal bass management circuits route DVD-A and SA-CD audio channels directly to the proper speakers. Video technology includes advanced 3:2 pull down circuitry and wide bandwidth video D/A converters for exceptional picture quality. Composite, S-Video, and component outputs? Progressive scan? Of course! Connectivity options include a variety of audio and video outputs. There's a D-BUS connector for total Marantz system control. The three-year warranty increases your peace of mind.

- Plays DVD-V, DVD-A, SACD-Multi, SACD-Stereo, DVD-R/RW, DVD+R/RW, SVCD, VCD, CD, CD-R/CD-RW, MP3, WMA, JPEG, DivX
- Faroudja DCDi processing and NSV (Noise Shaped Video)
- HDMI Output with Scaling (1080p, 1080i, 720p and 480p)
- CD Text and CD Up-Sampling
- RS-232C Terminal for System Control
- 192kHz/24-Bit Audio DAC
- Direct IR Input
- 216MHz/12-Bit Video DAC
- D-BUS remote Connection
- Progressive Scan w/3:2 Pull-Down
- Detachable AC Cord
- Dolby Prologic II and DTS Decoders

marantz®

Life Amplified



FEATURES

Separate Power Supply for Audio	-
DTS® Decoder	•
Dolby Digital® Decoder	• (Dolby Prologic II)
Disc Capacity	1
Progressive Scan	•
3:2 Pulldown	•
Playback Formats	DVD-V, DVD-A, SACD-Multi, SACD-Stereo, DVD-R/RW , DVD+R/RW , SVCD, VCD, CD, CD-R/RW , MP3, WMA, JPEG, DivX
Video DAC	216MHz/12-Bit
Audio DAC	192kHz/24-Bit
HDAM	-
Video Circuit Off	-
Display On/Off	•
Zero-Impedance Plate	-
Double Layer Bottom Plates	-
Headphone	-
Video Scaler	•
Bass Management	•
Gold Plated Terminals	-

SOUND ENHANCEMENT

Power Transformer	AI
Chassis	Metal
Lip-sync (digital audio delay)	-

IN/OUTPUTS

VIDEO	
HDMI Out	1
Component Out	1
S-Video Out	1
Composite Out	1
AUDIO	
Analog Out (RCA)	1
5.1ch Analog Out	1
Digital Optical Out	1
Digital Coaxial Out	1
i.Link (IEEE1394)	-
OTHER	
External control (RS232C)	•
D-Bus Remote (RC-5) In/Out	1/1
Direct IR input	•

SPECIFICATIONS

Freq. Response (Digital Audio)	4Hz - 44kHz (DVD fs:96kHz)
S/N Ratio	110db
Dynamic Range	100db
THD (1 kHz)	0.0030%
GENERAL	
Color	Black
Front Panel	Aluminum
Remote Control	•
Power Requirement	AC120-230V 50/60Hz
Power Consumption	25w, 0.8w in standby mode
Dimensions W x H x D (Inches)	17 5/16" x 3 1/16" x 12 9/16"
Weight (lbs)	8.8 lbs



marantz®

Life Amplified

*All specifications, dimensions and weights are subject to change without notice.
 D&M Holdings, Marantz, Marantz America, Inc. or any of its subsidiaries will not assume any liability for errors in this spec sheet which may result in consequential errors being made by retail dealers, designers, custom installers, cabinet makers or end users, etc based upon information contained within this document.