marantz[®]



REFERENCE SERIES Digital Surround Receiver

The Marantz Reference Series SR-19EX THX Ultra® Digital Surround Receiver delivers state-of-the-art surround sound audio performance, incorporating Dolby Digital®, THX® Surround EX and DTS® ES Matrix 6.1-channel decoding for the ultimate in multichannel sonic realism. The SR-19EX includes a host of high-end receiver features, such as 192kHz/24-bit D/A converters on all seven channels for extraordinary sonic performance, three sets of component video inputs, an

extensive complement of digital and analog inputs and many additional refinements. The SR-19EX is designed for exceptional ease of operation, featuring an intuitive on-screen menu system and learning remote control that provide complete control of an entire home theater system including multi-room operation. The SR-19EX is built to the highest standards, with stunning Reference Series styling that perfectly complements the most sophisticated home theater installations.

Feature

- ♦ THX Surround EX® and DTS® ES Matrix 6.1channel decoding
- ◆ Dolby Digital® and DTS® 5.1-channel decoding, plus additional surround modes
- ♦ 192kHz/24-bit D/A converters for all seven channels
- ♦ 130 watts power output for each of the five main channels with selectable power amp output
- ♦ Three sets of component video inputs
- ♦ Extensive array of digital and analog inputs, outputs and switching facilities
- ♦ Gyro Touch AM/FM tuner with 50 station preset tuning and station naming function
- ♦ On-screen display and award winning learning remote control

Benefit

- Provides an additional center back surround channel for enhanced surround sound realism
- ➤ Delivers accurate decoding of all popular surround sound formats
- ➤ State-of-the-art resolution and sonic performance
- > Front L/R amplifiers can be switched to power back surround channels in a 6.1channel system (additional stereo amplifier required for 6.1-channel operation)
- Accommodates multiple component video sources such as DVD players and DTV settop boxes
- > Unmatched connection flexibility in the widest range of systems
- ➤ Precision AM/FM tuning with clear reception of even weak and distant stations
- > Easy, intuitive operation with control of a complete audio/video system

State-of-the-Art Home Theatre Surround Sound



Reference Series Digital Surround Receiver

SR-19EX

Specifications

FM t	uner	section:
------	------	----------

Frequency range	87.5 - 108.0MHz
Usable sensitivity	IHF 1.8μV/16.4dBf
Signal to noise ratio	Mono/Stereo 76/72dB
Distortion	Mono/Stereo 0.2/0.3%
Stereo separation	1kHz 45dB
Alternative channel selec	tivity ±300kHz 60dB

AM tuner section:

Frequency range	520-1710kHz
Signal to noise ratio	50dB
Usable Sensitivity	Loop 400μV
Distortion	1kHz, 30% Mod. 0.5%
Selectivity	±20kHz 70dB

Audio section:

Continuous power output (RMS)

(<0.05% TH	ID, 20Hz - 20kHz)
Front (20Hz - 20kHz)	8Ω 130W/Ch
Center (20Hz - 20kHz)	8Ω 130W/Ch
Surround (20Hz - 20kHz)	8Ω 130W/Ch
Input sensitivity/impedance	
Linear	$350 \text{mV} / 47 \text{K}\Omega$
Signal to noise ratio	
Linear	106dB
Frequency response	

(analog input/source direct) 8Hz-80kHz(±3dB)

General:

Power requirements	AC 120V 60Hz
Power consumption	
(stereo mode rated p	ower) 530W
Dimensions	7 ¹⁵ / ₃₂ "H x 18"W x 19 ³ / ₈ "D
	190mm x 458mm x 493mm
Weight	50.7lbs (23kg)

Accessories:

Remote control unit RC-18SR	1
AA-size batteries	4
FM feeder antenna	1
AM loop antenna	1

Note: The specifications and design of this product are subject to change without notice.







THX EX, THX Ultra, THX Select, THX and Lucasfilm Cinema RE-EQ are registered trademarks of Lucasfilm Ltd. "DOLBY," "DOLBY DIGITAL," "Dolby Pro Logic," "Dolby B," "C," "S," and Dolby HX Pro," and the double-D symbol are trademarks of Dolby Laboratories Licensing Corp. DTS is a registered trademark of DTS Technology. DTV is a registered trademark of ATSC Laboratories.

