



PIN NO. VOLTAGE (V)			PIN NO. VOLTAGE (V)			PIN NO. VOLTAGE (V)		
IC101,103,104			IC105			IC301		
1	13.2	1	3.82	1	13.2	1	13.2	1
2	10.0	2	0	2	0	2	3.55	2
3	0	3	0.68	3	0	3	4.78	3
4	0	4	0	4	0.71	4	0.71	4
5	1.79	5	2.10	5	10.12	5	10.12	5
6	4.33	6	2.10	6	10.16	6	10.16	6
7	4.32	7	2.10	7	0	7	0	7
8		8	2.03	8	0.01	8	0.01	8
9		9	2.10	9	6.24	9	6.24	9
10		10	2.03	10	2.79	10	2.79	10
11	13.2	11	13.2	11	2.79	11	2.79	11
12	13.2	12	5.73	12	2.80	12	2.80	12
13	1.0	13	5.73	13	2.80	13	2.80	13
14	1.79	14	5.73	14	2.80	14	2.80	14
15	4.33	15	5.39	15	4.30	15	4.30	15
16	4.32	16	5.30	16	3.03	16	3.03	16
0		0	0	0		0		0

- SCHEMATIC SYMBOLS:**
- Ⓜ POLYESTER FILM CAPACITOR
 - Ⓢ POLYSTYRENE FILM CAPACITOR
 - Ⓣ TANTALUM ELECTROLYTIC CAPACITOR
 - Ⓛ BIPOLAR CAPACITOR
 - NONFLAMMABLE RESISTOR

- NOTES:**
1. SCHEMATIC IS SUBJECT TO CHANGE WITHOUT NOTICE.
 2. RESISTANCE VALUES ARE IN OHMS. K = 1,000; M = 1,000,000
 3. CAPACITANCE VALUES 1.0 AND ABOVE ARE IN pF OR μF (P = pF, M = μF). LESS THAN 1.0 ARE IN μF. (ELECTROLYTIC CAPACITANCE VALUES ARE IN μF/MV.)
 4. VOLTAGES ARE MEASURED TO CHASSIS GROUND WITH A "DC VOLTMETER".

V : VOLTAGES MEASURED WITH NO SIGNAL APPLIED.