



NO	FUNCTION	POSITION
S901	POWER	OFF [ON]
S321 ~ S325	SELECTOR	[CD, D] CD PHONO [TUNER] TUNER [AUX] AUX [TAPE-1/DAT] TAPE-1/DAT [TAPE-2] TAPE-2
S326	MONITOR	[SOURCE] TAPE-1/DAT
S327	MONITOR	[SOURCE] TAPE-2
S301	CARTRIDGE	[MC] MC [MM] MM
S351	MUTING	[OFF] OFF [ON] ON
S352	LOUDNESS	[OFF] OFF [ON] ON
S371	BASS/SEL-TONE	[BASS] SEL-TONE
S551	SPEAKERS	OFF [A] B A+B

**NOTES**

- THE COMPONENTS IDENTIFIED BY MARK  $\Delta$  ARE CRITICAL FOR SAFETY. REPLACE ONLY WITH PART NUMBER SPECIFIED.
- VOLTAGE (MEASURED WITH V.T.V.M.)  $\square$  V IS DC VOLTAGE. (NO INPUT SIGNAL)
- ELECTROLYTIC CAPACITORS ( $\square$ ) ARE IN  $\mu$ F/WV.
- ALL CAPACITORS ARE IN  $\mu$ F/50V UNLESS OTHERWISE NOTED.
- ALL RESISTORS ARE IN OHMS 1/4 WATTS UNLESS OTHERWISE NOTED.
- ALL DIODES ARE IS243, IS2076, US1040 or ISS133 UNLESS OTHERWISE NOTED.
- CIRCUIT IS SUBJECT TO CHANGE FOR IMPROVEMENT.

NAAF-2956-1A