

## Powerful performance, flexible control



The powerful control solution for your home and all your entertainment devices, fully customizable to the needs of you and your family.

### Single control solution for any device, any brand

- Extensive infrared code database for any device or brand
- Convenient IR learning from another remote by pointing to it
- Radio frequency works through walls and from other rooms
- Additional functionality through future software upgrades

### Fully customizable user interface

- Multiple commands blended into one-touch control
- Greyscale LCD displays realistic, easy to see buttons
- PC software to create your own user interface

### Great convenience

- LCD screen has backlighting for convenience in the dark
- Cursor keys simplify navigation through on-screen menus
- Settings and codes are retained when replacing the batteries
- Sensor reacts to ambient light to adjust backlighting



## Technical specifications

### Picture/Display

- **Diagonal screen size (inch):** 3.8 in
- **Display colors:** 16
- **Backlight**
- **Backlight color:** Blue
- **Resolution:** 320 x 240 pixels
- **Touch panel**

### Infrared Capabilities

- **Operating distance:** 33 ft (10 m)
- **Learning IR codes**
- **Learning frequency range:** Up to 78 kHz and 455 kHz
- **Transmitting LEDs:** 4
- **Universal IR code database**
- **Number of brands in database:** Over 1100

### RF Capabilities

- **Addresses (ID's):** 16
- **Channels:** 4
- **Communication:** 1-way
- **Frequency (MHz):** 433

### Customisation

- **Editor application on PC:** ProntoEdit NG
- **On screen customisation**
- **Full screen configurability**
- **Transparency**
- **Macros:** Up to 250 steps
- **Alpha-blending:** No

### Connectivity

- **USB:** USB 1.1

### Convenience

- **Automatic power off**

- **Clock with calendar**
- **Cursor key**
- **Hard buttons**
- **Programmable timers:** 20
- **Gentle fade out of light**
- **Multi language:** GB, D, F, E, NL
- **Cradle/Docking station:** Optional
- **Pick up sensor:** No

### Dimensions

- **Master carton weight:** 3.8 kg
- **Master carton quantity:** 2
- **Product dimensions (W x H x D):** 92 x 153 x 27 mm
- **Product weight:** 0.260 kg
- **Temperature Range (Operation):** +5°C/+45°C

### System Specifications

- **CPU:** Mitsubishi 16 bit
- **Flash memory size:** 4 MB

### System Requirements

- **CD-ROM drive**
- **Hard disk space:** 75 MB
- **PC OS:** Windows 98 SE, 2000, ME, XP
- **RAM memory:** 64 MB
- **USB:** Free USB port

### Accessories

- **Batteries:** 4 x AAA
- **CD-ROM:** with PC-editor software
- **Printed User Guide**
- **USB cable**
- **User Guide on CD-ROM**
- **Warranty Card**
- **Docking Station:** optional

## Product highlights

### Universal IR code database

A universal IR code database refers to a library of infrared codes built-in to a particular remote. This feature allows a remote to control your equipment without needing to learn individual signals. Select the correct infrared code sets in the database for the devices you want to control, to enable control of virtually every audio/video system element on the market today – regardless of model or brand.

### Greyscale LCD display

Create own layout in shades of gray. Easy selection of buttons and commands using the touch screen.

### Learning functionality

Learning functionality refers to the process through which a remote control captures and stores infrared signals from other remotes for later use. When device codes are not included in the on-board database, they can always be learned from the original remote, simply by pointing to it.

### One-touch convenience

One-touch convenience allows you to perform multiple commands with one press of a button via a macro. A macro combines a string of pre-programmed commands under one single button. Therefore, it simply takes one button press to execute a series of functions.

### Light sensor

Light sensor is a feature that automatically activates the backlight when the ambient lighting reaches a certain level.

### Radio frequency

A radio technology that allows you to control components not in direct line-of-sight, such as through walls or other obstacles. There are two types of RF used in remote controls: RF to component, and RF to infrared.

### PC software included



Date of issue 2005-05-11

Version: 5.0

12 NC: 9082 100 01591  
EAN: 87 10895 75450 7

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.  
© 2005 Koninklijke Philips Electronics N.V.  
All Rights reserved.  
[www.philips.com](http://www.philips.com)

