

## 8. SE-100

### SPECIFICATIONS

Speaker .....	Electret push-pull static type 2-way system
Static capacity .....	140pF (each channel, including the connecting cord)
Frequency response .....	20 to 35,000 Hz
Sensitivity .....	95 dB or greater (input 100V) with B&K Artificial ear 4153
Maximum sound pressure level .....	115 dB
Distortion .....	Less than 1% (at sound pressure level 100 dB)
Separation .....	40 dB or more (at audible band)
Connecting cord .....	8.2 ft./2.5 m (with 4-P plug)
Weight .....	13 oz/360 g (except connecting cord)

#### NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

### PARTS LIST

Key No.	Description	Part No.	
1	Speaker Assembly (Electret type)	SXC-048-0	
2	Case (L)	SXC-041-0	
3	Case (R)	SXC-042-0	
4	Ear Pad	SXC-043-0	
5	4-P Plug with Connecting Cord	K71-643-0	
6	Lead Wire	SXC-044-0	
7	Holder Unit	SXC-045-0	
8	Shaft for Holder	SXC-046-0	
9	Head Band Assembly	SXC-047-0	
10	Capacitor (39pF, DC 2kV)	SCG-001-0	
	Packing Case	H93-641-0	
	Styrol Protector	H92-609-0	
	Operating Guide (SE-100, JB-100)	SRB-009-0	



