

## 2. SE-20A

### SPECIFICATIONS

Matching Impedance	4 ~ 16Ω
Earpiece Element Impedance	8Ω per element
Maximum Allowable Input	0.5W (each element)
Frequency Response	20 ~ 18,000 Hz
Cord	8.2 ft, with 3-P plug
Weight	13.3 oz. (380g) without cord

**NOTE:**

Specifications and the design subject to possible modification without notice due to improvements.

### PARTS LIST

Key No.	Description	Part No.
1	Speaker Assembly	SXC-007-0
2	Protection Board (Left)	SCD-184-0
3	Protection Board (Right)	SCD-183-0
4	Case	SXC-021-0
5	Ear pad	SCD-134-0
6	Head pad	SCD-202-0
7	Head Band (A)	N63-741-A
8	Head Band (B)	N63-742-0
9	Adjusting Knob (Right & Left)	SXC-003-0
10	Cord with 3-P Plug	SXC-013-0
11	Lead Wire	SXC-005-0
12	Band Shaft	SXC-006-0
	Packing Case (not for SE-20A/up)	H93-626-0
	Leather Case (SE-20A/up only)	SHF-001-0
	Outer Case (SE-20A/up only)	H93-628-A
	Operating Guide	R12-719-0



