

DR SERIES

Sansui hi-fi systems—packed with features,
made for the sheer pleasure of digital



Sansui S-U2000

SYSTEM DR-700

DA-E70 Double Cassette Amplifier
T-E70L Quartz-PLL Synthesizer Tuner
P-E70 Auto-Return Turntable
CD-E70 Compact Disc Player (optional)
S-U2000 2-Way Speaker System



Sansui

Sansui's new DR series— Shelftop compacts for digital sound



SYSTEM DR-700

- High power output of 65 watts × 2 (DIN)
- 20-key full-function remote control
- 5 inputs: PHONO, TUNER, CD, TAPE, VIDEO SOUND/AUX
- 5-band graphic equalizer (100, 330Hz, 1k, 3.3k, 10kHz)
- Connections for Speakers A, B and Surround Sound
- Double cassette transports with full logic tape control
- One-touch dubbing at normal/high speed
- Continuous relay play of two tapes
- AMPS (Automatic Music Program Search) for tape
- Dolby* B noise reduction for low tape noise
- Accurate quartz-PLL synthesizer tuning
- Presets for 8 FM and 8 MW/LW stations
- Convenient auto-return record playback
- Low-mass straight tonearm for better tracking
- Two-way speaker systems with 165mm woofers
- CD player (optional) with 3-beam laser pickup, random programming of up to 16 tracks, auto spacing and 3-way repeat

*"Dolby" and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.

SPECIFICATIONS

DA-E70 [AMP] THD: 0.5% (at rated output)
 Freq. Response: 10—50,000Hz S/N Ratio: 90dB
[CASSETTE DECK] Wow & Flutter: 0.06% (WRMS)
 S/N Ratio: 64dB (Dolby "B" on)
 Dimensions (W × H × D): 380 × 222 × 301mm Weight: 8.1kg
T-E70L FM Sensitivity: 10.8dBf/0.9μV (DIN)
 Dimensions (W × H × D): 380 × 67 × 227mm Weight: 1.7kg
P-E70 Wow & Flutter: 0.06% (WRMS)
 Dimensions (W × H × D): 380 × 98 × 365mm Weight: 2.9kg
CD-E70 THD: 0.003% S/N Ratio: 100dB (IEC-A-WTD)
 Dimensions (W × H × D): 380 × 82 × 313mm Weight: 3.6kg
S-U2000 Woofer: 165mm cone type
 Tweeter: 50mm cone type
 Dimensions (W × H × D): 226 × 368 × 192mm
 Weight: 3.4kg



SYSTEM DR-600

- High power output of 35 watts × 2 (DIN)
- 4 inputs: PHONO, TUNER, CD/AUX, TAPE
- 5-band graphic equalizer (100, 330Hz, 1k, 3.3k, 10kHz)
- Double cassette transports
- Normal/high speed dubbing
- Continuous relay play of two tapes
- Mic mixing with source program
- Dolby B noise reduction system for low tape noise
- Accurate quartz-PLL synthesizer tuning
- Presets for 8 FM and 8 MW/LW stations
- Convenient auto-return record playback
- Low-mass straight tonearm for better tracking
- Two-way speaker systems with 165mm woofers
- CD player (optional) with 3-beam laser pickup, random programming of up to 16 tracks, auto spacing and 3-way repeat

SPECIFICATIONS

DA-E50 [AMP] THD: 0.5% (at rated output)
 Freq. Response: 10—50,000Hz S/N Ratio: 90dB
[CASSETTE DECK] Wow & Flutter: 0.12% (WRMS)
 S/N Ratio: 64dB (Dolby "B" on)
 Dimensions (W × H × D): 380 × 222 × 301mm Weight: 5.9kg
T-E70L FM Sensitivity: 10.8dBf/0.9μV (DIN)
 Dimensions (W × H × D): 380 × 67 × 227mm Weight: 1.7kg
P-E50 Wow & Flutter: 0.06% (WRMS)
 Dimensions (W × H × D): 380 × 98 × 365mm Weight: 2.9kg
CD-E70 THD: 0.003% S/N Ratio: 100dB (IEC-A-WTD)
 Dimensions (W × H × D): 380 × 82 × 313mm Weight: 3.6kg
S-U1000 Woofer: 165mm cone type
 Tweeter: 50mm cone type
 Dimensions (W × H × D): 226 × 368 × 192mm Weight: 3.2kg

SYSTEM DR-500

- High power output of 35 watts × 2 (DIN)
- 4 inputs: PHONO, TUNER, CD/AUX, TAPE
- 5-band graphic equalizer (100, 330Hz, 1k, 3.3k, 10kHz)
- Double cassette transports
- Normal/high speed dubbing
- Continuous relay play of two tapes
- Mic mixing with a source program
- Dolby B noise reduction system for low tape noise
- FM interstation noise muting
- 3-band radio reception: FM, MW and LW
- Convenient auto-return record playback
- Low-mass straight tonearm for better tracking
- Two-way speaker systems with 165mm woofers
- CD player (optional) with 3-beam laser pickup, random programming of up to 16 tracks, auto spacing and 3-way repeat

SYSTEM DR-600

- DA-E50** Double Cassette Amplifier
- T-E70L** Quartz-PLL Synthesizer Tuner
- P-E50** Auto-Return Turntable
- CD-E70** Compact Disc Player (optional)
- S-U1000** 2-Way Speaker System

SYSTEM DR-500

- High power output of 35 watts × 2 (DIN)
- 4 inputs: PHONO, TUNER, CD/AUX, TAPE
- 5-band graphic equalizer (100, 330Hz, 1k, 3.3k, 10kHz)
- Double cassette transports
- Normal/high speed dubbing
- Continuous relay play of two tapes
- Mic mixing with a source program
- Dolby B noise reduction system for low tape noise
- FM interstation noise muting
- 3-band radio reception: FM, MW and LW
- Convenient auto-return record playback
- Low-mass straight tonearm for better tracking
- Two-way speaker systems with 165mm woofers
- CD player (optional) with 3-beam laser pickup, random programming of up to 16 tracks, auto spacing and 3-way repeat

SPECIFICATIONS

DA-E50 [AMP] THD: 0.5% (at rated output)
 Freq. Response: 10—50,000Hz S/N Ratio: 90dB
[CASSETTE DECK] Wow & Flutter: 0.12% (WRMS)
 S/N Ratio: 64dB (Dolby "B" on)
 Dimensions (W × H × D): 380 × 222 × 301mm Weight: 5.9kg
T-E50L FM Sensitivity: 10.8dBf/0.9μV (DIN)
 Dimensions (W × H × D): 380 × 67 × 227mm Weight: 1.7kg
P-E50 Wow & Flutter: 0.06% (WRMS)
 Dimensions (W × H × D): 380 × 98 × 365mm Weight: 2.9kg
CD-E70 THD: 0.003% S/N Ratio: 100dB (IEC-A-WTD)
 Dimensions (W × H × D): 380 × 82 × 313mm Weight: 3.6kg
S-U1000 Woofer: 165mm cone type
 Tweeter: 50mm cone type
 Dimensions (W × H × D): 226 × 368 × 192mm Weight: 3.2kg

• Design and specifications subject to change without notice for improvements.

• In some areas, only the 2-band FM/AM version is available.

Sansui

SANSUI ELECTRIC CO., LTD.
 14-1, IZUMI 2-CHOME, SUGINAMI-KU, TOKYO 168,
 JAPAN / TELEX: J28310 SANSUITK

SANSUI ELECTRONICS (U.K.) LTD.
 UNIT 10A, LYON INDUSTRIAL ESTATE, ROCKWARE AVENUE, GREENFORD,
 MIDDX UB6, OAA, ENGLAND/TELEX: 895-2103 (SANSUI G)

Printed in Japan (60803K) DR-UK) Code No. AT-2700