

TEAC

CD Micro Component HR-X101



New Generation CD Micro Component System for Hi-Res Era

CD Receiver employs PC Streaming, CD Player, FM Tuner, and Bluetooth Connection

Hi-Res Audio Streaming from PC/Mac via USB Cable

Up-conversion to 24-bit/192kHz from CD, USB and Bluetooth®



Reference 101



HR-X101 CD Micro Component System



New Generation CD Micro Component System for Hi-Res Era.

■ Features at-a-glance

- Hi-Res Audio Streaming from PC/Mac via USB Cable
- Slot-in CD Drive supports MP3 and WMA (CD-DA, CD-R/RW)
- Built-in FM Tuner supports RDS (UK/Europe model only)
- Bluetooth® Wireless Connection with aptX® High-quality Playback from Smartphone/Tablet
- Up-convert to 192kHz from any source except FM radio
- HR Loudness Circuit for Stunning Bass Sound
- 26 Watts + 26 Watts Output Power by Energy-efficient Class-D Amplifier
- Small Footprint and All-aluminum Enclosure
- Ultra-compact Bookshelf Speakers with Gloss Cherry Wood Finish supports up to 40kHz
- Free Hi-Res Playback Software for Windows/Mac are Available



Amplifier Unit (CR-H101)

- | | | | |
|--------------------|---|------------------|-------------------------------------|
| ● Input Source | USB, CD, FM, optical digital, Bluetooth®, analog line | ● FM Frequency | 76.0MHz ~ 108.0MHz (Wide FM Range) |
| ● USB Input | USB-B terminal × 1 (max PCM 192kHz/24bit) | ● Supp. Media | CD-DA, CD-R, CD-RW |
| ● Digital Input | Optical TOS-link × 1 (max PCM 192kHz/24bit) | ● File formats | MP3, WMA |
| ● Analog Input | RCA/Cinch x 1 pair | ● Bluetooth® : | Version 3.0 Class2, aptX®, AAC, SBC |
| ● Speaker Output | 26W + 26W (max) , 20W + 20W (rated)
Screw-type x1 set | ● Freq. Response | 20Hz ~ 45,000Hz (-5dB) |
| ● Headphone Output | 80mW + 80mW (32Ω load, 1kHz)
3.5mm jack x1 | ● THD | 0.02% (1kHz, 4Ω, 1W) |
| ● Subwoofer Input | RCA/Cinch x1 | ● SNR | 90dB |
| ● Accessories: | (CR-H101) : Power Cord, Remote Control (RC-1324), AAA Batteries x2, FM Antenna, Owner's manual
(LS-101HR) : Speaker Cable (2m) , Silicone Feet x 8, Owner's manual | ● Op. Power | AC 220-240V, 50Hz |
| | | ● Dimensions | 182 × 93 × 221mm (W×H×D) |
| | | ● Weight | 2.2 kg |

Speakers (LS-101HR)

- Type: 2-way 2-speakers, Rear Bass-reflex
- Tweeter: 20mm Balance Dome
- Woofer: 70mm Cone
- Impedance: 4 Ω
- Handling Power: 25W (Rated), 35W (Maximum)
- Sensitivity: 86dB/W/0.5m
- Frequency Range: 65Hz ~ 40,000Hz
- Dimensions: 116 × 182 × 167 mm (W×H×D)
- Weight: 2.0kg



Rear View

TEAC®

TEAC CORPORATION
1-47, Ochiai, Tama-shi, Tokyo 206-8530, Japan
Phone: 042-356-9156 teac.jp

TEAC AMERICA INC.
1834 Gage Road, Montebello, CA 90640, U.S.A.
Phone: 323-726-0303 audio.teac.com

TEAC AUDIO EUROPE
Gutenberg Str. 3, 82178 Puchheim, Germany
Phone: +49-8142-4208-141 www.teac-audio.eu