New model information

DRA-CX3 Stereo Receiver

DCD-CX3 SC-CX303 CD/Super Audio CD Player

Speaker System

DENON

Beautiful to Hear and See, A Tactile Quality that's Wonderful to Behold.

Complete attention to detail not only for sound but also for design, materials, parts; the uncompromising skill and passion of a craftsman. Denon's CX3 delivers authenticity in sound required by the most discerning audiophiles.







64

Bullet points

Stereo Receiver DRA-CX3

- · Newly-developed amplifier circuitry, for improved power and clarity in music playback
- · Power unit capable of responding to sudden bursts of sound
- · Highly precise electronic volume
- · Separate power supplies and ground circuits for each stage
- Short Signal Path Circuitry, to suppress signal degradation
- · Thoroughly vibration-resistant construction

CD/Super Audio CD Player DCD-CX3

- · Newly-developed mechanism to accurately read information from the disc
- AL24 Processing, to dramatically enhance the music listening experience
- · Highly reliable DAC master clock design
- · Separate digital and analog transformers, for stable power supply and improved music playback performance

- · Pure Direct mode, for the enjoyment of pure music
- High-accuracy D/A converter

MP3

· Vibration-resistant construction

Speaker System SC-CX303

- Newly-developed 13cm D.D.L. cone woofer units utilizing carbon fiber
- ·Soft dome tweeters, to realize a lustrous vocal sound
- · Crossover network, for uniform sound pressure and phase response
- · Unit frame made of non-magnetic diecast aluminium to keep sound clean
- · Cabinets made of 30mm MDF board with natural wood sliced veneer and inlaid work
- · Born from European sound design and Denon collaboration

Other features

DRA-CX3

- MM/MC phono equalizer
- · Large speaker terminals made of gold-plated, machined brass, newly developed to also accommodate ultra-thick speaker cables
- · Gold-plated, machined brass input terminals with 18cm pitch (for CD)
- Slim system remote controller designed for ease of use and tasteful appearance
- Built-in AM/FM tuner
- Versatile connection environment for enjoying music from records, an iPod®, and various other sources

DCD-CX3

- · Plays MP3 and WMA files recorded on CD-R/RW discs
- · Gold-plated, machined brass input terminals with 18cm pitch (for CD), enabling upgrades in sound quality using high-class audio RCA pin cables
- · Optical digital output to accommodate connection of a digital recording device
- · Slim system remote controller designed for ease of use and tasteful appearance

SC-CX303

ė

۲

R EMMER

10

÷ O

89

0

10

01

0 -0.

- Rear duct to realize deep, transparent sound
- · Large speaker terminals made of gold-plated, machined brass, a Denon original
- · Parts strictly selected for high sound quality
- Includes slip-resistant natural cork

Terminals: DRA-CX3 PHONO IN x 1 CD x 1 L NE 1 x 1 L NE 2 x 1 L NE 3 (PB) x 1 OUT L NE 3 (REC) x 1 Others Dock control x 1 Tuner antenna AM/FM x 1 Main Specifications: DRA-CX3 Power amplifier section Rated output 75 W + 75 W (8 ohms, DIN, THD 0 07 %) 150 W + 150 W (1 kHz, 4 ohms, THD 0.7%) Preamplifier section IS ms 1V/47 Ηz:±

Input sensitivity/impedance	PHONO (MM): 2 5mV/47kohms PHONO (MC): 0.2 mV/100 ohm CD, LINE1, LINE2, LINE3 : 130 m ¹ kohms
Tone control	Bass 100 Hz : ±8 dB Treble 10 kH 8 dB
FM section	
Tuning frequency range	87.5 - 107 9 MHz
Usable sensitivity	1.5 µV (10 3 dBf)
AM section	
Tuning frequency range	520 - 1710 kHz
Usable sensitivity	20 µV
General	
Power supply	AC 120 V, 60 Hz
Dimensions (W x H x D)	300 x 80 x 341 mm
Weight	5.5 kg

Terminals: DCD-CX3 OUT Analog x 1 Digital coaxial x 1 Digital optical x 1

Main Specifications: DCD-CX3

	Super Audio CD	CD
Channels	2 channels	2 channels
Frequency response	2Hz-50kHz	2Hz-20kHz
Dynamic range	109dB	100 dB
Signal-to-noise ratio	112 dB	118 dB
Output voltage: Unbalanced	2.0V (10kΩ)	2 0V (10kΩ)
D gital output : Coaxial	-	0 5Vp-p/75Ω
: Optical	-	-1521dbm
Power supply	AC 120 V, 60 Hz	
Dimensions (W x H x D)	300 x 80 x 310 mm	
Weight	eight 7.0 kg	

Main Specifications: SC-CX303 Туре 2-way, 2-speakers Reflex box / Low-leakage-flux Drivers 13 cm cone bass-mid x1 2 5cm soft dome high range x1 Frequency range 35 Hz - 60 kHz Crossover frequency 3 kHz 100W (EC), 200W (PEAK) Max. input Input impedance 6 ohms Dimensions (W x H x D) 182 x 296 x 293 mm Weigt (kg/unit) 8.7 kg

*Design and specifications are the subject to change without notice. *Super Audio CD is a registered trademark of Sony and Philips. *IPod® is a trademark of Apple Inc., registered in the U.S. and other countries. *Windows Media is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.

