

KD-2033



SPECIFICATIONS

MOTOR and TURNTABLE

Drive System	Belt drive system
Motor	4-pole synchronous motor
Turntable Platter	12 inch (30 cm) diameter aluminum alloy diecast
Speeds	2 speeds, 33-1/3 and 45 rpm.
Wow and Flutter	Less than 0.06% (WRMS)
Signal to Noise	More than 49 dB

TONEARM

Type	Static-balance type, S-shaped pipe arm EIA plug-inconnector
Effective Arm Length	8-7/16 inch (215 mm)
Over-Hang	3/8 inch (9.5 mm)
Tracking Error	±1.5 degree
Stylus Pressure	
Variable Range	0 to 4 grams
Usable Cartridge Weight	4 to 10 grams

CARTRIDGE (Only for U,X,M type)

Type	Moving magnet type (V-39MKII)
Frequency Response	20~20,000 Hz
Channel Separation	More than 25 dB (at 1000 Hz)
Output Voltage	3 mV (5 cm/sec at 1,000 Hz)
Output Balance	1.5 dB (5 cm/sec at 1,000 Hz)
Load Impedance	50 k ohms
Stylus	0.5 mil diamond
Stylus Pressure	2±0.25 grams
Compliance	7 × 10 ⁻⁶ cm/dyne

SPECIAL MECHANISM

(Additional Feature)	Auto-return Auto-cut Pause elevation (variable speed) Return speed adjusting mechanism Anti-skating device Stylus pressure direct- readout counter Insulator Free-stop action dust cover
----------------------	--

ACCESSORIES

(Supplied)	EP adapter Motor lubricating oil Over-hang gauge Motor pulley and screw driver (only for M.U.W type)
------------	--

POWER

CONSUMPTION 11 watts

DIMENSIONS

W 18-7/8 inch (480 mm)
D 14-7/16 inch (367 mm)
H 6-7/8 inch (175 mm)

WEIGHT

13.2 lbs (6 kg)

POWER

REQUIREMENT

AC 120V, 60 Hz (K.P. type)
AC 220V, 50 Hz (L type)
AC 220V~240V, 50 Hz
(T.X.S type)
AC 110~120/220~240V,
50/60 Hz (M.U.W type)