

KR-6400 SPECIFICATIONS

FM TUNER SECTION

Frequency Range	88 MHz to 108 MHz
Usable Sensitivity (IHF)	87.5 MHz to 108 MHz (FTZ approved) 1.9 μ V
Quieting Slope	5 μ V 48 dB, 10 μ V 60 dB, 50 μ V 68 dB
Frequency Response	20 Hz - 15,000 Hz ± 0.5 dB
Harmonic Distortion	0.3% Mono (at 400 Hz 100% modulation) 0.5% Stereo (at 400 Hz 100% modulation)
Signal to Noise Ratio	68 dB at 1 mV input
Image Rejection	70 dB
Selectivity (IHF ALT channel)	65 dB
IF Rejection	90 dB
Spurious Signal Rejection	90 dB
AM Suppression	70 dB
Capture Ratio	1.5 dB
Stereo Separation	35 dB at 1,000 Hz 27 dB at 10,000 Hz
Sub Carrier Suppression	60 dB
Antenna Impedance	300 ohms balanced & 75 ohms unbalanced

AM TUNER SECTION

Usable Sensitivity (IHF)	18 μ V
Signal to Noise Ratio	45 dB at 1 mV input
Image Rejection	60 dB
Selectivity (IHF)	30 dB
IF Rejection	40 dB
Antenna	Built-in ferrite bar antenna, External antenna terminals

MAIN-AMPLIFIER SECTION

RMS Power Output	45 watts x 2 into 8 ohms at 20 Hz - 20,000 Hz
Both Channels Driven	52 watts x 2 into 8 ohms at 1,000 Hz 65 watts x 2 into 4 ohms at 1,000 Hz
Dynamic Power Output	160 watts into 8 ohms 240 watts into 4 ohms
Total Harmonic Distortion	0.3% at rated power into 8 ohms 0.07% at 1/2 rated power into 8 ohms at 1,000 Hz
Intermodulation Distortion	0.3% at rated power into 8 ohms
(60 Hz : 7 kHz = 4 : 1)	0.07% at 1/2 rated power into 8 ohms
Power Bandwidth	10 Hz - 30,000 Hz
Signal to Noise Ratio at 50 mW	55 dB
Damping Factor	50 at 8 ohms
Speaker Impedance	Accept 4 ohms to 16 ohms

PRE-AMPLIFIER SECTION

Input Sensitivity & Impedance	
Phono 1	2.5 mV, 50 K ohms
Phono 2	2.5 mV, 50 K ohms
AUX	150 mV, 80 K ohms
Tape Play A, B	150 mV, 80 K ohms
Mic	2.5 mV, 50 K ohms
Maximum Input Voltage (rms)	
Phono 1, 2	120 mV T.H.D. 0.3% at 1,000 Hz
Signal to Noise Ratio (IHF A CURVE)	
Phono 1, 2	70 dB
AUX	90 dB
Tape Play A, B	90 dB
Mic	65 dB
Output Voltage and Impedance	
Tape Rec. A, B (Pin)	150 mV 100 ohms
(Din Connector)	30 mV 80 K ohms
Frequency Response	
Phono 1, 2	RIAA Standard curve ± 1 dB
AUX, Tape Play	10 Hz - 40,000 Hz ± 1 dB
Tone Controls	
Bass	± 10 dB at 100 Hz
Treble	± 10 dB at 10,000 Hz
Loudness Control (-30 dB)	+8 dB at 100 Hz, +5 dB at 10,000 Hz
Low Filter 100 Hz	-8 dB
High Filter 10,000 Hz	-10 dB

GENERAL

Switches	
Speaker Selector	OFF, A, B, C, A + B, A + C
Input Selector	AM-FM-PHONO 1-PHONO 2-AUX-MIC
Mode	LEFT-RIGHT-STEREO-REV-MIX
Tape Monitor	SOURCE MON-B MON-A PLAY (A \rightarrow B) -SOURCE-B PLAY-A MON (B \rightarrow A)
Others	LOW FILTER, HIGH FILTER, FM MUTING LOUDNESS, MIC JACK, PHONE JACK
AC Outlet	Switched 1, Unswitched 2
Power Consumption	340 watts at full power 40 watts at no signal
Dimensions	W 18-15/16" (480mm), H 5-15/16" (151mm) D 13-9/16" (344mm)
Weight	29.8 lbs. (13.5 kg)