SBCRU980

Extreme colors, ultimate control

The ultimate control solution for your home and all your entertainment devices, fully customizable to the needs of you and your family.

Single control solution for any device, any brand

- Extensive infrared code database for any device or brand
- · Convenient IR learning from another remote by pointing to it
- Radio frequency works through walls and from other rooms
- Additional functionality through future software upgrades

Advanced graphical capabilities

- Attractive and easy-to-read touchscreen color LCD display
- Alpha blending allows see-through buttons and backgrounds
- Create transparent background around buttons

Great convenience

- · Multiple commands blended into one-touch control
- · LCD screen has backlighting for convenience in the dark
- Pick-up sensor activates the remote control when picked up
- · Timer functionality starts functions, even when you're out
- Select the language of the user interface







PHILIPS

Touchscreen remote control

Technical specifications

Picture/Display

- Backlight
- . Backlight color: Blue
- Diagonal screen size (inch): 3.8 in
- Display colors: 65,536 Resolution: 320 x 240 pixels
- Touch panel

Infrared Capabilities

- Operating distance: 33 ft (10 m)
- Learning IR codes
- Learning frequency range: Up to 78 kHz and 455 Dimensions kHz
- Transmitting LEDs: 4
- Universal IR code database
- Number of brands in database: Over 1100

RF Capabilities

- Adresses (ID's): 16
- Channels: 4
- Communication: I-way
- Frequency (MHz): 433

Customisation

- Editor application on PC: ProntoProEdit NG
- · On screen customisation
- Full screen configurability
- Transparency
- Alpha-blending
- Macros: Up to 250 steps

Convenience

- Automatic power off
- · Clock with calendar
- Cradle/ docking station
- Cursor key
- Gentle fade out of light
- Hard buttons

- · Pick up sensor
- Multi language: GB, D, F, E, NL
- Programmable timers: 20

Connectivity

• USB: USB 1.1

Power

- Mains power: 230V (+/-10/-15%)/50Hz
- · Charging time: Max 3 hrs hr

- Master carton quantity: I
- Product dimensions ($W \times H \times D$): 92 x 153 x 27 mm
- Product weight: 0.250 kg
- Temperature Range (Operation): +5°C/+45°C

System Specifications

- CPU: Mitsubishi 32 bit
- CPU speed: 20 Mhz
- Flash memory size: 32 MB

System Requirements

- CD-ROM drive
- . Hard disk space: 75 MB
- PC OS: Windows 98 SE, 2000, ME, XP
- RAM memory: 64 MB ٠
- USB: Free USB port

Accessories

- Printed User Guide
- Batteries: Ni-MH battery pack **Docking Station**
- USB cable
- User Guide on CD-ROM
- Warranty Card

SBCRU980/00

Product highlights

Universal IR code database

A universal IR code database refers to a library of infrared codes built-in to a particular remote. This feature allows a remote to control your equipment without needing to learn individual signals. Select the correct infrared code sets in the database for the devices you want to control, to enable control of virtually every audio/video system element on the market today - regardless of model or brand.

Learning functionality

Learning functionality refers to the process through which a remote control captures and stores infrared signals from other remotes for later use. When device codes are not included in the on-board database, they can always be learned from the original remote, simply by pointing to it.

One-touch convenience

One-touch convenience allows you to perform multiple commands with one press of a button via a macro. A macro combines a string of pre-programmed commands under one single button. Therefore, it simply takes one button press to execute a series of functions.

Alpha blending

Alpha blending is used to create the effect of transparency. It does this by combining a translucent foreground with a background colour to create an inbetween blend.

Radio frequency

A radio technology that allows you to control components not in direct line-of-sight, such as through walls or other obstacles. There are two types of RF used in remote controls: RF to component, and RF to infrared.



Version: 40

12 NC: 9082 100 02432 EAN: 87 10895 79512 8

Date of issue 2005-05-11

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners. © 2005 Koninklijke Philips Electronics N.V. All Rights reserved. www.philips.com

