

AV RECEIVER

RX-V2065/HTR-6295

SERVICE MANUAL

Note:

When IC513 of GUI P.C.B. or GUI P.C.B. is replaced, the network function of this unit will not operate properly without additional setting.

In such case, report the serial number of this unit to the following e-mail address.

Yamaha Corporation will reply providing the setting procedure to make the network function of this unit operate properly.

E-mail: ycav-ysiss@gmx.yamaha.com

IMPORTANT NOTICE

This manual has been provided for the use of authorized YAMAHA Retailers and their service personnel.

It has been assumed that basic service procedures inherent to the industry, and more specifically YAMAHA Products, are already known and understood by the users, and have therefore not been restated.

WARNING: Failure to follow appropriate service and safety procedures when servicing this product may result in personal injury, destruction of expensive components, and failure of the product to perform as specified. For these reasons, we advise all YAMAHA product owners that any service required should be performed by an authorized YAMAHA Retailer or the appointed service representative.

IMPORTANT: The presentation or sale of this manual to any individual or firm does not constitute authorization, certification or recognition of any applicable technical capabilities, or establish a principle-agent relationship of any form.

The data provided is believed to be accurate and applicable to the unit(s) indicated on the cover. The research, engineering, and service departments of YAMAHA are continually striving to improve YAMAHA products. Modifications are, therefore, inevitable and specifications are subject to change without notice or obligation to retrofit. Should any discrepancy appear to exist, please contact the distributor's Service Division.

WARNING: Static discharges can destroy expensive components. Discharge any static electricity your body may have accumulated by grounding yourself to the ground buss in the unit (heavy gauge black wires connect to this buss).

IMPORTANT: Turn the unit OFF during disassembly and part replacement. Recheck all work before you apply power to the unit.

CONTENTS

TO SERVICE PERSONNEL	2-3
FRONT PANELS	3-4
REAR PANELS	5-7
REMOTE CONTROL PANELS	8
SPECIFICATIONS	9-15
INTERNAL VIEW	16
SERVICE PRECAUTIONS	16
DISASSEMBLY PROCEDURES	17-19
UPDATING FIRMWARE	20-29
SELF-DIAGNOSTIC FUNCTION	30-66
CONFIRMATION OF IDLING CURRENT OF AMP UNIT	67

DISPLAY DATA	68-69
IC DATA	70-93
PIN CONNECTION DIAGRAMS	94-97
BLOCK DIAGRAMS	98-101
PRINTED CIRCUIT BOARDS	102-122
SCHEMATIC DIAGRAMS	123-139
REPLACEMENT PARTS LIST	141-156
REMOTE CONTROL	157-160
ADVANCED SETUP	161-162



このサービスマニュアルは、エコマーク認定の再生紙を使用しています。
This Service Manual uses recycled paper.

101147

Copyright © 2009 YAMAHA CORPORATION All rights reserved.
This manual is copyrighted by YAMAHA and may not be copied or redistributed either in print or electronically without permission.



YAMAHA

YAMAHA CORPORATION
P.O.Box 1, Hamamatsu, Japan

'09.08

RX-V2065/HTR-6295

■ TO SERVICE PERSONNEL


1. Critical Components Information

Components having special characteristics are marked Δ and must be replaced with parts having specifications equal to those originally installed.

2. Leakage Current Measurement (For 120V Models Only)

When service has been completed, it is imperative to verify that all exposed conductive surfaces are properly insulated from supply circuits.

- Meter impedance should be equivalent to 1500 ohms shunted by 0.15 μ F.



- Leakage current must not exceed 0.5mA.
- Be sure to test for leakage with the AC plug in both polarities.



For U model

“CAUTION”

“F6002: FOR CONTINUED PROTECTION AGAINST RISK OF FIRE, REPLACE ONLY WITH SAME TYPE 10A, 125V FUSE.”

For C model

CAUTION

F6002: REPLACE WITH SAME TYPE 10A, 125V FUSE.

ATTENTION

F6002: UTILISER UN FUSIBLE DE RECHANGE DE MÊME TYPE DE 10A, 125V.

WARNING: CHEMICAL CONTENT NOTICE!

This product contains chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

DO NOT PLACE SOLDER, ELECTRICAL/ELECTRONIC OR PLASTIC COMPONENTS IN YOUR MOUTH FOR ANY REASON WHATSOEVER!

Avoid prolonged, unprotected contact between solder and your skin! When soldering, do not inhale solder fumes or expose eyes to solder/flux vapor!

If you come in contact with solder or components located inside the enclosure of this product, wash your hands before handling food.

About lead free solder

All of the P.C.B.s installed in this unit and solder joints are soldered using the lead free solder.

Among some types of lead free solder currently available, it is recommended to use one of the following types for the repair work.

- Sn + Ag + Cu (tin + silver + copper)
- Sn + Cu (tin + copper)
- Sn + Zn + Bi (tin + zinc + bismuth)

Caution:

As the melting point temperature of the lead free solder is about 30°C to 40°C (50°F to 70°F) higher than that of the lead solder, be sure to use a soldering iron suitable to each solder.

WARNING: Lithium batteries

CAUTION

Danger of explosion if battery is incorrectly replaced.
Replace only with the same or equivalent type.

WARNING: Lithium batteries are dangerous because they can be exploded by improper handling. Observe the following precautions when handling or replacing lithium batteries.

- Leave lithium battery replacement to qualified service personnel.
- Always replace with batteries of the same type.
- When installing on the PC board by soldering, solder using the connection terminals provided on the battery cells. Never solder directly to the cells. Perform the soldering as quickly as possible.
- Never reverse the battery polarities when installing.
- Do not short the batteries.
- Do not attempt to recharge these batteries.
- Do not disassemble the batteries.
- Never heat batteries or throw them into fire.

ADVARSEL!

Lithiumbatteri –Eksplodingsfare ved fejlagtig håndtering.
Udskiftning må kun ske med batteri af samme fabrikat og type. Levér det brugte batteri tilbage til leverandøren.

VARNING

Explosionsfara vid felaktigt batteribyte. Använd samma batterityp eller en ekvivalent typ som rekommenderas av apparattillverkaren. Kassera använt batteri enligt fabrikantens instruktion.


VAROITUS

Paristo voi räjähtää, jos se on virheellisesti asennettu.
Vaihda paristo ainoastaan laitevalmistajan suosittelemaan tyyppiin. Hävitä käytetty paristo valmistajan ohjeiden mukaisesti.


FRONT PANELS

Top view

U model




C, R, T, K, A, B, G, E, F, L models




Front view


RX-V2065 (U model)




RX-V2065 (C, R, K, A, B, G, E, F, L models)



RX-V2065 (T model)




HTR-6295 (C model)




REAR PANELS


RX-V2065 (U model)




RX-V2065 (C model)




RX-V2065 (R model)




RX-V2065 (T model)




RX-V2065 (K model)




RX-V2065 (A model)




RX-V2065 (B, G, E, F models)



RX-V2065 (L model)




HTR-6295 (C model)



■ REMOTE CONTROL PANELS


RAV296

(U model)




RAV297

(C, R, A, L models)




RAV298

(T, K, B, G, E, F models)



RAV38

(U, C, R, T, K, A, B, G, E, F, L models)



SPECIFICATIONS

Audio Section

Minimum RMS Output Power (Power Amp. Section)

(20 Hz to 20 kHz, 0.08 % THD, 8 ohms)

FRONT L/R	130 W + 130 W
CENTER	130 W
SURROUND L/R	130 W + 130 W
SURROUND BACK L/R	130 W + 130 W

Maximum Power (JEITA) (1 kHz, 10 % THD, 8 ohms)

[R, T, K, A, L models]

FRONT L/R	175 W + 175 W
CENTER	175 W
SURROUND L/R	175 W + 175 W
SURROUND BACK L/R	175 W + 175 W

MAX. Power Per Channel (1 kHz, 0.7 % THD, 4 ohms)

[B, G, E, F models]

FRONT L/R	180 W + 180 W
CENTER	180 W
SURROUND L/R	180 W + 180 W
SURROUND BACK L/R	180 W + 180 W

IEC Power (1 kHz, 0.08 % THD, 8 ohms)

[B, G, E, F models]

FRONT L/R	130 W + 130 W
-----------	---------------

Dynamic Power Per Channel (IHF)

FRONT L/R drive

(8 / 6 / 4 / 2 ohms)	160 / 200 / 260 / 330 W
----------------------	-------------------------

Dynamic Headroom [U, C models]

8 ohms	0.9 dB
--------	--------

Damping Factor

(20 Hz to 20 kHz, 8 ohms, SPEAKER-A)

FRONT L/R	100 or more
-----------	-------------

Input Sensitivity/Input Impedance

(1 kHz, 100 W/8 ohms)

PHONO (MM)	3.5 mV / 47 k-ohms
AV5 etc.	200 mV / 47 k-ohms
MULTI CH INPUT	
FRONT L/R, CENTER, SURROUND L/R, SURROUND BACK L/R, SUBWOOFER	
	200 mV / 47 k-ohms

Maximum Input Signal (1 kHz)

PHONO (MM) (0.1 % THD)	60 mV or more
AV5 etc. (Effect ON) (0.5 % THD)	2.3 V or more

Output Level/Output Impedance

REC OUT	200 mV/1.2 k-ohms
PRE OUT	1 V/1.2 k-ohms
SUBWOOFER (2 ch stereo and FRONT SP: small)	
	1 V/1.2 k-ohms
ZONE2, 3 OUT	200 mV/1.4 k-ohms

Headphone Jack Rated Output/Output Impedance

AV5 etc. input (1 kHz, 50 mV, 8 ohms)	100 mV/470 ohms
---------------------------------------	-----------------

Frequency Response

AV5 etc., FRONT (10 Hz to 100 kHz)	+0/-3 dB
------------------------------------	----------

RIAA Equalization Deviation

PHONO (MM)	0 ±0.5 dB
------------	-----------

Total Harmonic Distortion

PHONO (MM) to REC OUT (20 Hz to 20 kHz, 1 V)	
	0.02 % or less
AV5 etc. (PURE DIRECT) to FRONT SP OUT (20 Hz to 20 kHz, 50 W)	
8 ohms	0.06 % or less

Signal to Noise Ratio (IHF-A network)

PHONO (MM) to REC OUT (Input shorted 5 mV)

U, C, R, T models	86 dB or more
K, A, B, G, E, F, L models	81 dB or more
AV5, etc. (PURE DIRECT) to SP OUT (Input shorted 250 mV)	
	100 dB or more

Residual Noise (IHF-A network)

FRONT L/R to SP OUT	150 µV or less
---------------------	----------------

Channel Separation (1 kHz / 10 kHz)

PHONO (Input shorted)

	60 dB or more / 55 dB or more
AV5, etc. (Input 5.1 k-ohms shorted)	
	60 dB or more / 45 dB or more

Volume Control

MUTE / -80 dB to +16.5 dB / 0.5 dB step	
---	--

Tone Control Characteristics

FRONT L/R

Bass	
Boost/Cut	±10 dB/2 dB, step 50 Hz
Turnover frequency	350 Hz
Treble	
Boost/Cut	±10 dB/2 dB, step 20 kHz
Turnover frequency	3.5 kHz

Filter Characteristics

FRONT, CENTER, SURROUND, SURROUND BACK small (H.P.F.)

fc=40/60/80/90/100/110/120/160/200 Hz, 12 dB/oct.	
---	--

SUBWOOFER small (L.P.F.)

fc=40/60/80/90/100/110/120/160/200 Hz, 24 dB/oct.	
---	--

Video Section

Video Signal Type (Gray back)

Gray back

U, C, R, K models	NTSC
T, A, B, G, E, F, L models	PAL

Video conversion

	NTSC/PAL
--	----------

Composite Video Signal Level

	1 Vp-p / 75 ohms
--	------------------

S-Video Signal Level [B, G, E, F models]

Y	1 Vp-p / 75 ohms
C	0.286 Vp-p / 75 ohms

Component Video Signal Level

Y	1 Vp-p / 75 ohms
Cb/Cr	0.7 Vp-p / 75 ohms

Video Maximum Input Level

VIDEO CONVERSION OFF	1.5 Vp-p or more
----------------------	------------------

Video Signal to Noise Ratio

	50 dB or more
--	---------------

Monitor Out Frequency Response

(VIDEO CONVERSION OFF)

Component video signal level	5 Hz to 60 MHz, -3 dB
------------------------------	-----------------------

FM Section

Tuning Range

U, C models	87.5 to 107.9 MHz
R, L models	87.5 to 108.0 MHz / 87.50 to 108.00 MHz
T, K, A, B, G, E, F models	87.50 to 108.00 MHz

50 dB Quietening Sensitivity (IHF) (1 kHz, 100 % MOD.)

Mono	3 µV (20.8 dBf)
------	-----------------

Signal to Noise Ratio (IHF)

Mono	74 dB
Stereo	70 dB
HD (U model)	80 dB

Harmonic Distortion (1 kHz)

Mono	0.3 %
Stereo	0.3 %
HD (U model)	0.03 %

Antenna Input

..... 75 ohms unbalanced

■ AM Section**Tuning Range**

U, C models	530 to 1,710 kHz
R, L models	530 to 1,710 kHz / 531 to 1,611 kHz
T, K, A, B, G, E, F models	531 to 1,611 kHz

Antenna Loop antenna

■ General**Power Supply**

U, C models	AC 120 V, 60 Hz
R model	AC 110/120/220/230–240 V, 50/60 Hz
T model	AC 220 V, 50 Hz
K model	AC 220 V, 60 Hz
A model	AC 240 V, 50 Hz
B, G, E, F models	AC 230 V, 50 Hz
L model	AC 220/230–240 V, 50/60 Hz

Power Consumption

U, C models	450 W / 560 VA
R, T, K, A, B, G, E, F, L models	450 W

Standby Power Consumption (reference data)

HDMI control: OFF / Standby through: OFF / RS-232C: OFF	0.2 W or less
HDMI control: ON / Standby through: ON / Network Standby: ON	5.6 W or less
HDMI control: ON / Standby through: ON / Network Standby: ON / Repeat	10.6 W or less

Maximum Power Consumption [R, L models]

..... 680 W

Dimensions (W x H x D)

..... 435 x 171 x 365 mm (17-1/8" x 6-3/4" x 14-3/8")

Weight

..... 12.4 kg (27.4 lbs.)

Finish

[RX-V2065]	
Black color	U, C, R, T, K, A, B, G, E, F, L models
Titanium color	R, G, E, F, L models

[HTR-6295]

Black color	C model
-------------------	---------

Accessories

Remote control	x 1
Simplified remote control	x 1
Battery (R03, AAA, UM-4)	x 2
Lithium battery (CR2025)	x 1
Indoor FM antenna (1.4 m)	x 1
AM loop antenna (1.2 m) (U model)	x 1
(1.0 m) (C, R, T, K, A, B, G, E, F, L models)	x 1
Optimizer microphone (6.0 m)	x 1
VIDEO AUX input cover	x 1
Power cable (2.0 m)	x 1

* Specifications are subject to change without notice due to product improvements.

U *U.S.A. model*
 C *Canadian model*
 R *General model*
 T *Chinese model*
 K *Korean model*
 A *Australian model*

B *British model*
 G *European model*
 E *South European model*
 F *Russian model*
 L *Singapore model*



Manufactured under license from Dolby Laboratories. Dolby, Pro Logic and the double-D symbol are trademarks of Dolby Laboratories.



DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademark of DTS, Inc. © 1996-2007 DTS, Inc. All Rights Reserved.



Neural Surround™ name and related logos are trademarks owned by Neural Audio Corporation.

iPod™

"iPod" is a trademark of Apple Inc., registered in the U.S. and other countries.



Fraunhofer Institut
Integrierte Schaltungen

MPEG Layer-3 audio coding technology licensed from Fraunhofer IIS and Thomson.



This receiver supports network connections.

Bluetooth™

Bluetooth is a registered trademark of Bluetooth SIG and is used by Yamaha in accordance with a license agreement.



"HDMI," the "HDMI" logo and "High-Definition Multimedia Interface" are trademarks, or registered trademarks of HDMI Licensing LLC.

x.v.Color

"x.v.Color" is a trademark of Sony Corporation.

SILENT™ CINEMA

"SILENT CINEMA" is a trademark of Yamaha Corporation.

SIRIUS
READY

((XM))
READY

XMHD
SURROUND-SOUND

XM Mini-Tuner

SIRIUS, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. and its subsidiaries. All rights reserved. **Service not available in Alaska and Hawaii.**

HD Radio


HD Radio™ Technology Manufactured Under License From iBiquity Digital Corp. U.S. and Foreign Patents. HD Radio™ and the HD Radio logo are proprietary trademarks of iBiquity Digital Corp.

Rhapsody

Rhapsody and the Rhapsody logo are registered trademarks of RealNetworks, Inc.

Windows XP, Windows Vista, Windows Media Audio, Windows Media Connect and Windows Media Player are either registered trademarks or trademarks of Microsoft corporation in the United States and/or other countries.

• DIMENSIONS



Unit: mm (inch)

• SCENE TEMPLATE

Name	BD/DVD	TV	CD	RADIO
INPUT	HDMI1	AV-1 (Component / Optical)	AV-3 (Video / Coaxial)	TUNER
Sound field mode	STRAIGHT	STRAIGHT	STRAIGHT	MUSIC ENHANCER 7ch Enhancer
IR code output	DVD Play	None	CD Power On / Play	None

• SOUND FIELD PARAMETERS

		Parameter																															
Category	Program	Decode Type	3D DSP: ON/OFF	DSP Level: -6dB to +3dB	Init. Delay: 1 to 99ms	Room Size: 0.1 to 2.0	Liveness: 0 to 10	Sur. Init. Delay: 1 to 49ms	Sur. Room Size: 0.1 to 2.0	Sur. Liveness: 0 to 10	SB. Init. Delay: 1 to 49ms	SB. Room Size: 0.1 to 2.0	SB. Liveness: 0 to 10	Rev. Time: 1.0 to 5.0s	Rev. Delay: 0 to 250ms	Rev. Level: 0 to 100%	Dialogue Lift: 0 to 5	Center Level: 0 to 100%	Surround L Level: 0 to 100%	Surround R Level: 0 to 100%	Sur.Back Level: 0 to 100%	Presence L Level: 0 to 100%	Presence R Level: 0 to 100%	Direct: Auto/Off	Effect Level: High/Low	Panorama: On/Off	Center Width: 0 to 7	Dimension: -3 to +3	Center Image: 0.0 to 1.0	FOCUS: 0 to 8	TruBass: 0 to 8	Initialize	
MOVIE	Standard	● *1	●	●				●	●	●	●	●	●				●															●	
	Spectacle	● *1	●	●	●	●		●	●		●	●					●															●	
	Sci-Fi	● *1	●	●	●	●		●	●		●	●					●															●	
	Adventure	● *1	●	●	●	●		●	●		●	●					●															●	
	Drama	● *1	●	●	●	●		●	●		●	●					●															●	
	Mono Movie		●	●	●	●	●							●	●	●	●															●	
	Sports		●	●	●	●		●	●		●	●					●															●	
	Action Game		●	●	●	●		●	●		●	●					●															●	
Roleplaying Game		●	●	●	●		●	●		●	●					●															●		
MUSIC	Hall in Munich		●	●	●	●	●										●															●	
	Hall in Vienna		●	●	●	●	●										●															●	
	Chamber		●	●	●		●							●	●	●	●															●	
	Cellar Club		●	●	●	●	●										●															●	
	The Roxy Theatre		●	●	●	●	●							●	●	●	●															●	
	The Bottom Line		●	●	●	●	●										●															●	
	Music Video		●	●	●	●		●	●		●	●					●															●	
STEREO	2ch Stereo																		●	●	●	○	●	●	●							●	
	7ch Stereo																		●	●	●	○	●	●								●	
MUSIC ENHANCER	Straight Enhancer																									●							●
	7ch Enhancer																									●							●
SUR. DECODE	Surround Decoder	● *2																									△	△	△	▲	■	■	●
STRAIGHT																																	

○ : The parameter to be used varies between when there is one surround pack and when there are two. On the display, the parameter value varies accordingly while the same parameter name appears.

△ : Setting is possible only when Pro Logic II x Music (Pro Logic II Music) is selected using decode type.

▲ : Setting is possible only when Neo:6 Music is selected using decode type.

■ : Setting is possible only when CS II Cinema/Music is selected using decode type.

*1 Decode Type

Decode Type	PL II x Movie	PL II when Surround Back is None.
	Neo:6 Cinema	

*2 Decode Type

Decode Type	Pro Logic	PL II when Surround Back is None.
	PL II x Movie	
	PL II x Music	
	PL II x Game	
	Pro Logic II z	PL II when Surround Back is None.
	Neo:6 Cinema	
	Neo:6 Music	
	Neural Sur.	(U model)


• SET MENU TABLE

MAIN MENU		SUB-MENU	PARAMETER	VALUE [INITIAL VALUE]	
1 • Speaker Setup					
1 Auto Setup (YPAO)	Extra Speaker Assignment			[Zone2] / Zone2 + Zone3 / Presence / None	
	EQ Type			[Natural] / Flat / Front	
	Start			[ENTER]: Start	
2 Manual Setup	A) Speaker Configuration	Extra Speaker Assignment		[Zone2] / Zone2 + Zone3 / Presence / None	
		LFE/Bass Out		Subwoofer / Front / [Both]	
		Front Speaker		Small / [Large]	
		Center Speaker		None / [Small] / Large	
		Surround L/R Speaker		None / [Small] / Large	
		Surround Back L/R Speaker		None / Large x 1 / Small x 1 / Large x 2 / [Small x 2]	
		Bass Crossover Frequency		40 / 60 / [80] / 90 / 100 / 110 / 120 / 160 / 200 Hz	
		Subwoofer Phase		[Normal] / Reverse	
	B) Speaker Level	Front L		-10.0 to +10.0 dB, [0 dB], 0.5 dB step	
		Front R			
		Center		-10.0 to +10.0 dB, [-1.0 dB], 0.5 dB step	
		Surround L			
		Surround R			
		Surround Back L			
		Surround Back R			
		Subwoofer		-10.0 to +10.0 dB, [0 dB], 0.5 dB step	
		Presence L			
		Presence R			
	C) Speaker Distance	Unit		meters (m) / [feet (ft)]	
		Front L		0.30 to 24.00 m, [3.00 m]	
		Front R			
		Center			
		Surround L		0.30 to 24.00 m, [2.40 m]	
		Surround R			
		Surround Back L			
		Surround Back R			
		Subwoofer			
		Presence L		0.30 to 24.00 m, [3.00 m]	
		Presence R			
		Front L			1.0 to 80.0 ft, [10.0 ft]
		Front R			
		Center			
		Surround L		1.0 to 80.0 ft, [8.0 ft]	
		Surround R			
		Surround Back L			
		Surround Back R			
		Subwoofer			
		Presence L		1.0 to 80.0 ft, [10.0 ft]	
		Presence R			
		D) Equalizer	EQ Type Select		Auto PEQ / [GEQ] / Off
			GEQ		* "GEQ" is available only when "EQ Type Select" is set to "GEQ".
	Front L		63 Hz 0 dB	-6.0 to +6.0 dB, [0 dB], 0.5 dB step
	Front R		160 Hz 0 dB	
	Center		400 Hz 0 dB	
	Sur. L		1 kHz 0 dB	
	Sur. R		2.5 kHz 0 dB	
	SBL		6.3 kHz 0 dB	
	SBR		16 kHz 0 dB	
	E) Test Tone		[Off] / On		
	2 • Sound Setup				
1 Dynamic Range			Min/Auto / STD / [Max]		
2 Lipsync	HDMI OUT1		0 to 240 ms, [0 ms], 1 ms step		
	HDMI OUT2				
	ANALOG MONITOR OUT				

MAIN MENU	SUB-MENU		PARAMETER	VALUE [INITIAL VALUE]
3 • Function Setup				
1 HDMI	HDMI Control		On / [Off]	
	Standby Through		On / [Off] * This menu is available only when “HDMI Control” is set to “Off”.	
	Audio Output		[Amplifier] / TV / Amplifier + TV * This menu is available only when “HDMI Control” is set to “Off”.	
	Resolution		[Through] / 480p (576p) / 720p / 1080i / 1080p	
	Aspect		[Through] / 16:9 / Smart Zoom	
2 Display	Dimmer		-4 to 0, [0]	
	Front Panel Display Scroll		[Continuous] / Once	
3 Volume	GUI Position		-5 to +5, [0]	
	Adaptive DRC		Auto / [Off]	
	Max Volume		-30.0 dB to +15.0 dB / [+16.5 dB], 5.0 dB step	
	Initial Volume		[Off] / Mute / -80.0 to +16.5 dB, 0.5 dB step	
4 Input Rename			Input is possible to 9 characters Input possible Character type Capital : A to Z Small : a to z Figure : 0 to 9 Space Marks : # * + , - . / : < > ? etc.	
5 Zone	Zone2/Zone3 Max. Volume		-30.0 dB to +15.0 dB / [+16.5 dB], 5.0 dB step	
	Zone2/Zone3 Initial Volume		[Off] / Mute / -80.0 to +16.5 dB, 0.5 dB step	
6 Network	IP Address	DHCP	[On] / Off	
		IP Address	xxx.xxx.xxx.xxx	
		Subnet Mask	* This menu is available only when “IP Address” is set to “DHCP On”.	
		Default Gateway		
		DNS Server (Primary)		
		DNS Server (Secondary)		
	MAC Address Filter		[Off] / On	
	MAC Address 1–10		xx : xx : xx : xx : xx : xx * This menu is available only when “MAC Address Filter” is set to “On”.	
	Network Standby		[Off] / On	
	Information	MAC Address	xx : xx : xx : xx : xx : xx	
		IP Address	xxx.xxx.xxx.xxx	
		Subnet Mask	xxx.xxx.xxx.xxx	
		Default Gateway	xxx.xxx.xxx.xxx	
		DNS Server (Primary)	xxx.xxx.xxx.xxx	
		DNS Server (Secondary)	xxx.xxx.xxx.xxx	
		Link Status	No Link	
		vTuner ID	xxxxxxxxxxx	
7 Rhapsody Information	Account Status			
	Sign In			
	Rhapsody Free Trial			
	Remove Account			
4 • DSP Parameter				
STEREO	7ch Stereo	Center Level	0 to 100 %	
		Surround L Level		
		Surround R Level		
		Surround Back Level		
		Initialize		
MUSIC ENHANCER	Straight Enhancer	Effect Level · High	[High] / Low	
		Initialize		
	7ch Enhancer	Effect Level · High	[High] / Low	
		Initialize		

MAIN MENU	SUB-MENU	PARAMETER	VALUE [INITIAL VALUE]
SURROUND DECODE	Surround Decoder	Decode Type Pro Logic	Pro Logic / PL Ilx Movie / PL Ilx Music / PL Ilx Game / Neo:6 Cinema / Neo:6 Music / Neural Sur. (U model)
		Pro Logic Initialize	
		PL Ilx Movie Initialize	
		PL Ilx Music Panorama	[Off] / On
		Center Width	0 to 7, [3]
		Dimension	-3 to [STD] to +3
		Initialize	
		PL Ilx Game Initialize	
		Neo:6 Cinema Initialize	
		Neo:6 Music Center Image	0.0 to 1.0, [0.3]
		Initialize	
		Neural Sur. Initialize	
MOVIE	Standard	Decode Type PL Ilx Movie	PL Ilx Movie / Neo:6 Cinema
		PL Ilx Movie [1], [4], [8], [11], [16]	
		Neo:6 Cinema [1], [4], [8], [11], [16]	
	Spectacle	Decode Type PL Ilx Movie	PL Ilx Movie / Neo:6 Cinema
		PL Ilx Movie [1], [3], [4], [7], [8], [16]	
		Neo:6 Cinema [1], [4], [8], [11], [16]	
	Sci-Fi	Decode Type PL Ilx Movie	PL Ilx Movie / Neo:6 Cinema
		PL Ilx Movie [1], [3], [4], [7], [8], [16]	
		Neo:6 Cinema [1], [3], [4], [7], [8], [16]	
	Adventure	Decode Type PL Ilx Movie	PL Ilx Movie / Neo:6 Cinema
		PL Ilx Movie [1], [3], [4], [7], [8], [16]	
		Neo:6 Cinema [1], [3], [4], [7], [8], [16]	
	Drama	Decode Type PL Ilx Movie	PL Ilx Movie / Neo:6 Cinema
		PL Ilx Movie [1], [3], [4], [7], [8], [16]	
		Neo:6 Cinema [1], [3], [4], [7], [8], [16]	
	Mono Movie	[1], [2], [6], [10], [13], [14], [15], [16]	
	Sports	[1], [3], [4], [7], [8], [16]	
	Action Game	[1], [3], [4], [7], [8], [16]	
	Roleplaying Game	[1], [3], [4], [7], [8], [16]	
MUSIC	Hall in Munich	[1], [2], [6], [10], [16]	
	Hall in Vienna	[1], [2], [6], [10], [16]	
	Chamber	[1], [2], [10], [13], [14], [15], [16]	
	Cellar Club	[1], [2], [6], [10], [16]	
	The Roxy Theatre	[1], [2], [6], [10], [13], [14], [15], [16]	
	The Bottom Line	[1], [2], [6], [10], [16]	
	Music Video	[1], [3], [4], [7], [8], [16]	
STEREO	2ch Stereo	Direct	[Auto] / Off
		Initialize	
	[1]	DSP Level	-6 to +3 dB, [0 dB]
	[2]	Initial Delay	1 to 99 ms
	[3]	P. Initial Delay	
	[4]	Sur. Initial Delay	1 to 49 ms
	[6]	Room Size	
	[7]	P. Room Size	0.1 to 2.0
	[8]	Sur. Room Size	
	[10]	Liveness	0 to 10
	[11]	S. Liveness	
	[13]	Reverb Time	1.0 to 5.0 s
	[14]	Reverb Delay	0 to 250 ms
	[15]	Reverb Level	0 to 100 %
	[16]	Initialize	
5 • Memory Guard			[Off] / On

INTERNAL VIEW



- ❶ OPERATION (2) P.C.B.
- ❷ OPERATION (9) P.C.B.
(R, T, K, A, B, G, E, F, L models)
- ❸ HD RADIO TUNER (U model)
- ❹ VIDEO (4) P.C.B.
- ❺ OPERATION (8) P.C.B.
- ❻ ACDC (1) P.C.B.
- ❼ MAIN (1) P.C.B.
- ❽ DIGITAL (3) P.C.B.
- ❾ VIDEO (9) P.C.B. (B, G, E, F models)
- ❿ AM/FM TUNER
(C, R, T, K, A, B, G, E, F, L models)
- ⓫ DIGITAL (1) P.C.B.
- ⓬ GUI P.C.B.
- ⓭ VIDEO (1) P.C.B.
- ⓮ MAIN (3) P.C.B. (R, L models)
- ⓯ VIDEO (3) P.C.B.
- ⓰ MAIN (2) P.C.B.
- ⓱ ACDC (2) P.C.B.
(U, C, T, K, A, B, G, E, F models)
- ⓲ MAIN (4) P.C.B.
- ⓳ POWER TRANSFORMER
- ⓴ VIDEO (6) P.C.B.
- ⓵ MAIN (6) P.C.B.
- ⓶ ACDC (3) P.C.B.
- ⓷ DIGITAL (2) P.C.B.
- ⓸ OPERATION (10) P.C.B.
- ⓹ OPERATION (4) P.C.B.
- ⓺ OPERATION (1) P.C.B.
- ⓻ OPERATION (5) P.C.B.
- ⓼ OPERATION (3) P.C.B.
- ⓽ OPERATION (6) P.C.B.

SERVICE PRECAUTIONS

Safety measures

- Some internal parts in this product contain high voltages and are dangerous.
Be sure to take safety measures during servicing, such as wearing insulating gloves.
- Note that positions indicated below are dangerous even after the power is turned off because an electric charge remains and a high voltage continues to exist there.
Before starting any repair work, perform discharge by connecting a discharge resistor (5k-ohms/10W) between terminals at following positions.
The time required for discharging is about 30 seconds.
C6006 on ACDC (1) P.C.B.
Refer to "PRINTED CIRCUIT BOARDS: ACDC (1) P.C.B."


■ DISASSEMBLY PROCEDURES

(Remove parts in the order as numbered.)

Disconnect the power cable from the AC outlet.

1. Removal of Top Cover

- Remove 4 screws (①), 5 screws (②) and screw (③). (Fig. 1)
- Slide the top cover rearward to remove it. (Fig. 1)



2. Removal of Front Panel and Sub-Chassis Unit

- Remove screw (④) and then remove the center frame. (Fig. 1)
- Remove 2 knobs. (Fig. 1)
- Remove 6 screws (⑤) and then remove the front panel. (Fig. 1)
- Remove 2 push rivets and then remove the plate side (L) and (R). (Fig. 1)
- Remove CB1, CB20, CB461 and CB550. (Fig. 1)
- Remove 2 screws (⑥) and then pull out the sub-chassis unit. (Fig. 1)
- Unlock and remove CB333 and CB477. (Fig. 1)
- Remove the sub-chassis unit. (Fig. 1)




Fig. 1

3. Removal of GUI, DIGITAL (1) and (3) P.C.B.s

- Remove 2 screws (7). (Fig. 2)
- Remove CB501. (Fig. 2)
- Unlock and remove CB500 and CB503. (Fig. 2)
- Release hook, and remove the GUI P.C.B.. (Fig. 2)
- Remove 2 screws (8) and 2 jack screws. (Fig. 2)
- Remove CB80 (U model). (Fig. 2)
- Unlock and remove CB81. (Fig. 2)
- Remove the DIGITAL (3) P.C.B.. (Fig. 2)
- Remove 3 screws (U model) / 2 screws (C, R, T, K, A, B, G, E, F, L models) (9) and 6 screws (10). (Fig. 2)
- Remove screw (11) and 2 screws (12). (Fig. 2)
- Remove CB7, CB21, CB25, CB29, CB31, CB71 and CB73 (B, G, E, F models). (Fig. 2)
- Unlock and remove CB22–24. (Fig. 2)
- Remove the DIGITAL (1) P.C.B. which is connected directly to the OPERATION (2) P.C.B. with board-to-board connectors. (Fig. 2)

4. Removal of AMP Unit

- Remove 3 screws (13) and 4 screws (14). (Fig. 2)
- Remove 3 screws (15). (Fig. 2)
- Remove the amp unit. (Fig. 2)




Fig. 2

When checking the P.C.B.s:

- Place the P.C.B.s (with rear panel) upright. (Fig. 3)
- Connect the ground points of the heatsink, rear panel and MAIN (1) P.C.B. (G1000) to the chassis with a ground lead or the like. (Fig. 3)
- When connecting the flexible flat cable, be careful with polarity.
- Reconnect all cables (connectors) that have been disconnected.

Be sure to use the extension cable for servicing for the following section.

DIGITAL (1) P.C.B. CB20 to OPERATION (1) P.C.B. CB401:

MF125400 (25P, 400mm, P=1.25)

OPERATION (1) P.C.B. CB402 to OPERATION (2) P.C.B. CB461:

MF109400 (9P, 400mm, P=1.25)

DIGITAL (1) P.C.B. CB1 to DIGITAL (2) P.C.B. CB96:

MFA20250 (20P, 250mm, P=1.0)




Fig. 3

■ UPDATING FIRMWARE

Note) The user memories (sound field parameters, system memory, tuner presetting, etc.) are preserved even after the firmware is written.

When replacing the following parts, be sure to write the latest firmware.

Replaced parts	Writing method using the USB	Writing method using PC (RS232C)
DIGITAL P.C.B.	yes	yes
IC20 (Main microprocessor) of DIGITAL P.C.B.	no	yes
IC49 (TI (DSP) flash ROM) of DIGITAL P.C.B.	yes	yes
IC513 (BF (Sub-microprocessor) flash ROM) of GUI P.C.B.	yes	no

● Confirmation of firmware version and checksum

Before and after writing firmware, check the firmware version and checksum by using the self-diagnostic function menu.

Start up the self-diagnostic function and select "25. ROM VER/SUM/PORT" menu. (See "SELF-DIAGNOSTIC FUNCTION")

Using the sub-menu, have the firmware version and checksum displayed, and note down them.

25. ROM VER/SUM/PORT

Firmware version

Ver: C024

The firmware version of main microprocessor (IC20 DIGITAL P.C.B.) is displayed.

All checksum

Sum: 5253

The checksum value of main microprocessor (IC20 DIGITAL P.C.B.) is displayed.

TI (DSP) FLASH ROM version

TiVer:01.03r1

The firmware version of TI (DSP) FLASH ROM (IC49 DIGITAL P.C.B.) is displayed.

TI (DSP) FLASH ROM checksum

TiSum:F1AD0135A

The checksum value of TI (DSP) FLASH ROM (IC49 DIGITAL P.C.B.) is displayed.

BF version

BF Ver: C019

The firmware version of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

BF checksum 1 (All/Master boot)

Al:3ED2Ma:0122

The checksum value (All/Master boot) of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

BF checksum 2 (Application/USB)

Ap:67DAUs:ADBC

The checksum value (Application/USB) of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

Supplementary information:

In this unit, it is possible to check the firmware version by using the ADVANCED SETUP menu as well as the self-diagnostic function menu.

Follow the procedures below.

1. While pressing the "STRAIGHT" key of this unit, press the "MAIN ZONE ON/OFF" key of this unit to turn on the power.
The ADVANCED SETUP mode is activated, and "ADVANCED SETUP" is displayed. (Fig. 1)
2. Rotate the "PROGRAM" knob and select the "VER---.---.---". (Fig. 1)
After a few seconds, each firmware version is displayed.




Fig. 1

3. Press the "MAIN ZONE ON/OFF" key of this unit to turn off the power.

Writing method using the USB

Required Tools

- USB storage device
- Firmware RX-V2065 : RX-V2065_xxxx.bin
 HTR-6295 : HTR-6295_xxxx.bin

Preparation

1. Download the latest firmware from the specified download source to the folder of the PC.
2. Copy the latest firmware from the PC to the root folder of the USB storage device.
Note) When the firmware is copied to a sub-folder of the USB storage device, the update will not proceed.

Operation procedures

1. Insert the USB storage device to the USB terminal located on the front panel of this unit. (Fig. 2)
2. While pressing the “TONE CONTROL” key of this unit, connect the power cable to the AC outlet. (Fig. 2)
Writing of the firmware is started and the screen is displayed as shown below. (Fig. 3).




Fig. 2




Fig. 3

3. When writing of the firmware is completed, "UPDATE SUCCESS" is displayed.
 - * When "UPDATE FAIL" is displayed before writing is completed, perform the operation procedures from step 1 to 2 again.
4. Press the "MAIN ZONE ON/OFF" key of this unit to turn off the power.
5. Remove the USB storage device from the USB terminal of this unit.
6. Start up the self-diagnostic function and select "25. ROM VER/SUM/PORT" menu.

Using the sub-menu, have the firmware version and checksum displayed, and then check that they are the same as written ones.

 - * When the displayed firmware version and checksum are different from written ones, perform the "Writing the Firmware" procedure all over again.
7. Press the "MAIN ZONE ON/OFF" key to turn off the power.

Writing method using PC (RS232C)

● Required Tools

- Firmware downloader program
For main microprocessor:
DSP_FLASHER_v3.0.exe
For DSP (TI flash ROM):
DSP_FLASHER Ver2.7.exe
- Firmware
For main microprocessor: V265xxxx.mot
For DSP (TI flash ROM):
Vx65_data1_verxxxxr.hex
- RS232C cross cable "D-sub 9 pin female"
(Specifications)

Pin No.2 RxD	Pin No.2 RxD
Pin No.3 TxD	Pin No.3 TxD
Pin No.5 GND	Pin No.5 GND
Pin No.7 RTS	Pin No.7 RTS
Pin No.8 CTS	Pin No.8 CTS
- RS232C conversion adaptor (Part No.: WR492800)

● Preparation and precautions

- Download the firmware downloader program and the firmware from the specified source to the same folder of the PC.
- Prepare the above specified RS232C cross cable.
- While writing the firmware, keep the other application software on the PC closed.
It is also recommended to keep the software on the task tray closed as well.

● Connection

- Remove the top cover. (See "DISASSEMBLY PROCEDURES")
- Connect the writing port (CB27 of DIGITAL P.C.B.) of this unit to the serial port (RS232C) of the PC with RS232C cross cable, RS232C conversion adaptor and flexible flat cable as shown below. (Fig. 1)
- Set the switch (SW7) of RS232C conversion adaptor as shown below. (Fig. 1)




Fig. 1

● Operation Procedures

Writing to the main microprocessor

1. With the power cable of this unit disconnected from the AC outlet, start up DSP_FLASHER_v3.0.exe.
The screen appears as shown below. (Fig. 2)
2. Click [...] and select the firmware name. (Fig. 2)




Fig. 2

3. Connect the power cable of this unit to the AC outlet.
4. Click [E.P.] to start writing. (Fig. 3)
5. When writing of the firmware is completed, "Program Finished!" is displayed. (Fig. 3)
Click [OK]. (Fig. 3)
6. Click [EXIT] to end DSP_FLASHER_v3.0.exe. (Fig. 3)




Fig. 3

7. Disconnect the power cable of this unit from the AC outlet.
8. Remove the RS232C conversion adaptor and flexible flat cable from the writing port (CB27, DIGITAL P.C.B.) of this unit.
9. Start up the self-diagnostic function and select "25.ROM VER/SUM/PORT" menu.
Using the sub-menu, have the firmware version and checksum displayed, and then check that they are the same as written ones.
* When the firmware version and checksum are different from written ones, perform the "Writing to the microprocessor" all over again.
10. Press the "MAIN ZONE ON/OFF" key of this unit to turn off the power.
11. Disconnect the power cable of this unit from the AC outlet.

Writing to DSP

1. With the power cable of this unit disconnected from the AC outlet, start up DSP_FLASHER Ver2.7.exe.
The screen appears as shown below. (Fig. 4)
2. Click [Vx61 DSP]. (Fig. 4)



Fig. 4

3. Click [...] and select the firmware name. (Fig. 5)






Fig. 5

4. Click [RDY]. (Fig. 6)



Fig. 6

5. While pressing the “PURE DIRECT” key of this unit, connect the power cable of this unit to the AC outlet. (Fig. 7)
Writing is started automatically. (Fig. 7)



Writing being executed.

Fig. 7

6. When writing of the firmware is completed, "Vx61 DSP Flash finished!" is displayed. (Fig. 3)
7. Click [EXIT] to end DSP_FLASHER_v2.7.exe. (Fig. 8)



Fig. 8

8. Start up the self-diagnostic function and select "25.ROM VER/SUM/PORT" menu.
Using the sub-menu, have the firmware version and checksum displayed, and then check that they are the same as written ones.
* When the firmware version and checksum are different from written ones, perform the "Writing to DSP" all over again.
9. Press the "MAIN ZONE ON/OFF" key of this unit to turn off the power.
10. Disconnect the power cable of this unit from the AC outlet.
11. Remove the RS232C conversion adaptor and flexible flat cable from the writing port (CB27, DIGITAL P.C.B.) of this unit.

■ SELF-DIAGNOSTIC FUNCTION

CAUTION!

Do not disconnect the power cable of this unit from the AC outlet while this unit is in the self-diagnostic function mode, otherwise the user memories (input rename, sound field parameters, system memory, tuner presetting, etc.) will be initialized.

Therefore, to cancel the self-diagnostic function, be sure to press the "MAIN ZONE ON/OFF" key of this unit to turn off the power.

This unit has self-diagnostic functions that are intended for inspection, measurement and location of faulty point.

There are 27 main menu items, each of which has sub-menu items.

Listed in the table below are main menu items and sub-menu items.

Note that not all menu items listed will apply to the models covered in this service manual.

No.	Main menu	Sub-menu	
1	BYPASS	1	ANALOG BYPASS
		2	DSP BYPASS
2	RAM THROUGH	1	RAM MARGIN
		2	RAM FULL ALL
		3	RAM FULL CENTER
		4	RAM FULL SURROUND
		5	RAM FULL SURROUND BACK
3	HDMI AUDIO	1	SPDIF
		2	Multi
		3	DSD
4	SPEAKERS SET	1	FRNT: SML 0dB
		2	CENTER: NONE
		3	LFE/B: FRNT
		4	Zone2/3 Amp ON
		5	Bi-AMP
		6	TONE: MAX
		7	TONE: MIN
		8	SPEAKER 6 ohms
5	MULTI CH-INPUT	1	8ch INPUT 6 ohms
		2	8ch INPUT 8 ohms
		3	LIM/PLDET/THM
6	MIC CHECK	1	MIC CHECK
7	FL/GUI CHECK	1	VFD CHECK
		2	VFD DISP OFF / MONITOR OUTPUT OFF
		3	VFD DISP ALL / COMPONENT OUTPUT OFF
		4	VFD DIMMER / GUI SCREEN ON
		5	CHECK PATTERN / GUI SCREEN ON
8	MANUAL TEST	1	TEST ALL
9	A/D DATA CHECK	1	PS1/PS2
		2	DC/TH
		3	IMP/PL
		4	DST/DK
		5	K0/K1


No.	Main menu	Sub-menu	
10	VIDEO CHECK	1	I2C
		2	DIGITAL COMPONENT
		3	DIGITAL CVBS
		4	DIGITAL Y/C (B, G, E, F models)
		5	ANALOG BYPASS
		6	TEST PATTERN
		7	VIDEO INFORMATION
11	XM STATUS (U model)	1	1k -1dB /44kHz
		2	1k -61dB /44kHz
		3	Mute /44kHz
		4	XM Tone /44kHz
		5	ISO Tone /44kHz
		6	1k -1dB /32kHz
		7	1k -61dB /32kHz
		8	Mute /32kHz
		9	XM Tone /32 kHz
		10	ISO Tone /32 kHz
		11	Bus Power: OFF
12	SIRIUS (U model)	1	SIRIUS: OK (NG)
		2	SR
		3	SSP (SIRIUS #0 VERSION)
		4	MAC (SIRIUS #1 VERSION)
		5	ADP (SIRIUS #2 VERSION)
		6	PRDID
		7	SEQID
13	HD RADIO (U model)	1	HD CPU VERSION
		2	HD DSP VERSION
14	DOCK	1	DOCK
		2	BT VERSION
15	HDMI INFO	1	HMN
		2	HPI
		3	HVN
16	HDMI SELECT	1	HDMI NONE
		2	HDMI IN 1
		3	HDMI IN 2
		4	HDMI IN 3
		5	HDMI IN 4
		6	HDMI IN F
		7	HDMI UP CONVERSION
		8	HDMI UP THROUGH
17	USB	1	USB File 1
		2	USB File 2

No.	Main menu	Sub-menu	
18	IF STATUS (Not applied to these models.)	1	DSP STATUS
19	BUS CHECK	1	TI BUS
		2	BF LOOP
20	NO MENU	Invalidity	
21	PROTECTION HISTORY	1	HISTORY 1
		2	HISTORY 2
		3	HISTORY 3
		4	HISTORY 4
22	NO MENU	1	Invalidity
23	UPDATE	1	TI FLASH BOOT (Not applied to these models.)
24	FACTORY PRESET	1	PRESET INHI
		2	PRESET RSRV
25	ROM VER/SUM/PORT	1	VERSION
		2	ALL SUM
		3	TI (DSP) FLASH VERSION
		4	TI (DSP) FLASH SUM
		5	BF VERSION
		6	BF SUM 1 (All/Main)
		7	BF SUM 2 (Application/USB)
		8	XM VERSION (U model)
		9	SIRIUS VERSION (U model)
		10	MODEL/DESTINATION
		11	Verify (Not applied to these models.)
		12	MAC address
26	SERIAL	1	RS-232C loop back check
		2	EEPROM check
27	NETWORK	1	IP Address check
		2	MAC Address check
		3	MAC LABEL No. SET
		4	LINK check
		5	NETWORK loop back check
		6	Line noise measurement 10Mbps
		7	Line noise measurement 100Mbps

● Starting Self-Diagnostic Function

While pressing those 2 keys of this unit as shown in the figure below, press the “MAIN ZONE ON/OFF” key to turn on the power.

The self-diagnostic function mode is activated.



● Starting Self-Diagnostic Function in the protection cancel mode

If the protection function works and causes hindrance to trouble shoot, cancel the protection function as described below, and it will be possible to enter the self-diagnostic function mode.

(The protection functions other than the excess current detect function will be disabled.)

While pressing those 2 keys as shown in the figure above, press the “MAIN ZONE ON/OFF” key to turn on the power and keep pressing those 2 keys and “MAIN ZONE ON/OFF” key for 3 seconds or longer.

The self-diagnostic function mode is activated with the protection functions disabled.

In this mode, the SLEEP segment of the FL display of this unit flashes to indicate that the mode is self-diagnostic function mode with the protection functions disabled.

CAUTION!

Using this product with the protection function disabled may cause damage to itself. Use special care when using this mode.

● Canceling Self-Diagnostic Function


1. Before canceling self-diagnostic function, execute setting for FACTORY PRESET of main menu No. 24 (Memory initialization inhibited or Memory initialized).
 - * In order to keep the user memory stored, be sure to select PRESET INHIBITED (Memory initialization inhibited).
2. Press the “MAIN ZONE ON/OFF” key of this unit to turn off the power.

● Display provided when Self-Diagnostic Function started

The display is as described below depending on the situation when the last time the power to this unit is turned off.

1. When the power is turned off by usual operation:

The FL display of this unit displays "NO PROTECT" then the main menu (sub-menu "1. ANALOG BYPAS" of main menu 1 BYPASS) a few seconds later.



2. When the protection function worked to turn off the power:

The FL display of this unit displays the data of protection function which worked at that time then the main menu (sub-menu "1. ANALOG BYPAS" of main menu 1 BYPASS) a few seconds later.

Note: At that time if you reactivate the self-diagnostic function after turning off the power once by pressing the "MAIN ZONE ON/OFF" key, "NO PROTECT" will be displayed because that situation is equal to "1. When the power is turned off by usual operation:" described above.

However the protection function history is stored in a backup memory. For details, refer to main menu 21 PROTECTION HISTORY.

2-1. When the protection function worked due to excess current.

PS PRT:xxx

AD value when the protection function is working

Cause: An excessive current flowed through the power amplifier.

Supplementary information: As current of the power amplifier is detected, the abnormal channel can be identified by checking the current detect transistor.

Turning on the power without correcting the abnormality will cause the protection function to work immediately and the power supply will instantly be shut off.

Note)

- Applying the power to this unit without correcting the abnormality can be dangerous and cause additional circuit damage. To avoid this, if protection function has been activated 3 times continuously, the power will not turn on even when the "MAIN ZONE ON/OFF" key is pressed. In order to turn on the power again, disconnect the power cable of this unit from the AC outlet once and then reconnect it again.
- The output transistors in each amplifier channel should be checked for damage before applying power of this unit.
- Amplifier current should be monitored by measuring DC voltage across the emitter resistors for each channel.

2-2. When the protection function worked due to a short between speaker terminals.

I PROTECT:xxx

AD value when the protection function is working

Cause: The line between speaker terminals is shorted.

Supplementary information: As the excess current is detected after operation of the speaker relay, the shorted speaker terminal and the connected speaker can be identified.

Turning on the power without correcting the abnormality will cause the protection function to work immediately and the power supply will instantly be shut off.

2-3. When the protection function worked due to abnormal DC output.

DC PRT:xxx

AD value when the protection function is working

Cause: DC output from the power amplifier is abnormal.

Supplementary information: The protection function worked due to a DC voltage appearing at the speaker terminal. A cause could be a defect in the amplifier.

Turning on the power without correcting the abnormality will cause the protection function to work in 3 seconds and the power supply will be shut off.

2-4. When the protection function worked due to abnormal voltage in the power supply section.

PRV PRT:xxx

AD value when the protection function is working

Cause: The voltage in the power supply section is abnormal.

Supplementary information: The protection function worked due to a defect or overload in the power supply.

Turning on the power without correcting the abnormality will cause the protection function to work in 1 second and the power supply will be shut off.

2-5. When the protection function worked due to excessive heatsink temperature.

THM PRT:xxx

AD value when the protection function is working

Cause: The temperature on the heatsink is excessive.

Supplementary information: The protection function worked due to the temperature limit being exceeded.

Causes could be poor ventilation or a defect related to the thermal sensor.

Turning on the power without correcting the abnormality will cause the protection function to work in 1 second and the power supply will be shut off.

* For detection of each protection function, refer to main menu described later.

● History of protection function

When the protection function has worked, its history is stored in memory with a backup.

Even if no abnormality is noted while servicing the unit, an abnormality which has occurred previously can be defined as long as the backup data has been stored.

For details of the history of protection function, refer to main menu 21 PROTECTION HISTORY.

The history of the protection function is cleared when self-diagnostic function is cancelled by selecting PRESET RESERVED (Memory initialized) of main menu 24 or when the backup data is erased.

● Operation procedure of Main menu and Sub-menu


There are 27 main menu items, each of them having sub-menu items.

Main menu selection

Select the main menu using "PROGRAM" knob.

Sub-menu selection

Select the sub-menu using "SCENE RADIO" (forward) and "SCENE CD" (reverse) keys.



● Functions in Self-Diagnostic Function mode

In addition to the self-diagnostic function menu items, functions as listed below are available.

- Power ON/OFF
- Master volume
- Muting
- Input select
- Audio select
- PROGRAM select
- Tone control
- PURE DIRECT ON/OFF
- ZONE2 ON/OFF
- ZONE3 ON/OFF

* Functions related to the tuner and the set menu are not available.

● Initial settings used to start Self-Diagnostic Function

The following initial settings are used when starting self-diagnostic function.

When self-diagnostic function is canceled, these settings are restored to those before starting self-diagnostic function.

- Master volume: -20 dB
- Zone2 Volume: +2.5 dB
- Input: AV5 (MAIN ZONE) / AUDIO1 (ZONE2)
- Main menu: 1. ANALOG BYPASS
- Speaker setting: LARGE, Bass out to SWFR (All channels)
- Speaker impedance: 8 ohms position
- OSD: ON
- XM Power: ON (U model)

● Details of Self-Diagnostic Function menu

1. BYPASS

Using the sub-menu, it is possible to select ANALOG BYPASS output or DSP BYPASS output.

ANALOG BYPASS

The analog input audio signal is output to FRONT L/R in PURE DIRECT.

INPUT: AV5 ANALOG

SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz


Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	+13.0 dBm	-∞	-∞	-∞	-∞	-∞	-∞	-∞

DSP BYPASS

The digital input audio signal is output to FRONT L/R in PURE DIRECT.


0	000	000	0000	0000	0	0	0000	000	000	000
000	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0
0	0	0	000	0000	0	0	0	0000	000	000
000	000	0	0	0	0	0	0	0	0	0
000	000	0000	0000	0	0	0	0	0	0	0

ANALOG BYPASS



(Shaded items not used in this example)

DSP BYPASS



(Shaded items not used in this example)

2. RAM THROUGH

Using the sub-menu, it is possible to select MARGIN output or FULL BIT output.

RAM MARGIN

The audio signal is output including the head margin.

2. RAM MARGIN

INPUT: AV5 ANALOG

SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-∞	-∞	-∞	-6.5 dBm


RAM FULL BIT

The audio signal is output in digital full bit without including the head margin.
The SUBWOOFER signal is output but not in digital full bit.

2. RAM FULL ALL

INPUT: AV5 ANALOG
SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-∞	-∞	-∞	-6.5 dBm



When input source is stereo, signal is assigned as below.

- Front L → Front L / Center / Surround L / Surround Back L, R
- Front R → Front R / Surround R
- Front L +10 dB → SWFR

RAM FULL CENTER

The audio signal is output to only CENTER in digital full bit without including the head margin.

2. RAM FULL C

INPUT: AV5 ANALOG

SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	-∞	+13.0 dBm	-∞	-∞	-∞	-∞	-∞	-∞

RAM FULL SURROUND

The audio signal is output to only SURROUND L/R in digital full bit without including the head margin.

2. RAM FULL SUR

INPUT: AV5 ANALOG

SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	-∞	-∞	+13.0 dBm	-∞	-∞	-∞	-∞	-∞

RAM FULL SURROUND BACK

The audio signal is output to only SURROUND BACK L/R in digital full bit without including the head margin.

2. RAM FULL SB

INPUT: AV5 ANALOG


SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	-∞	-∞	-∞	+13.0 dBm	-∞	-∞	-∞	-∞

3. HDMI AUDIO

Using the sub-menu, the audio signals input to HDMI IN are selected and output.

* When selecting “DSD”, be sure to connect an HDMI unit equipped with DSD output function to this unit.




4. SPEAKER SET

The analog switch settings for each sub-menu are as shown in the table below.

		FRONT	CENTER	SURROUND	SURROUND BACK	SUBWOOFER
FRNT	: SML 0dB	SMALL	LARGE	LARGE	LARGE	SWFR
CENTER	: NONE	LARGE	NONE	LARGE	LARGE	SWFR
LFE/B	: FRNT	LARGE	SMALL	SMALL	SMALL	FRONT
Zone2/3 Amp ON		LARGE	LARGE	– (*1)	– (*1)	SWFR
Bi-AMP		LARGE	LARGE	LARGE	LARGE (*2)	SWFR
TONE	: MAX	LARGE	LARGE	LARGE	LARGE	SWFR
TONE	: MIN	LARGE	LARGE	LARGE	LARGE	SWFR
SPEAKER 6 ohms		LARGE	LARGE	LARGE	LARGE	SWFR

(*1) ZONE2/3 L/R (EXTRA SP1/2 L/R): LARGE
(*2) Bi-AMP: LARGE

- LARGE:** This mode is used for a speaker with high bass reproduction performance (a large unit). Full bandwidth signals are output.
- SMALL:** This mode is used for a speaker with low bass reproduction performance (a small unit). The signals of 90 Hz or less are mixed into the channel specified by LFE/BASS.
- NONE:** This mode is used for no center speaker. The center content is reduced by 3 dB and distributed to FRONT L/R.
- SWFR:** LFE of 5.1 ch signal or LFE/BASS lower than 90 Hz is output through SUBWOOFER OUT.
- FRONT:** LFE of 5.1 ch signal or LFE/BASS lower than 90 Hz is distributed to FRONT L/R.



INPUT: AV5 ANALOG

SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Sub-menu	Input level	Volume	SPEAKER OUT				SUBWOOFER OUTPUT
			FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
FRNT : SML 0dB	Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-3.0 dBm
CENTER : NONE	Both ch, -20 dBm	+6.5 dB	+18.0 dBm	-∞	+13.0 dBm	+13.0 dBm	-7.5 dBm
LFE/B : FRNT (50 Hz)	Both ch, -20 dBm	+6.5 dB	-∞	+13.0 dBm	+13.0 dBm	+13.0 dBm	-∞
Zone2/3 Amp ON	Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	-∞ (*)	-∞ (*)	-7.5 dBm
Bi-AMP	Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-7.5 dBm
TONE : MAX	Both ch, -20 dBm	+6.5 dB	+14.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-7.5 dBm
TONE : MIN	Both ch, -20 dBm	+6.5 dB	+12.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-7.5 dBm
SPEAKER 6 ohms	Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-7.5 dBm

(*) ZONE2/3 L/R (EXTRA SP1/2 L/R) SPEAKER OUT: +13.0 dBm

5. MULTI CH-INPUT

The input source "MULTI CHANNEL INPUT" is selected.

Using the sub-menu, it is possible to select the 6 ohms/8 ohms.

When LIM / PLDET / THM menu is selected, keys become non-operable.

However, it is possible to advance to the next main menu by turning the "PROGRAM" knob of this unit.

8 ch INPUT 6 ohms

5. 8ch INPUT_60

INPUT: MULTI CH INPUT
SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-∞	-∞	-∞	-16.5 dBm

8 ch INPUT 8 ohms

5. 8ch INPUT_80

INPUT: MULTI CH INPUT
SPEAKER OUT: 1 kHz, SUBWOOFER OUTPUT: 50 Hz

Input level	Volume	SPEAKER OUT							SUB-WOOFER OUTPUT
		FRONT	CENTER	SURROUND	SURROUND BACK	PRESENCE	ZONE2	ZONE3	
Both ch, -20 dBm	+6.5 dB	+13.0 dBm	+13.0 dBm	+13.0 dBm	+13.0 dBm	-∞	-∞	-∞	-16.5 dBm

LIM / PLDET / THM

LIM: Setting value of LIM (Limiter control)

* Do not change the value settings because this menu is only for the use of development staff.

PLDET: Power limiter detection


The A/D conversion value during operation is displayed.

(Reference voltage: 3.3 V=255)

THM: Temperature protection detection

The A/D conversion value during operation is displayed.

(Reference voltage: 3.3 V=255)

**6. MIC CHECK**

The signals input through the microphone are output to only FRONT L via A/D and D/A.


6. MIC CHK

7. FL/GUI CHECK


This menu is used to check the FL display and video control sections. When checking the video control section, connect a TV monitor to this unit with a component video cable and video pin cable.

Using the sub-menu, the FL display section or video control section switches as shown below.

Checking FL display section



Check of the Video control section. (Monitor out)



Segment conditions of the FL driver and the FL tube are checked by turning ON and OFF all segments. Next, the operation of the FL driver is checked by using the dimmer control. Then a short between segments next to each other is checked by turning ON and OFF all segments alternately (in lattice).

(In the above example, the segments in the second row from the top are shorted.)

8. MANUAL TEST

The built-in noise generator of DSP outputs the test noise through the channels specified by using the sub-menu.

The noise frequency for LFE is 30 to 80 Hz. Other than that, the noise frequency is 500 Hz to 2 kHz.

TEST ALL

The test noise is output from all channels.

8. TEST ALL

9. A/D DATA CHECK

This menu is used to display the A/D conversion value of the microprocessor which detects panel keys of this unit and protection functions by using the sub-menu.

When K0/K1 menu is selected, keys become non-operable due to detection of the values of all keys.

However, it is possible to advance to the next main menu by turning the "PROGRAM" knob of this unit.

* The figures in the diagram are given as reference only.

PS1/PS2

PSx: Power supply voltage protection detection

PS1

Voltage detects: AC_BL, AC_12, AC_5, ± 12 and +5V

Normal value: 38 to 128

(Reference voltage: 3.3 V=255)

PS2

Voltage detects: -5 and +5V

Normal value: 31 to 125

(Reference voltage: 3.3 V=255)

* If PS1 or PS2 becomes out of the normal value range, the protection function works to turn off the power.

PS1:087 2:077

DC/TH**DC:** Power amplifier DC (DC voltage) output is detected.Normal value: 32 to 74
(Reference voltage: 3.3 V=255)**TH:** Temperature on the heatsink is detected.Normal value: 0 to 124
(Reference voltage: 3.3 V=255)

* If DC or TH becomes out of the normal value range, the protection function works to turn off the power.

DC:049 TH:117

IMP/PL**IMP:** 8 or 6 ohms impedance setup detection

IMP 8: 8 ohms setting

IMP 6: 6 ohms setting

PL: PLDET (Power amplifier output voltage detection)

The power amplifier output voltage is detected and the power amplifier input voltage is controlled according to the detected output voltage.

(Reference voltage: 3.3 V=255)

IMP:8 PL:255

U, C, T, K, A, B, G, E, F models (Reference voltage: 3.3 V=255)

	During normal operation	Value for starting limiter operation	Value for canceling limiter operation
PLDET (8 ohms/6 ohms)	255 / 255	87 / 146	125 / 171
LIM (Limiter control)	H	L	H

R, L models (Reference voltage: 3.3 V=255)

	During normal operation	Value for starting limiter operation	Value for canceling limiter operation
PLDET (8 ohms/6 ohms)	255 / 255	100 / 100	131 / 131
LIM (Limiter control)	H	L	H

DST/DK

DST: Destination detection
(Reference voltage: 3.3 V=255)

DK: DOCK type detection
(Reference voltage: 3.3 V=255)

DST:211 DK:255

Destination detection for AD port
Pull-up resistance 10 k-ohms

Ohm (R3809 VIDEO P.C.B.)	1.2 k	2.7 k	4.7 k	6.8 k	10.0 k	15.0 k	47.0 k	100.0 k
A/D value (3.3 V=255)	15 – 46	46 – 69	69 – 92	92 – 115	115 – 139	139 – 177	185 – 224	224 – 247
DEST (139 pin)	U	C	R	T	K	A	B, G, E, F	L

DOCK detection for AD port (IC20 Microprocessor pin no. 128)
Pull-up resistance 10 k-ohms

DOCK type (DKID 141 pin)	Bluetooth	iPod	No connect
A/D value (3.3 V=255)	5 – 25	120 – 140	255

K0/K1

K0/K1: KEY0/KEY1 (Panel key of this unit)

When the A/D conversion value of the panel key becomes out of the specified range, normal operation will not be available.

In that case, check the constant of voltage dividing resistor, solder condition, etc. Refer to the table below.

(Reference voltage: 3.3 V=255)

K0:255 K1:255


Display	K0
0 – 11	SCENE RADIO
12 – 32	SCENE CD
33 – 54	SCENE TV
55 – 75	SCENE BD/DVD
76 – 95	ZONE2 ON/OFF
96 – 118	ZONE3 ON/OFF
119 – 142	—
143 – 162	—
181 – 197	MAIN ZONE ON/OFF
198 – 229	TONE CONTROL
255	KEY OFF

Display	K1
0 – 11	PURE DIRECT
12 – 32	STRAIGHT / EFFECT
33 – 54	ZONE CONTROLS
55 – 77	INFO
78 – 98	PRESET ◀
99 – 120	PRESET ▶
121 – 143	MEMORY
144 – 165	BAND/CATEGORY
166 – 185	TUNING CH ◀
186 – 205	TUNING CH ▶
255	KEY OFF

10. VIDEO CHECK


I2C check

The I2C (Inter integrated circuit) bus line connection is checked.




Digital component

The video signal is converted and output as shown below.




Digital CVBS (Video)

The video signal is converted and output as shown below.


**Digital Y/C (S-Video) (B, G, E, F models)**

The video signal is converted and output as shown below.





Analog bypass

The video signal is converted and output as shown below.




Test pattern

The test pattern is output from IC72 (DIGITAL P.C.B.).




Video information

The information of input video signal is displayed.




11. XM STATUS (U model)

This menu is used to check the output of XM Radio Antenna.



12. SIRIUS (U model)

The SIRIUS information are displayed.



13. HD RADIO (U model)

The firmware version is displayed.

CPU version

The firmware version is displayed.

HD CPU V:03.00

DSP version

The DSP version is displayed.

D: C0003.000

14. DOCK


This menu is used to check the DOCK connector without the iPod itself.

With the power to this unit turned off, short between pins No. 14 (TX) and No. 18 (RX), between pins No. 1 (PWR) and No. 17 (ACCPOW), between pins No. 4 (iPDET) and No. 8 (DGND). Also, connect a 10 k-ohms, 1/4 W resistor between pins NO. 21 (DKID) and No. 8 (DGND). (Make sure that the power is turned off when shorting pins.)

Start up the self-diagnostic function and select this menu.

The check result is displayed according to the following display specifications.

Note) Be sure to return the shorted pins to their original condition after executing this test.



DOCK CONNECTOR

DOCK: NG NNNN

All Y = "OK"
Others = "NG"

Check item	Short pins	Result		Display
UART loop back test	Pins No.14 (TX) – No.18 (RX)	OK		Y
		NG		N
iPAP (iPod accessory power) detection	Pins No.1 (PWR) – No.17 (ACCPOW)	IC20 pin No. 114	High = YES	Y
			Low = No	N
iPDET (iPod installation to DOCK) detection	Pins No.4 (iPDET) – No.8 (DGND)	IC20 pin No. 8	Low = installed	Y
			High = not installed	N
DKID (DOCK ID) detection	Pins No.21 (DKID) – No.8 (DGND) * 10 k-ohms, 1/4 W pull down	IC20 pin No. 141	10 k-ohms, 1/4 W pull down	Y
			Other	N


BT VERSION

The DOCK (Bluetooth module) version is displayed.

BT V:xxxxx

15. HDMI INFORMATION



The HDMI informations are displayed.




16. HDMI SELECT

Using the sub-menu, the selected input signal is output to HDMI OUT.

* Support audio is set to "OTHER".





17. USB

The music file stored in the USB storage device is reproduced.

- Copy 2 or more music files from PC to the root folder of the USB storage device.
- Insert the USB storage device to the USB terminal of this unit.

USB file 1

The 1st music file stored in the USB storage device connected to the USB terminal is reproduced.

17:USB file 1

USB file 2

The 2nd music file stored in the USB storage device connected to the USB terminal is reproduced.

17:USB file 2

18. IF STATUS (Input function status)

Not applied to these models.


DSP status

19. BUS CHECK

Communication and bus line connection between devices on the DIGITAL P.C.B. are checked.

TI (DSP) BUS check

Communication and bus line connection between microprocessor (IC20) and TI (DSP, IC44) are checked.



NoEr : No error detected.

Boot : When "Boot" is displayed for a few seconds or "Boot" and "NoEr" are displayed alternately, there is a possibility that an error had occurred.

BF LOOP :

Communication and bus line connection between main microprocessor (IC20) and BF (sub-microprocessor, IC505) are checked.




OK : No error detected.

NG : An error is detected.

20. NO MENU (Invalidity)


21. PROTECTION HISTORY

The history of protection function is displayed.
Select this menu and press the “STRAIGHT” key, all history will be erased.



22. NO MENU (Invalidity)

23. UPDATE

Not applied to these models.

UPDATE TI

23.UPDATE TI

24. FACTORY PRESET

This menu is used to reserve/inhibit initialization of the back-up IC.

24.PRESET INHI



24.PRESET RSRV

PRESET INHIBIT (Initialization inhibited) / PRESET INHIBIT

Back-up IC initialization is not executed. Select this sub-menu to protect the values set by the user.

PRESET RESERVED (Initialization reserved)

Initialization of the back-up IC is reserved. (Actually, initialization is executed the next time that the power is turned on.) Select this sub-menu to reset to the original factory settings or to reset the back-up IC. Any protection history will be cleared.

CAUTION: Before setting to the PRESET RESERVED, write down the existing preset memory content of the tuner.
(This is because setting to the PRESET RESERVED will cause the user memory content to be erased.)

25. ROM VER/SUM/PORT

The firmware version, checksum values, model name and destination are displayed.

The checksum is obtained by adding the data at every 8-bit for each program area and expressing the result as a 4-figure hexadecimal data.

* The figures in the diagram are given as reference only.

Firmware version

The firmware version of microprocessor (IC20 DIGITAL P.C.B.) is displayed.

```
Ver:  C024
```

All checksum

The checksum value of microprocessor (IC20 DIGITAL P.C.B.) is displayed.

```
Sum:  5253
```

TI (DSP) FLASH ROM version

The firmware version of TI (DSP) FLASH ROM (IC49 DIGITAL P.C.B.) is displayed.

```
TiVer:01.03r1
```

TI (DSP) FLASH ROM checksum

The checksum value of TI (DSP) FLASH ROM (IC49 DIGITAL P.C.B.) is displayed.

```
TiSum:F1D0135A
```

BF version

The firmware version of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

```
BF Ver:  C019
```

BF checksum 1 (All/Master boot)

The checksum value (All/Master boot) of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

```
A1:3ED2Ma:0122
```

BF checksum 2 (Application/USB)

The checksum value (Application/USB) of BF (sub-microprocessor, IC505 GUI P.C.B.) is displayed.

AP:67DAUS:ADEC

XM version (U model)

The firmware version of XM is displayed.

XM A010-A001

BF (sub-microprocessor)
Main microprocessor

SIRIUS version (U model)


The firmware version of SIRIUS is displayed.

SR A001-A001

BF (sub-microprocessor)
Main microprocessor

MODEL/DESTINATION

The model name and destination are displayed.

**VERIFY error**

Not applied to these models.

Verify 255

MAC address

The MAC address is displayed.


XXXXXXXXXXXX

26. SERIAL

RS-232C loop back check


This menu is used to check transmission and reception of the data, and the flow port of hardware.
With the power to this unit turned off, short between pins No. 2 (RxD) and No. 3 (TxD), and between pins No. 7 (RTS) and No. 8 (CTS) of the RS232C terminal. (Be sure to turn off the power when shorting the pins.)
Start up the self-diagnostic function and select this menu.
“OK” appears when the data is transmitted and received properly, and “NG” appears when it is not.
In this mode, NULL command transmission is continued after the test command is transmitted.

Note) Be sure to return the shorted pins to their original condition after executing this test.



EEPROM check

Communication and bus line connection between main microprocessor (IC20) and EEPROM (IC22) on the DIGITAL P.C.B. are checked.



27. Network

- * When the network condition varies while sub-menu is displayed (e.g., the network is deactivated once), the correct result will not be displayed.
In that case, once turn off the power to this unit, then start up the self-diagnostic function again and select this menu.

IP Address Check

Whether IP address is obtained or not is checked.

27.NET IP: NG

OK: Connected (IP address obtained)
NG: No traffic / Unconnected

MAC Address Check

MAC address information is checked.

27.NET MAC: OK

OK: Normal
NG: Unwritten

MAC LABEL No SET

This menu is used to change MAC address number.

When IC513 of GUI P.C.B. or GUI P.C.B. is replaced, use this menu to restore the previous MAC address number.

Yamaha Corporation will provide the setting procedure for proper operation.


Please report the serial number of this unit to the following e-mail address for further instruction.

E-mail: ycav-ysiss@gmx.yamaha.com

27.NET MAC SET

LINK CHECK


A network cable connection is checked.



NETWORK loop back check

This menu is used to check the NETWORK connector.
With the power to this unit turned off, short between pins No. 1 (Tx+) and No. 3 (Rx+) and between pins No. 2 (Tx-) and No. 6 (Rx-) of the NETWORK connector. (Be sure to turn off the power to this unit when shorting these pins.)
Start up the self-diagnostic function and select this menu.

Note) Be sure to return the shorted pins to their original condition after executing this test.



Line noise measurement 10Mbps

The line noise 10Mbps is output.



Line noise measurement 100Mbps

The line noise 100Mbps is output.





■ CONFIRMATION OF IDLING CURRENT OF AMP UNIT

- Right after power is turned on, confirm that the voltage across the terminals of R1152 (SURROUND BACK Rch), R1154 (SURROUND Rch), R1150 (FRONT Rch), R1148 (CENTER), R1149 (FRONT Lch), R1153 (SURROUND Lch), R1151 (SURROUND BACK Lch) are between 0.1mV and 10.0mV.
- If it exceeds 10.0 mV, open (cut off) R1104 (SURROUND BACK Rch), R1106 (SURROUND Rch), R1102 (FRONT Rch), R1100 (CENTER), R1101 (FRONT Lch), R1105 (SURROUND Lch), R1103 (SURROUND BACK Lch) and reconfirm the voltage.

Attention


If the measured voltage exceeds 10.0mV after an amplifier repair, first check for a defective component before cutting the bias resistor.

- Confirm that the voltage is 0.2 mV to 15.0 mV after 60 minutes.



■ DISPLAY DATA

● V4001 : 18-MT-09GNK (OPERATION P.C.B.)





● PIN CONNECTION

Pin No.	69	68	67	66	65	64	63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35
Connection	F2	NX	NP	NP	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16	P17	P18	P19	P20	P21	P22	P23	P24	P25	P26	P27	P28	P29	P30	P31

Pin No.	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
Connection	P32	P33	P34	P35	P36	NX	NX	NX	NX	NX	NX	NX	18G	17G	16G	15G	14G	13G	12G	11G	10G	9G	8G	7G	6G	5G	4G	3G	2G	1G	NP	NP	NX	F1

Note : 1) F1, F2 Filament pin 2) NP No pin 3) NX No extend pin 4) 1G-18G Grid pin


● GRID ASSIGNMENT



● ANODE CONNECTION

	18G	17G	16G	15G	1G-14G
P1	1a	1a	1a	S5	1-1
P2	1h	1h	1h	S7	2-1
P3	1j	1j	1j	1d	3-1
P4	1k	1k	1k	2d	4-1
P5	1b	1b	1b	S2	5-1
P6	1f	1f	1f	1e	1-2
P7	1m	1m	1m	2e	2-2
P8	1g	1g	1g	S3	3-2
P9	1c	1c	1c	1c	4-2
P10	1e	1e	1e	2c	5-2
P11	1r	1r	1r	S4	1-3
P12	1p	1p	1p	1g	2-3
P13	1n	1n	1n	2g	3-3
P14	1d	1d	1d	1f	4-3
P15	2a	2a	2a	2f	5-3
P16	2h	2h	2h	1b	1-4
P17	2j	2j	2j	2b	2-4
P18	2k	2k	2k	1a	3-4
P19	2b	2b	2b	2a	4-4
P20	2f	2f	2f	PL	5-4
P21	2m	2m	2m	SW	1-5
P22	2g	2g	2g	PR	2-5
P23	2c	2c	2c	L	3-5
P24	2e	2e	2e	C	4-5
P25	2r	2r	2r	R	5-5
P26	2p	2p	2p	SL	1-6
P27	2n	2n	2n	SR	2-6
P28	2d	2d	2d	SBL	3-6
P29	SIRIUS	S8	HD	SB	4-6
P30	XM	S9	TAG	SBR	5-6
P31	HDMI	iPod CHARGE	CINEMA DSP	S6	1-7
P32	OUT1	SP B	3	S13	2-7
P33	OUT2	S15	STEREO	MUTE	3-7
P34	S12	SP A	TUNED	ZONE 2	4-7
P35	S10	S14	S17	ZONE 3	5-7
P36	S11	—	S16	SLEEP	S1

* No replacement part available.





No.	Function Name (P.C.B.)	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	Detail of Function
1	VSS				
2	AHCLKX0/AHCLKX2	IO	–	Y	McASP0 and McASP2 transmit master clock
3	AMUTE0	IO	–	Y	McASP0 mute output
4	AMUTE1	IO	–	Y	McASP1 mute output
5	AHCLKX1	IO	–	Y	McASP1 transmit master clock
6	VSS				
7	ACLKX1	IO	–	Y	McASP1 transmit bit clock
8	CVDD				
9	ACLKR1	IO	–	Y	McASP1 receive bit clock
10	DVDD				
11	AFSX1	IO	–	Y	McASP1 transmit frame Sync (L/R clock)
12	AFSR1	IO	–	Y	McASP1 receive frame Sync (L/R clock)
13	VSS				
14	RESET	IO	–	N	Device reset pin
15	VSS				
16	CVDD				
17	CLKIN	IO	–	N	Alternate clock input (3.3-V LVCMOS input)
18	VSS				
19	TMS	IO	IPU	N	Test mode select
20	CVDD				
21	TRST	IO	IPU	N	Test reset
22	OSCVSS	PWR	–	N	Oscillator Vss tap point (for filter only)
23	OSCIN	IO	–	N	1.2-V oscillator input
24	NC	O	–	N	
25	OSCVDD	PWR	–	N	Oscillator 1.2-V Vpp tap point (for filter only)
26	VSS				
27	PLLHV	PWR	–	N	PLL 3.3-V supply input (requires external filter)
28	TDI	IO	IPU	N	Test data in
29	TDO	OZ	IPU	N	Test data out
30	VSS				
31	DVDD				
32	EMU[0]	IO	IPU	N	Emulation pin 0
33	CVDD				
34	EMU[1]	IO	IPU	N	Emulation pin 1
35	TCK	IO	IPU	N	Test clock
36	Ground(Vss)				
37	EM_CAS	O	–	N	SDRAM column address strobe
38	EM_WE	O	–	N	SDRAM write enable
39	EM_WE_DQM[0]	O	–	N	Write enable or byte enable for EM_D [7:0]
40	VSS				
41	EM_D[7]	IO	–	N	EMIF data bus [lower 16-bits]
42	DVDD				
43	EM_D[6]	IO	–	N	EMIF data bus [lower 16-bits]
44	CVDD				
45	EM_D[5]	IO	–	N	EMIF data bus [lower 16-bits]
46	EM_D[4]	IO	–	N	EMIF data bus [lower 16-bits]
47	VSS				
48	EM_D[3]	IO	–	N	EMIF data bus [lower 16-bits]
49	EM_D[2]	IO	–	N	EMIF data bus [lower 16-bits]
50	DVDD				
51	EM_D[1]	IO	–	N	EMIF data bus [lower 16-bits]
52	EM_D[0]	IO	–	N	EMIF data bus [lower 16-bits]
53	CVDD				
54	VSS				
55	EM_D[15]	IO	–	N	EMIF data bus [lower 16-bits]
56	EM_D[14]	IO	–	N	EMIF data bus [lower 16-Bits]
57	CVDD				
58	EM_D[13]	IO	–	N	EMIF data bus [lower 16-Bits]
59	EM_D[12]	IO	–	N	EMIF data bus [lower 16-Bits]
60	DVDD				
61	EM_D[11]	IO	–	N	EMIF data bus [lower 16-Bits]

No.	Function Name (P.C.B.)	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	Detail of Function
62	VSS				
63	EM_D[10]	IO	–	N	EMIF data bus [lower 16-Bits]
64	EM_D[9]	IO	–	N	EMIF data bus [lower 16-Bits]
65	CVDD				
66	EM_D[8]	IO	–	N	EMIF data bus [lower 16-bits]
67	EM_WE_DQM[1]	O	–	N	Write enable or byte enable for EM_D [15:8]
68	DVDD				
69	VSS				
70	EM_CLK	O	–	N	SDRAM clock
71	EM_CKE	O	–	N	SDRAM clock enable
72	VSS				
73	DVDD				
74	EM_A[11]	O	–	N	EMIF address bus
75	EM_A[9]	O	–	N	EMIF address bus
76	EM_A[8]	O	–	N	EMIF address bus
77	CVDD				
78	VSS				
79	EM_A[7]	O	–	N	EMIF address bus
80	EM_A[6]	O	–	N	EMIF address bus
81	DVDD				
82	VSS				
83	EM_A[5]	O	–	N	EMIF address bus
84	EM_A[4]	O	–	N	EMIF address bus
85	CVDD				
86	EM_A[3]	O	–	N	EMIF address bus
87	VSS				
88	EM_A[2]	O	–	N	EMIF address bus
89	EM_A[1]	O	–	N	EMIF address bus
90	CVDD				
91	EM_A[0]	O	–	N	EMIF address bus
92	DVDD				
93	EM_A[10]	O	–	N	EMIF address bus
94	EM_BA[1]	O	–	N	SDRAM bank address and asynchronous memory Low-Order address
95	VSS				
96	EM_BA[0]	O	–	N	SDRAM bank address and asynchronous memory Low-Order address
97	EM_CS[0]	O	–	N	SDRAM chip select
98	EM_RAS	O	–	N	SDRAM row address strobe
99	VSS				
100	EM_CS[2]	O	–	N	Asynchronous memory chip Select
101	CVDD				
102	NC	O	–	N	Asynchronous memory read/not write
103	DVDD				
104	EM_OE	O	–	N	SDRAM output enable
105	SPI0_ENA/I2C1_SDA	IO	–	Y	SPI0 enable (ready) or I2c1 serial data
106	VSS				
107	SPI0_ENA/I2C1_SCL	IO	–	Y	SPI0 enable (ready) or I2c1 serial clock
108	SPI0_CLK/I2C0_SCL	IO	–	Y	SPI0 serial clock or I2c0 serial clock
109	VSS				
110	SPI0_SIMO	IO	–	Y	SPI0 data pin slave in master out
111	SPI0_SOMI/I2C0_SDA	IO	–	Y	SPI0 data pin slave out master in or I2C0 serial data
112	DVDD				
113	AXR0[0]	IO	–	Y	McASP0 serial data 0
114	VSS				
115	AXR0[1]	IO	–	Y	McASP0 serial data 1
116	AXR0[2]	IO	–	Y	McASP0 serial data 2
117	AXR0[3]	IO	–	Y	McASP0 serial data 3
118	VSS				
119	AXR0[4]	IO	–	Y	McASP0 serial data 4
120	SPI1_SCS	IO	–	Y	McASP0 serial data 5 or SPI1 slave chip select
121	SPI1_ENA	IO	–	Y	McASP0 serial data 6 or SPI1 enable (ready)
122	SPI1_CLK	IO	–	Y	McASP0 serial data 7 or SPI1 serial clock

No.	Function Name (P.C.B.)	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	Detail of Function
123	CVDD				
124	VSS				
125	DVDD				
126	/SPI1_SOMI	IO	–	Y	McASP0 serial data 8 or McASP1 serial data 5 or SPI1 data pin slave out master in
127	/SPI1_SIMO	IO	–	Y	McASP0 serial data 9 or McASP1 serial data 4 or SPI1 data pin slave in master out
128	CVDD				
129	VSS				
130	AXR0[10]	IO	–	Y	McASP0 serial data 10 or McASP1 serial data 3
131	AXR0[11]	IO	–	Y	McASP0 serial data 11 or McASP1 serial data 2
132	CVDD				
133	VSS				
134	AXR0[12]	IO	–	Y	McASP0 serial data 12 or McASP1 serial data 1
135	AXR0[13]	IO	–	Y	McASP0 serial data 13 or McASP1 serial data 0
136	DVDD				
137	AXR0[14]	IO	–	Y	McASP0 serial data 14 or McASP2 serial data 1
138	AXR0[15]	IO	–	Y	McASP0 serial data 15 or McASP2 serial data 0
139	ACLKR0	IO	–	Y	McASP0 receive bit clock
140	VSS				
141	AFSR0	IO	–	Y	McASP0 receive frame Sync (L/R clock)
142	ACLKX0	IO	–	Y	McASP0 transmit bit clock
143	AHCLKR0/AHCLKR1	IO	–	Y	McASP0 and McASP1 receive master clock
144	AFSX0	IO	–	Y	McASP0 transmit frame Sync (L/R clock)



IC402: M66003-0131FP (OPERATION P.C.B.)
FL display driver



Pin No.	Port Name	Function Name	I/O	Detail of Function
1	RESET	/RESET	Reset input	When "L" M66003 is initialized.
2	CS	/CEFL	Chip select input	When "L" communication with the MCU is possible.
3	SCK	CKFL	Shift clock input	When "H", any instruction from the MCU is neglected.
4	SDATA	DTFL	Serial data input	Serial input data is taken and shifted by the positive edge of SCK.
5	Vss	VSS		GND (0V)
6	XOUT	XOUT	Clock out	When use as a CR oscillator, connect external resistor and capacitor.
7	XIN	XIN	Clock in	When use an external clock input external clock to XIN, and XOUT must be opened.

Pin No.	Port Name	Function Name	I/O	Detail of Function
8	Vcc1	VDD		Positive power supply for internal logic.
9	SEG34	P11	Segment output	Connect to segment (anode) pins of VFD.
10	SEG33	P2		
11	SEG32	P3		
12	SEG31	P4		
13	SEG30	P5		
14	SEG29	P6		
15	SEG28	P7		
16	SEG27	P8		
17	SEG26	P9		
18	Vcc2	VDD		Positive power supply for DIG and SEG outputs.
19	SEG25	P10	Segment output	Connect to segment (anode) pins of VFD.
20	SEG24	P11		
21	SEG23	P12		
22	SEG22	P13		
23	SEG21	P14		
24	SEG20	P15		
25	SEG19	P16		
26	SEG18	P17		
27	SEG17	P18		
28	SEG16	P19		
29	SEG15	P20		
30	SEG14	P21		
31	SEG13	P22		
32	SEG12	P23		
33	SEG11	P24		
34	SEG10	P25		
35	SEG09	P26		
36	SEG08	P27		
37	SEG07	P28		
38	SEG06	P29		
39	SEG05	P30		
40	SEG04	P31		
41	SEG03	P32		
42	SEG02	P33		
43	SEG01	P34		
44	SEG00	P35		
45	SEG35	P36		
46	SEG36	P37		
47	DIG16/SEG37	G17	Digital output	Connect to digit (grid) pins of VFD.
48	DIG15/SEG38	G16		
49	DIG14/SEG39	G15		
50	DIG13/SEG40	G14		
51	DIG12/SEG41	G13		
52	DIG11/SEG42	G12		
53	DIG10	G11		
54	DIG09	G10		
55	DIG08	G9		
56	DIG07	G8		
57	DIG06	G7		
58	DIG05	G6		
59	DIG04	G5		
60	DIG03	G4		
61	DIG02	G3		
62	DIG01	G2		
63	DIG00	G1		
64	VP	VP		Negative power supply to pull down.

IC41: LC89058WD-E (DIGITAL P.C.B.)
Digital audio interface receiver



Pin No.	Function Name	I/O	Detail of Function
1	RXOUT1	O	RX0-6 input S/PDIF through output pin 1
2	RX0	I _s (pd)	5V withstand voltage TIL input level compatible S/PDIF input pin (connected to GND when RX1 is set)
3	RX1	I(pd)	Co-axial compatible S/PDIF input pin (supported demodulation sampling frequency of up to 96 kHz)
4	RX2	I _s (pd)	5V withstand voltage TIL input level compatible S/PDIF input pin (connected to GND when RX1 is set)
5	RX3	I _s (pd)	5V withstand voltage TIL input level compatible S/PDIF input pin
6	DGND		Digital GND
7	DVDD		Digital power supply (3.3V)
8	RX4	I _s (pd)	5V tolerable TIL input level compatible S/PDIF input pin
9	RX5	I _s (pd)	5V tolerable TIL input level compatible S/PDIF input pin
10	RX6	I _s (pd)	5V tolerable TIL input level compatible S/PDIF input pin
11	DVDD		Digital power supply (3.3V)
12	DGND		Digital GND
13	LPF	O	PLL loop filter connection pin
14	AVDD		Analog power supply (3.3V)
15	AGND		Analog GND
16	RMCK	O	R system clock output pin (VCO, 512fs, XIN)
17	RBCK	O/I	R system bit clock 1/0 pin (64fs)
18	DGND		Digital GND
19	DVDD		Digital power supply (3.3V)
20	RLRCK	O/I	R system LR clock 1/0 pin (fs)
21	RDATA	O	Serial audio data output pin
22	SBCK	O	S system bit clock output pin (16fs, 32fs, 64fs, 128fs)
23	SLRCK	O	S system LR clock output pin (fs/4, fs/2, fs, 2fs)
24	SDIN	I _s	External serial audio data input pin
25	DGND		Digital GND
26	DVDD		Digital power supply (3.3V)
27	XMCK	O	Oscillation amplifier clock output pin
28	XOUT	O	Output pin connected to the resonator
29	XIN	I	External clock input pin. connected to the resonator (12.288 MHz or 24.576 MHz)
30	DVDD		Digital power supply (3.3V)
31	DGND		Digital GND
32	MOUT	I/O	Emphasis information II input fs monitor output II chip address setting input pin
33	AUDIO	I/O	Channel status bit 1 output II chip address setting input pin
34	CKST	I/O	Clock switching transition period signal output II master/slave setting input pin
35	INT	I/O	Microcontroller interrupt signal output II pins 44-48 I/O setting input pin
36	RERR	O	PLL lock error and data error flag output pin
37	DO	O	CCB microcontroller I/F, read data output pin (3-state)
38	DI	I _s	CCB microcontroller I/F, write data input pin
39	CE	I _s	CCB microcontroller I/F, chip enable input pin
40	CL	I _s	CCB microcontroller I/F, clock input pin
41	XMODE	I _s	System reset input pin
42	DGND		Digital GND
43	DVDD		Digital power supply (3.3V)
44	GPIO0	O/I	General-purpose I/O pin II selector input pin (output referred to RMCK pin)
45	GPIO1	O/I	General-purpose I/O pin II selector input pin (output referred to RBCK pin)
46	GPIO2	O/I	General-purpose I/O pin II selector input pin (output referred to RLRCK pin)
47	GPIO3	O/I	General-purpose I/O pin II selector input pin (output referred to RDATA pin)
48	RXOUT2	O	RX0-6 input S/PDIF through output pin 2

* Input voltage: 1= -0.3 to 3.6V, I_s = -0.3 to 5.5V

* Output voltage: 0= -0.3 to 3.6V

* Pins 2, 4, 5, 8, 9, 10, 24, 38, 39, 40, and 41 have an internal pull-down resistor (Pd). Their level is fixed when they are unselected.

* Pins 32 and 33 are input pins for chip address setting when pin 41 is held at the low level.


* Pin 34 serves as the input pin for designating as the master or slave when pin 41 is held at the low level.

* Pin 35 serves as the input pin for configuring the I/O of pins 44 to 47 when pin 41 is held at the low level.

* The DVDD and AVDD pins must be held at the same level and turned on and off at the same timing to preclude latch-up conditions.

IC153: R2A15220FP (MAIN P.C.B.)


8-channel electronic volume with 11 input selector and tone control




Pin No.	Port name	Function Name	Detail of Function
1	AGND	AE	Analog ground of internal circuit
2	SBROUT	VOSBL	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
3	SBR Pre-OUT	VOPSB	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
4	SBRC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
5	AGND	AE	Analog ground of internal circuit
6	SLC	VOPSR	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
7	SL Pre-OUT	VOSR	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
8	SLOUT	AE	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
9	AGND	AE	Analog ground of internal circuit
10	SROUT	VOSL	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
11	SR Pre-OUT	VOPSL	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
12	SRC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
13	SWC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
14	SWOUT	VOSW	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
15	AGND	AE	Analog ground of internal circuit
16	COUT	VOC	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
17	CC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
18	FLC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
19	FL Pre-OUT	VOPFR	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
20	FLOUT	VOFR	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
21	AGND	POE	Analog ground of internal circuit
22	FROUT	VOFL	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel
23	FR Pre-OUT	VOPFL	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
24	FRC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
25	BASSL1	AE	Frequency characteristic setting pin of L/R channel tone control (Bass)
26	BASSL2	AE	Frequency characteristic setting pin of L/R channel tone control (Bass)
27	TREL	AE	Frequency characteristic setting pin of L/R channel tone control (Treble)
28	BASSR1	AE	Frequency characteristic setting pin of L/R channel tone control (Bass)
29	BASSR2	AE	Frequency characteristic setting pin of L/R channel tone control (Bass)
30	TRER	AE	Frequency characteristic setting pin of L/R channel tone control (Treble)
31	AVCC	VCC	Positive power supply to internal circuit
32	SUBL1	N.C.	Output pin for L/R channel SUB1/SUB2 output
33	SUBL2	N.C.	Output pin for L/R channel SUB1/SUB2 output
34	SRCIN	N.C.	3rd multi input pin for SBL/SBR/SL/SR channel volume that is able to swap SBR/SBL with SR/SL
35	SLCIN	N.C.	3rd multi input pin for SBL/SBR/SL/SR channel volume that is able to swap SBR/SBL with SR/SL
36	SBLIN2	8SBR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
37	SBRIN2	8SBL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
38	CIN2	8C	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
39	SWIN2	8SW	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
40	SLIN2	8SR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
41	SRIN2	8SL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
42	FLIN2	8FR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
43	FRIN2	8FL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
44	SBRCIN	Z2L	3rd multi input pin for SBL/SBR/SL/SR channel volume that is able to swap SBR/SBL with SR/SL
45	SBLCIN	Z2R	3rd multi input pin for SBL/SBR/SL/SR channel volume that is able to swap SBR/SBL with SR/SL
46	SUBL1	Z2R	Output pin for L/R channel SUB1/SUB2 output
47	SUBR1	Z2L	Output pin for L/R channel SUB1/SUB2 output
48	DGND	MG	Digital ground of internal circuit
49	DATA	VOL_SCK	Input pin of control data
50	CLOCK	VOL_MOSI	Input pin of control clock
51	MUTE	AE	Outside mute control pin
52	AVEE	–	Negative power supply to internal circuit
53	ADCL	ADR	Output pin for L/R channel ADC
54	ADCR	ADL	Output pin for L/R channel ADC
55	AGND	AE	Analog ground of internal circuit
56	INR1	AU2L	Input pin of L/R channel (Input selector)
57	INL1	AU2R	Input pin of L/R channel (Input selector)

Pin No.	Port name	Function Name	Detail of Function
58	INR2	AU1L	Input pin of L/R channel (Input selector)
59	INL2	AU1R	Input pin of L/R channel (Input selector)
60	INR3	AV-6L	Input pin of L/R channel (Input selector)
61	INL3	AV-6R	Input pin of L/R channel (Input selector)
62	INR4	AV-5L	Input pin of L/R channel (Input selector)
63	INL4	AV-5R	Input pin of L/R channel (Input selector)
64	INR5	PHL	Input pin of L/R channel (Input selector)
65	INL5	PHR	Input pin of L/R channel (Input selector)
66	INR6	SRL	Input pin of L/R channel (Input selector)
67	INL6	SRR	Input pin of L/R channel (Input selector)
68	INR7	IPL	Input pin of L/R channel (Input selector)
69	INL7	IPR	Input pin of L/R channel (Input selector)
70	INR8	XML	Input pin of L/R channel (Input selector)
71	INL8	XMR	Input pin of L/R channel (Input selector)
72	INRA/RECR1	AV-OUT_L	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
73	INLA/RECL1	AV-OUT_R	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
74	INR9	USBL	Input pin of L/R channel (Input selector)
75	INL9	USBR	Input pin of L/R channel (Input selector)
76	INRB/RECR2	AOL	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
77	INLB/RECL2	AOR	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
78	INR10/RECR4	TUL	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
79	INL10/RECL4	TUR	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
80	INR11/RECR5	MIC	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
81	INL11/RECL5	AE	Output pin for L/R channel (input selector)/Output pin for L/R channel REC output
82	INR12	AUXL	Input pin of L/R channel (Input selector)
83	INL12	AUXR	Input pin of L/R channel (Input selector)
84	INR13	AE	Input pin of L/R channel (Input selector)
85	INL13	AE	Input pin of L/R channel (Input selector)
86	INR14	AE	Input pin of L/R channel (Input selector)
87	INL14	AE	Input pin of L/R channel (Input selector)
88	RECR3	N.C.	Output pin for L/R channel REC output
89	RECL3	N.C.	Output pin for L/R channel REC output
90	FLIN1	DAFR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
91	FRIN1	DAFL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
92	CIN1	DAC	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
93	SWIN1	DASW	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
94	SLIN1	DASR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
95	SEIN1	DASL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
96	SBLIN1	DASBR	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
97	SBRIN1	DASBL	Multi input pin of L/R/C/SW/SL/SR/SBL/SBR channel (Multi IN 1/2)
98	SBLC	AE	Connects capacitor for reducing click noise of L/R/C/SW/SL/SR/SBL/SBR channel volume
99	SBL Pre-OUT	VOPSB	Pre-output pin of FL/FR/SL/SR/SBL/SBR channel
100	SBL OUT	VOSBR	Output pin of FL/FR/C/SW/SL/SR/SBL/SBR channel

IC20: M3087BFKBGP (DIGITAL P.C.B.)
Main microprocessor



- NOTES:
1. Ports P11 to P15 are provided in the 144-pin package only.
 2. Included in the 144-pin package only.
 3. The supply voltage of M32C/84T (High-reliability version) must be $V_{CC1}=V_{CC2}$.



- NOTES:
1. P70 / TA0OUT / Tx02 / SD02 / SRx02 / INPC1e / OUTC1e
 2. P70 and P71 are ports for the N-channel open drain output.
 3. The supply voltage of M32C/84T must be $V_{CC1}=V_{CC2}$.

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	Stby Thrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
1	TXD4	SCPU_MOSI	SO	O	O	O	[O]		Synchronous data output for SubCPU
2	CLK4 P95/ANEX0/CLK4	SCPU_SCK	SO	O	O	O	[O]		Synchronous clock output for SubCPU
3	P94 P94/DA1/TB4in/ CTS4/RTS4/SS4	SCPU_CTS	SI	I	I	O	[O]		Input for transmission control for SubCPU (clear to send)
4	DA0 P93/DA0/TB3in/ CTS3/RTS3/SS3	AMP_LMT	DA	I	I	I	[I]		Limiter control output
5	TXD3 P92/TB2in/TXD3/ SDA3/SRXD3/ OUTC20/IEout/ ISTXD2	XM_MOSI	SO	O	O	O	O		Asynchronous data output for XM (U model)
	P92		O	O	O	O	O		(C, R, T, K, A, L models)
	TB2in	RDS_RDY	TMR	O	O	O	O		RDS READY input
6	RXD3 P91/TB1in/RXD3/ SCL3/STXD3/IEin/ ISRXD2	XM_MISO	SI	O	O	O	O		Asynchronous data input for XM (U model)
	P91		O	O	O	O	[O]		(C, R, T, K, A, L models)
	RXD3	RDS_MISO	SI	O	O	O	[O]		Synchronous data input for RDS (B, G, E, F model)
7	P90 P90/TB0in/CLK3	XM_LINK	I	I	O	O	[O]		XM LINK detection (U model)
	P90		O	O	O	O	[O]		(C, R, T, K, A, L models)
	CLK3	RDS_SCK	SO	O	O	O	[O]		Synchronous clock output for RDS IC Low level should stand by (B, G, E, F model)
8	INT8 P146/INT8	IPD_DET	IRQ	IRQ	IRQ	IRQ	[O]		iPod detection Restriction of port: INT is high edge or low edge only When inserting an iPod into the DOCK H → L
9	P145 P145/INT7	DIR_N_INT	IRQ	I	O	O	[O]		DIR interrupt Restriction of port: INT is high edge or low edge only
10	P144 P144/INT6	DSP_N_INT	IRQ	I	O	O	[O]		DA70Y interrupt Restriction of port: INT is high edge or low edge only
11	P143 P143/INPC17/ OUTC17	XM_N_RST	O	O	O	O	O		XM reset (U model)
	P143		O	O	O	O	O		(C, R, T, K, A, L models)
	P143	RDS_N_RST	O	O	O	O	O		RDS reset (B, G, E, F model)
12	P142 P142/INPC16/ OUTC16	XM_REV	I	I	O	O	[O]		XM antenna revision detection H: An compatibility antenna (U model)
	P142		O	O	O	O	[O]		(C, R, T, K, A, B, G, E, F, L models)
13	P141 P141/INPC15/ OUTC15	DIR_N_CS	CS	O	O	O	[O]		DIR chip select
14	P140 P140/INPC14/ OUTC14	DSP_N_RST	O	O	O	O	[O]		DA70Y reset
15	BYTE BYTE	BYTE	MCU	MCU	MCU	MCU	[MCU]		Switch of width of data bus input When set to single chip mode: L (16 bit)
16	CNVss CNPss	CNPss	MCU	MCU	MCU	MCU	[MCU]		Processor mode select Low: Single chip mode High: To Flash included boot mode To boot mode with hardware resetting of P50=H, P55=L, CNVss=H, and a standard serial. Input/output mode
17	P87 P87/Xcin	DSP_N_CS	CS	O	O	O	[O]		DA70Y chip select
18	P86 P86/Xcout	DAC_N_CS	CS	O	O	O	[O]		DAC chip select

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	StbyThrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
19	/RESET /RESET	/RESET	MCU	MCU	MCU	MCU	[MCU]		Reset
20	Xout Xout	Xout	MCU	MCU	MCU	MCU	[MCU]		20 MHz ceramic resonator
21	Vss Vss	Vss	MCU	MCU	MCU	MCU	[MCU]		GND
22	Xin Xin	Xin	MCU	MCU	MCU	MCU	[MCU]		20 MHz ceramic resonator
23	Vcc1 Vcc1	Vcc1	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
24	/NMI P85/NMI	/NMI	MCU	MCU	MCU	MCU	[MCU]		Unused, pull up to Vcc
25	INT2 P84/INT2	HDMI_MUT	IRQ	IRQ	O	O	[O]		HDMI mute input H: Mute
26	INT1 P83/INT1	HDMI_INT	IRQ	IRQ	O	O	[O]		Interrupt from HDMI RX
27	INT0 P82/INT0	HEQ_N_INT	IRQ	IRQ	O	O	O		Interrupt from HDMI INPUT EQ While CEC microprocessor is in use, interruptive CEC microprocessor may be used
28	P81 P81/TA4in/U/ INPC15/OUTC15/ CTS5/RTS5/RTP23	DSP_N_RDY	I	I	O	O	[O]		DA70Y RDY
29	RXD5 P80/TA4out/U/ ISRXD0/RXD5	DSP_MISO	SI	I	O	O	[O]		Synchronous data input for DIR, DA70Y, DAC
30	CLK5 P77/TA3in/INPC14/ OUTC14/ISCLK0/ CLK5/RTP22	DSP_SCK	SO	O	O	O	[O]		Synchronous clock output for DIR, DA70Y, DAC
31	TXD5 P76/TA3out/INPC13/ OUTC13/ISTXD0/ TXD5	DSP_MOSI	SO	O	O	O	[O]		Synchronous data output for DIR, DA70Y, DAC
32	P75 P75/TA2in/W/ INPC12/OUTC12/ ISRXD1/RTP21	DIR_N_RST	O	O	O	O	[O]		DIR reset
33	P74 P74/TA2out/W/ INPC11/OUTC11/ ISCLK1/RTP20	DSP_FMT	O	O	O	O	[O]		DA70Y full mute output H: Mute
34	TA1in P73/TA1in/V/CTS2/ RTS2/SS2/INPC10/ OUTC10/ISTXD1	232C_MISO	TMR	TMR	TMR	TMR	[O]		RS232C reception detection Uses for the return trigger from stop mode (MCUSleep)
35	P72 P72/TA1out/V/CLK2	SEL_CDDA	O	O	O	O	[O]		CDDA writing route select H: CDDA writing mode L: Operational mode usually
36	SCL2 P71/TA0in/TB5in/ RXD2/SCL2/STXD2/ INPC17/OUTC17/ OUTC22/ISRXD2/ IEin/RTP03	CEC_SCL	SO	SO	O	O	[O]		CEC microprocessor, Tuner, HDMI_EQ (SiI9185A) I2C SCL output U-com block then +3.3S, 3.3k then pull up (100 kHz device)
37	SDA2 P70/TA0out/TXD2/ SDA2/SRXD2/ INPC16/OUTC16/ OUTC20/ISTXD2/ IEout/RTP02	CEC_SDA	SIO	SIO	O	O	[O]		CEC microprocessor, Tuner, HDMI_EQ (SiI9185A) I2C SDA input U-com block then +3.3S, 3.3k then pull up (100 kHz device)

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	Stby Thrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
38	TxD1	232C_MOSI	SO	SO	SO	O	[O]		RS232C data output Pull up at 100 k-ohms
	P67/TXD1/SDA1/SRXD1								
	TxD1	TXD						SO	E8a, ICP (In-Circuit Programmer) data output
39	Vcc1	Vcc1	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
	Vcc1								
40	RxD1	232C_MISO	SI	SI	SI	I	[I]		RS232C data input Pull up at 100 k-ohms
	P66/RXD1/SCL1/STXD1								
	RxD1	RXD						SI	E8a, ICP (In-Circuit Programmer) data input
41	Vss	Vss	All	MCU	MCU	MCU	[MCU]		Microprocessor GND
	Vss								
42	P65	232C_RTS	SO	SO	SO	O	[O]		RS232C CTS input
	P65/CLK1								
	CLK1	E8a_SCLK						SI	E8a, ICP (In-Circuit Programmer) clock input Pull up at 100 k-ohms
43	CTS1	232C_CTS	SI	SI	SI	I	[I]		RS232C CTS input Pull down at 100 k-ohms
	P64/CTS1/RTS1/SS1/OUTC21/ISCLK2								
	RTS1	E8a_BUSY						SO	E8a, ICP (In-Circuit Programmer) BUSY output
44	SDA0	HDMI_SDA	SIO	SIO	O	O	[O]		HDMI RX/TX, Video Enc/Dec I2C SCL output Pull up at HDMI block HDMI RX/TX: 5V tolerant (400 kHz device)
	P63/TXD0/SDA0/SRXD0/IrDAout								
45	SCL0	HDMI_SCL	SIO	SIO	O	O	[O]		HDMI RX/TX, Video Enc/Dec I2C SDA input/output Pull up at HDMI block HDMI RX/TX: 5V tolerant (400 kHz device)
	P62/RXD0/SCL0/STXD0/IrDAin								
46	P61	232C_PON	O	O	O	O	[O]		RS232C driver power supply ON/OFF control H: ON, L: OFF Default at standby U, C models: H (232C ON) R, T, K, A, B, G, E, F, L models: L
	P61/CLK0/RTP01								
47	P60	CXB1442_CE	O	O	O	O	[O]		FRONT HDMI EQ chip enable output Pull down at FRONT HDMI block H: enable When CEC microprocessor is used, it substitutes it with HDMI_PON (Pin 60)
	P60/CTS0/RTS0/SS0/RTP00								
48	P137	HEQ_N_RST	O	O	O	O	[O]	O	HDMI INPUT EQ reset output Pull up at HDMI EQ block L: Reset When CEC microprocessor is used, it substitutes it with HDMI_PON (Pin 60)
	P137/OUTC27								
49	ISCLK2	REM_CLK	SO	O	O	O	[O]		Clock output for remote control code generation No connection destination
	P136/OUTC21/ISCLK2								
50	P135	HTX_N_RST2	O	O	O	O	[O]		HDMI TX (OUT2) reset output Pull down at HDMI block L: Reset
	P135/OUTC22/ISRXD2/IEin								
51	ISTXD2	REM_OUT	SO	O	O	O	[O]		SCENE select DVD control remote control code output
	P134/OUTC20/ISTXD2/leout								
52	P57	HRX_N_RST	O	O	O	O	[O]		HDMI TX reset output Pull down at HDMI block L: Reset
	P57/RDY								
53	P56	HTX_N_RST	O	O	O	O	[O]		HDMI TX (OUT1) reset output Pull down at HDMI block L: Reset
	P56/ALE								
54	P55	E8a_N_EPM	I	I	I	I	[I]		E8a writing mode enable input 10 k-ohms pull down
	P55/HOLD								
55	P54	HTX_AUSEL	O	O	O	O	[O]		
	P54/HLDA/ALE								

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	StbyThrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
56	P133 P133/OUTC23	HTX_VSEL	O	O	O	O	[O]		
57	Vss Vss	Vss	MCU	MCU	MCU	MCU	[MCU]		Microprocessor GND
58	P132 P132/OUTC26	ABT_N_RST	O	O	O	O	[O]		Video I/P & Scaler IC reset VID_PON=L: Low fix L: reset
59	Vcc2 Vcc2	Vcc2	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
60	P131 P131/OUTC25	HDMI_PON	O	O	O	O	[O]		HDMI power supply ON/OFF control When uses CEC microprocessor, HDMI EQ (CXB1442, Sil9185A) reset may be used H: ON, L: OFF
61	P130 P130/OUTC24	VID_PON	O	O	O	O	[O]		Video power supply ON/OFF control Configured based on the Pure Direct specification H: ON, L: OFF
62	P53 P53/CLKout/BCLK/ ALE	SCPU_N_RST	O	O	O	O	[O]		SubCPU reset Because the delay circuit of 2 ms is passed so that it may discriminate against reset of Flash and BlackFin, it is necessary to secure the change time of 5 ms or more
63	P52 P52/RD	SCPU_N_SS	O	O	O	O	[O]		SubCPU slave select
64	P51 P51/WRH/BHE	SCPU_RTS	SO	O	O	O	[O]		Output for SubCPU reception control (request to send)
65	P50 P50/WRL/WR	E8a_N_CE	I	I	I	I	[I]		E8a enable input 10 k-ohms pull up
66	P127 P127	SVID_DET	I	O	O	O	[O]		S video detection VID_PON = L: Low fix
67	P126 P126	DVID_N_RST	O	O	O	O	[O]		Video Enc/Dec reset VID_PON = L: Low fix
68	P125 P125	OSD_N_CS	CS	O	O	O	[O]		OSD chip select VID_PON = L: Low fix
69	P47 P47/SC0/A23	DSP_PON	O	O	O	O	[O]		DSP power supply ON/OFF control H: ON, L: OFF
70	P46 P46/SC1/A22	SPRY_FA	O	O	O	O	[O]		Front A speaker relay control H: ON, L: OFF
71	P45 P45/SC2/A21	SPRY_FB	O	O	O	O	[O]		Front B speaker relay control H: ON, L: OFF
72	P44 P44/SC3/A20	CPNT_DET	O	O	O	O	[O]		No use
73	P43 P43/A19	SPRY_C	O	O	O	O	[O]		Center speaker relay control
74	Vcc2 Vcc2	Vcc2	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
75	P42 P42/A18	SPRY_S	O	O	O	O	[O]		Surround speaker relay control
76	Vss Vss	Vss	MCU	MCU	MCU	MCU	[MCU]		Microprocessor GND
77	P41 P41/A17	VOL_SCK	O	O	O	O	[O]		Electronic volume Flip-flop synchronous clock output
78	P40 P40/A16	VOL_MOSI	O	O	O	O	[O]		Electronic volume Flip-flop synchronous data output
79	P37 P37/A15/(D15)	SPRY_SB	O	O	O	O	[O]		Surround back/Bi-AMP relay control
80	P36 P36/A14/(D14)	SPRY_Z2	O	O	O	O	[O]		Zone2/Presence Speaker relay control SPRY_Z2 and SPRY_FB do not become High at the same time
81	P35 P35/A13/(D13)	SPRY_Z3	O	O	O	O	[O]		Zone3 speaker relay control
82	P34 P34/A12/(D12)	HPRY	O	O	O	O	[O]		Head phone relay control

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	Stby Thrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
83	P33	SP_IMP	O	HiZ	HiZ	HiZ	[HiZ]		Speaker impedance relay control GND pull down Set to 8 ohms: Hi-Z (Relay OFF, B voltage High) Set to 6 ohms plus during rising temperature: High (Relay ON, B voltage Low)
	P33/A11/(D11)								
84	P32	HP_N_DET	I	O	O	O	[O]		Headphone detection +3.3S pull up L: Headphone
	P32/A10/(D10)								
85	P31	E2R_N_CS	CS	CS	CS	I	[I]		EEPROM chip select Pull up to EEPROM power at 10 k-ohms
	P31/A9/(D9)								
86	P124	MUTE_N_Z3	O	O	O	O	[O]		Zone3 line out mute control L: Mute
	P124								
87	P123	MUTE_N_Z2	O	O	O	O	[O]		Zone2 line out mute control L: Mute
	P123/CTS6/RTS6								
88	RXD6	HDR_MISO	SI	I	I	I	[I]		Asynchronous data input for HD Radio To prevent pulling of HD Radio's High output and microprocessor's Low Fix output, switch to constant input (U model)
	P122/RXD6								
	P122	TUN_N_ST	I	O	O	O	[O]		FM/AM tuner STEREO detection input +3.3S to 47k then pull up
89	P121	MUTE_N_SW	O	O	O	O	[O]		Subwoofer mute control L: Mute All
	P121/CLK6								
90	TXD6	HDR_MOSI	SO	O	O	O	[O]		HD Radio asynchronous data output (U model)
	P120/TXD6	HDR_MOSI							
	P120	(TUNCEC_N_EN)	O	O	O	O	[O]		FM/AM tuner CEC enable output Pull up at +3.3SDSP L: Enable, H: Disable (C, R, T, K, A, B, G, E, F, L, J models)
91	Vcc2	Vcc2	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
	Vcc2								
92	P30	MUTE_N_SB	O	O	O	O	[O]		Surround back/Bi-AMP/Zone2 mute control L: Mute
	P30/A8/(D8)								
93	Vss	Vss	MCU	MCU	MCU	MCU	[MCU]		Microprocessor GND
	Vss								
94	P27	HDR_N_RST	O	O	O	O	[O]		HD Radio reset (U model)
	P27	TUN_N_TUND	I	O	O	O	[O]		FM/AM tuner TUNED input +3.3S to 47k then pull up (C, R, T, K, A, B, G, E, F, L, J models)
	P27/A7/(D7)/AN27								
95	P26	HDMI_N_INT_TX	I	I	O	O	O		HDMI TX1,2 interrupts (receive with polling) TUN_N_ST is received by pin 88
	P26/A6/(D6)/AN26								
96	P25	+3.3S_PON	O	O	O	O	[I]		+3.3S power supply ON/OFF control H: ON, L: OFF At standby sleep, becomes L [to avoid unnecessary power consumption (Mute, pull Up)] Input (HiZ) then mechanically +3.3S power switches on (to function Mute, when power down is detected)
	P25/A5/(D5)/AN25								
97	P24	PRY	O	O	O	O	[O]		Power relay ON/OFF control H: ON, L: OFF
	P24/A4/(D4)/AN24								
98	P23	I_PRT	I	I	O	O	[O]		Overcurrent protection detection
	P23/A3/(D3)/AN23								
99	P22	MUTE_N_S	O	O	O	O	[O]		Surround mute control L: Mute
	P22/A2/(D2)/AN22								
100	P21	MUTE_N_C	O	O	O	O	[O]		Center mute control L: Mute
	P21/A1/(D1)/AN21								
101	P20	MUTE_N_F	O	O	O	O	[O]		Front (Headphone is contained) mute control L: Mute
	P20/A0/(D0)/AN20								
102	INT5	ACPWR_DET	IRQ	IRQ	IRQ	IRQ	[O]		AC power detection L: Power down
	P17/D15/INT5								
103	INT4	PSW_DET	IRQ	IRQ	IRQ	IRQ	[O]		Main/Zone/Input key interrupt KEY1 port distinguishes the pressed keys
	P16/D14/INT4								
104	INT3	REM_IN	IRQ	IRQ	IRQ	IRQ	[O]		Remote control pulse input
	P15/D13/INT3								

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	StbyThrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
105	P14	XM_PON	O	O	O	O	[O]		XM Radio power supply ON/OFF control H: ON, L: OFF (U model) (C, R, T, K, A, B, G, E, F, L, J models)
	P14/D12		O	O	O	O	[O]		
106	P13	DOCK_PON	O	O	O	O	[O]		DOCK power supply ON/OFF control H: ON, L: OFF
	P13/D11		O	O	O	O	[O]		
107	P12	IOXV_N_CS	CS	O	O	O	[O]		IO extended IC (for video) chip select
	P12/D10		CS	O	O	O	[O]		
108	P11	IOXV_N_RST	O	O	O	O	[O]		IO extended IC (for video) reset
	P11/D9		O	O	O	O	[O]		
109	P10	PD_LED	O	O	O	O	[O]		Pure Direct LED ON/OFF control H: ON, L: OFF
	P10/D8		O	O	O	O	[O]		
110	P07	FLD_N_RST	O	O	O	O	[O]		FL driver reset
	P07/D7/AN07		O	O	O	O	[O]		
111	P06	PRG_RA	I	O	O	O	[O]		Program rotary A
	P06/D6/AN06		I	O	O	O	[O]		
112	P05	PRG_RB	I	O	O	O	[O]		Program rotary B
	P05/D5/AN05		I	O	O	O	[O]		
113	P04	MIC_N_DET	I	O	O	O	[O]		MIC detection L: MIC
	P04/D4/AN04		I	O	O	O	[O]		
114	P114	IPD_APDET	I	I	I	I	[I]		iPod accessory power detection While iPod boots up (about two seconds) it is set at Low after the boot, it identifies To prevent pulling of iPod High output and microprocessor Low Fix output, switch to constant input
	P114		I	I	I	I	[I]		
115	P113	VOL_RA	I	O	O	O	[O]		Volume rotary A
	P113/INPC13/OUTC13		I	O	O	O	[O]		
116	ISRXD1	SR_MISO	SI	I	I	I	[I]		Asynchronous data input for SIRIUS Pull up at 100 k-ohms Serial communication is 5V TTL/CMOS logic level To prevent pulling of SIRIUS tuner's High output and microprocessor's Low Fix output, switch to constant input (U model) (C, R, T, K, A, B, G, E, F, L, J models)
	P112/INPC12/OUTC12/ISRXD1		SI	I	I	I	[I]		
	P112		O	O	O	O	[O]		
117	P111	VOL_RB	I	O	O	O	[O]		Volume rotary B
	P111/INPC11/OUTC11/ISCLK1		I	O	O	O	[O]		
118	ISTXD1	SR_MOSI	SO	O	O	O	[O]		Asynchronous data output for SIRIUS Serial communication is 5V TTL/CMOS logic level (U model) (C, R, T, K, A, B, G, E, F, L, J models)
	P110/INPC10/OUTC10/ISTXD1		SO	O	O	O	[O]		
	P110		O	O	O	O	[O]		
119	P03	SR_PON	O	O	O	O	[O]		SIRIUS radio power supply ON/OFF control H: Power ON, L: Power OFF (U model) (C, R, T, K, A, B, G, E, F, L, J models)
	P03/D3/AN03		O	O	O	O	[O]		
120	P02	SEL_PD	O	O	O	O	[O]		DSP Pure Direct route select H: Pure Direct ON
	P02/D2/AN02		O	O	O	O	[O]		
121	P01	ADC_N_PDWN	O	O	O	O	[O]		ADC power down L: Power down
	P01/D1/AN01		O	O	O	O	[O]		
122	P00	FLD_N_CS	CS	O	O	O	[O]		FL driver chip select
	P00/D0/AN00		CS	O	O	O	[O]		
123	AN157	L3_DET	I	I	I	O	[O]		No use Pull down at GND
	P157/AN157/CTS6/RTS6		I	I	I	O	[O]		
124	AN156	THM	AD	AD	O	O	[O]		Temperature detection
	P156/AN156/CLK6		AD	AD	O	O	[O]		
125	AN155	AMP_OLV	AD	AD	O	O	[O]		Power AMP output level detection
	P155/AN155/RXD6		AD	AD	O	O	[O]		
126	AN154	DC_PRT	AD	AD	O	O	[O]		Power AMP DC detection
	P154/AN154/TXD6		AD	AD	O	O	[O]		
127	AN153	MODEL	AD	AD	AD	O	[O]		AD destination discrimination Data is taken in when resetting is cancelled
	P153/AN153/CTS5/RTS5		AD	AD	AD	O	[O]		

Pin No.	Port Name	Function Name (P.C.B.)	I/O						Detail of Function
			PowerOn	Stby Thrh	Standby	Stby Sleep	Sleep [MCU]	E8a, ICP	
128	ISRXD0 P152/AN152/ ISRXD0/RXD5	E2R_MISO	SI	SI	SI	O	[O]		Synchronous data input for EEPROM
129	ISCLK0 P151/AN151/ ISCLK0/CLK5	FLD_SCK	SO	SO	SO	O	[O]		FL driver, OSD, IO extended IC (Video), EEPROM synchronous clock output Inhalation attention of power supply off device
130	Vss Vss	Vss	MCU	MCU	MCU	MCU	[MCU]		Microprocessor GND
131	ISTXD0 P150/AN150/ ISTXD0/TXD5	FLD_MOSI	SO	SO	SO	O	[O]		FL driver, OSD, IO extended IC (Video), EEPROM synchronous data output Inhalation attention of power supply off device
132	Vcc1 Vcc1	Vcc1	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
133	AN7 P107/AN7/KI3/ RTP33	KEY1	AD	AD	AD	I	[O]		KEY1 AD value taken in During PSW_DET interruption, distinguishes the used keys which are switched to AD
134	AN6 P106/AN6/KI2/ RTP32	KEY2	AD	AD	AD	I	[O]		KEY2 AD value taken in During PSW_DET interruption, distinguishes the used keys which are switched to AD
135	AN5 P105/AN5/KI1/ RTP31	PS1_PRT	AD	AD	O	O	[O]		PS protection detection 1
136	AN4 P104/AN4/KI0/ RTP30	PS2_PRT	AD	AD	O	O	[O]		PS protection detection 2
137	P103 P103/AN3/RTP13	ISEL_RA	I	O	O	O	[O]		Input selector rotary A
138	P102 P102/AN2/RTP12	ISEL_RB	I	O	O	O	[O]		Input selector rotary B
139	AN1 P101/AN1/RTP11	DEST	AD	AD	AD	O	[O]		AD destination discrimination Data is taken in when resetting is cancelled
140	AVss AVss	AVss	MCU	MCU	MCU	MCU	[MCU]		Microprocessor GND
141	AN0 P100/AN0/RTP10	DOCK_TYPE	AD	AD	AD	I	[O]		DOCK discriminate Make a distinction from IPD_DET Low edge through post-10ms A/D value Identifies the connected DOCK type, then switches the action During IPD_DET interruption, switches to AD, make a distinction based on post-10 ms A/D value
142	Vref Vref	VREF	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
143	AVcc AVcc	AVcc	MCU	MCU	MCU	MCU	[MCU]		Microprocessor power supply
144	RXD4 P97/ADTRG/RXD4/ SCL4/STXD4	SCPU_MISO	SO	I	I	I	[O]		Synchronous data input for SubCPU

Key detection for A/D port

Key input (A/D) pull-up resistance 10 k-ohms

Ohm	0	+1.0k	+1.0k	+1.5k	+1.5k	+2.2k	+3.3k	+4.7k	+22.0k	+33.0k
V	0 – 0.15	0.15 – 0.42	0.43 – 0.70	0.71 – 0.97	0.98 – 1.24	1.25 – 1.53	1.54 – 1.84	1.84 – 2.1	2.34 – 2.55	2.55 – 2.97
A/D value (3.3 V=255)	0 – 11	12 – 32	33 – 54	55 – 75	76 – 95	96 – 118	119 – 142	143 – 162	181 – 197	198 – 229
KEY1 (133 pin)	SCENE RADIO	SCENE CD	SCENE TV	SCENE BD/DVD	ZONE2 ON/OFF	ZONE3 ON/OFF	—	—	MAIN ZONE ON/OFF	ZONE CONTROL

Ohm	0	+1.0k	+1.0k	+1.5k	+1.8k	+2.2k	+3.3k	+4.7k	+6.8k	+10.0k
V	0 – 0.15	0.15 – 0.42	0.43 – 0.70	0.71 – 0.99	1.0 – 1.27	1.28 – 1.56	1.57 – 1.86	1.86 – 2.14	2.14 – 2.4	2.4 – 2.65
A/D value (3.3 V=255)	0 – 11	12 – 32	33 – 54	55 – 77	78 – 98	99 – 120	121 – 143	144 – 165	166 – 185	186 – 205
KEY2 (134 pin)	PURE DIRECT	STRAIGHT / EFFECT	ZONE CONTROLS	INFO	PRESET <	PRESET >	MEMORY	BAND/ CATEGORY	TUNING CH <	TUNING CH >

Destination detection for A/D port

Destination input (A/D) pull-up resistance 10 k-ohms

Ohm (R3809 VIDEO P.C.B.)	1.2 k	2.7 k	4.7 k	6.8 k	10.0 k	15.0 k	47.0 k	100.0 k
V	0.2 – 0.6	0.6 – 0.9	0.9 – 1.2	1.2 – 1.5	1.5 – 1.8	1.8 – 2.3	2.4 – 2.9	2.9 – 3.2
A/D value (3.3V=255)	15 – 46	46 – 69	69 – 92	92 – 115	115 – 139	139 – 177	185 – 224	224 – 247
DEST (139 pin)	U	C	R	T	K	A	B, G, E, F	L


Model detection for A/D port

Ohm (R200 DIGITAL P.C.B.)	—	10 k
Ohm (R201 DIGITAL P.C.B.)	1 k	1 k
V	0	0.2 – 0.6
A/D value (3.3 V=255)	0	15 – 46
MODEL (127 pin)	RX-V2065	HTR-6295

IC505: AD91089ZSKBC (GUI P.C.B.)

Sub-microprocessor

* **No replacement part available.**



Memory Interface

Pin No.	Function Name	I/O	Detail of Function
121	ADDR19	O	Address bus for async/Sync access
122	ADDR18		
123	ADDR17		
124	ADDR16		
125	ADDR15		
126	ADDR14		
127	ADDR13		
135	ADDR12	O	Address bus for async/Sync access
136	ADDR11		
137	ADDR10		
138	ADDR9		
139	ADDR8		
140	ADDR7		
141	ADDR6		
142	ADDR5	O	Address bus for async/Sync access
146	ADDR4		
147	ADDR3		
148	ADDR2		
149	ADDR1		
98	DATA15	I/O	Data bus for async access
99	DATA14		
100	DATA13		
101	DATA12		
102	DATA11		
103	DATA10		
104	DATA9		
105	DATA8	I/O	Data bus for async access
108	DATA7		
109	DATA6		
110	DATA5		
112	DATA4		
113	DATA3		
114	DATA2	I/O	Data bus for async access
115	DATA1		
116	DATA0		
150	ABE1	O	Byte enables/Data masks for async/Sync access
151	ABE0		
163	BR	I	Bus request (This pin should be pulled HIGH if not used.)
119	BG	O	Bus grant
120	BGH	O	Bus grant hang

Asynchronous memory control

Pin No.	Function Name	I/O	Detail of Function
158	AMS3	O	Banks select
159	AMS2		
160	AMS1		
161	AMS0		
162	ARDY	I	Hardware ready control (This pin should be pulled HIGH if not used.)
154	AOE	O	Output enable
153	ARE	O	Read enable
152	AWE	O	Write enable

Synchronous memory control

Pin No.	Function Name	I/O	Detail of Function
167	SRAS	O	Row address strobe
166	SCAS	O	Column address strobe
165	SWE	O	Write enable
173	SCKE	O	Clock enable
169	CLKOUT	O	Clock output
164	SA10	O	A10 pin
172	SMS	O	Bank select

Timers

Pin No.	Function Name	I/O	Detail of Function
79	TMR0	I/O	Timer0
78	PPI_FS1	I/O	Timer1/PPI frame sync1
77	PPI_FS2	I/O	Timer2/PPI frame sync2

PPI port

Pin No.	Function Name	I/O	Detail of Function
22	PP10	I/O	PPI3-0
23	PP11		
24	PP12		
26	PP13		
21	PPI_CLK	I	PPI clock/External timer reference

Port F: GPIO/Parallel peripheral interface port/SPI/Timers

Pin No.	Function Name	I/O	Detail of Function
51	N_SPISS	I/O	GPIO/SPI slave select input
50	PF1	I/O	GPIO/SPI slave select enable 1/ Timer alternate clock input
49	PF2	I/O	GPIO/SPI slave select enable 2
48	PPI_PS3	I/O	GPIO/SPI slave select enable 3/ PPI frame sync 3
47	PF4	I/O	GPIO/SPI slave select enable 4/ PPI 15
46	PF5	I/O	GPIO/SPI slave select enable 5/ PPI 14
38	PF6	I/O	GPIO/SPI slave select enable 6/ PPI 13
37	PF7	I/O	GPIO/SPI slave select enable 7/ PPI 12
36	PF8	I/O	GPIO/PPI 11
35	PF9	I/O	GPIO/PPI 10
34	PF10	I/O	GPIO/PPI 9
33	PF11	I/O	GPIO/PPI 8
32	PPI7	I/O	GPIO/PPI 7
29	PPI6	I/O	GPIO/PPI 6
28	PPI5	I/O	GPIO/PPI 5
27	PPI4	I/O	GPIO/PPI 4

JTAG port

Pin No.	Function Name	I/O	Detail of Function
94	TCK	I	JTAG clock
87	TDO	O	JTAG serial data out
86	TDI	I	JTAG serial data in
85	TMS	I	JTAG mode select
84	TRST	I	JTAG reset (This pin is should be pulled LOW if JTAG is not used.)
83	EMU	O	Emulation output

SPI port

Pin No.	Function Name	I/O	Detail of Function
55	MOSI	I/O	Master out slave in
54	MISO	I/O	Master in slave out (This pin is should be pulled HIGH through a 4.7 k-ohms resistor if booting via the SPI port.)
53	SCK	I/O	SPI clock

Serial ports

Pin No.	Function Name	I/O	Detail of Function
76	RSCLK0	I/O	SPORT0 receive serial clock
75	RFS0	I/O	SPORT0 receive frame sync
74	DR0PRI	I	SPORT0 receive data primary
73	DR0SEC	I	SPORT0 receive data secondary
72	TSCLK0	I/O	SPORT0 transmit serial clock
69	TFS0	I/O	SPORT0 transmit frame sync
68	DT0PRI	O	SPORT0 transmit data primary
67	DT0SEC	O	SPORT0 transmit data secondary
65	RSCLK1	I/O	SPORT1 receive serial clock
64	RFS1	I/O	SPORT1 receive frame sync
63	DR1PRI	I	SPORT1 receive data primary
62	DR1SEC	I	SPORT1 receive data secondary
61	TSCLK1	I/O	SPORT1 transmit serial clock
60	TFS1	I/O	SPORT1 transmit frame sync
59	DT1PRI	O	SPORT1 transmit data primary
58	DT1SEC	O	SPORT1 transmit data secondary

UART port

Pin No.	Function Name	I/O	Detail of Function
82	RX	I	UART receive
81	TX	O	UART transmit

Real-time clock

Pin No.	Function Name	I/O	Detail of Function
17	RTXI	I	RTC crystal input (This pin should be pulled LOW when not used.)
16	RTXO	O	RTC crystal output

Clock

Pin No.	Function Name	I/O	Detail of Function
10	CLKIN	I	Clock/Crystal input (This pin needs to be at a level or clocking.)
11	XTAL	O	Crystal output

Mode controls

Pin No.	Function Name	I/O	Detail of Function
13	RESET	I	Reset (This pin is always active during core power-on.)
14	NMI	I	Nonmaskable interrupt (This pin should be pulled LOW when not used.)
95	BMODE1	I	Boot mode strap (These pins must be pulled to the state required for the desired boot mode.)
96	BMODE0		

Voltage regulator























Pin No.	Function Name	I/O	Detail of Function
4	VROUT1	O	External FET drive
5	VROUT0		

Supplies

































Pin No.	Function Name	I/O	Detail of Function	Pin No.	Function Name	I/O	Detail of Function
6	VDDEXT	P	I/O power supply	1	GND	G	External ground
12				2			
20				3			
31				7			
45				8			
57				9			
71				15			
93				19			
107				30			
118				39			
134				40			
145				41			
156				42			
171				43			
25	VDDINT	P	Core power supply	44			
52				56			
66				70			
80				88			
111				89			
143				90			
157				91			
168				92			
18	VDDRTC	P	Real-time clock power supply	97			
				106			
				117			
				128			
				129			
				130			
				131			
				132			
				133			
				144			
				155			
				170			
				174			
				175			
				176			

PIN CONNECTION DIAGRAMS














ICs

74LVC08APW 74LVC32APW	74LVC1G08GW	74LVC245APW,118	CS230003-CZZR	CXB1442AR-T4
				
ABT1012Q100 LAN9217-MT SiI9134CTU	ADV7800BSTZ-80 AD91089ZSKBC		ADV7172KST AK8814VQ	BA00JC5WT-V5
				
BD9323EFJ-E2	D70YE101BRFP266 M3087BFKBGP SiI9233ACTU	FHP3350IM14X	K4S641632N-LC60000	
				
F2621E-01-TR	ISL83385EIBZ-T	ISP1760BE	KIA7912PI	K4S560832J-UC75000
				
K8P6415UQB-PI4B000	LA73050-TLM-E	LC709004A-TLM-E	LC72725KM-UY-TLM-E	
				
















RX-V2065/HTR-6295

LC89058WD-E 	LE25LB2562M-TLM-E LE25LB643M-TLM-E NJM4565M (TE1) 	LM19CIZ/LF 	M66003-0131FP-R 	NE5532DR 	NJM2068MD-TE2 
NJM2388F05 	NJM2396F05 	NJM2581M 	NJM2867F3-05 	NJM7812FA 	NJM78M05DL1A (TE1) 
PCA9517DP 	PCM1680DBQR 	PCM1781DBQR SN74LV163APWR 	PCM1803DBR 	R1172H181B-T1-F R1172H331D-T1-F R1172H501D-T1-F 	
R1173S001D-E2-F R1172S121D-E2-F R1172S331B-E2-F 	R2A15220FP 	R5523N001A-TR-F 	SN74LVC245APWR SN74LVTH245APW 	SN74LV74APWR 	
SiI9185ACTU 	TC74HC4051AFEL 	TC74HC4053AF 	TC74VHC157FT 	TC74VHCT08AFT TC74VHCU04FT 	
TC7SH04FU-TE85L TC7SH08FU 	TC7WH14FK TC7WZ32FK (TE85L, F) 	TC7WHU04FU 	TL431ACLPR 	TOP255MN 	

• Diodes

1N4002S 1SS133 1SS176	1SS355	D15XBN20-7001 15A		HT18G
				
MAZ8033GHL 3.4V MAZ8036GLL 3.5V	MTZJ10B MTZJ12B MTZJ13B MTZJ2.4B MTZJ22C MTZJ3.3B MTZJ39D		RB051L-40 UDZ5.1B	P6KE100A
				
MA111 RB501V-40	RLZ7.5B 7.5V	RS203M-B-C-J80	S1NBC60 1A 600V	SG10SC4M
				


• Transistors

2N5401C-AT/P 2SA1015-Y		2SA1145 2SC2705 2N5551C-AT		2SA1708		2SA2168 2SC5291		2SC6011/2SA2151	
2SC1815 Y		2SC1740S		2SC4081 T106		2SD1938F 2SC3906K		DTA114EKA DTA143EKA DTA144EKA DTC114EKA DTC144EKA	
KRA102M-AT/P KRC105M-AT		KA1A1046-Y-U/P KA1A1837-U/P		KTA1517S KTC3875S KTC3911S		MCH6336-TL-E		μPA672T-T1-A	


■ BLOCK DIAGRAMS

MAIN • See page 132, 133 →
SCHEMATIC DIAGRAM

ANALOG AUDIO Section Block Diagram



DIGITAL AUDIO Section Block Diagram



PRINTED CIRCUIT BOARDS

DIGITAL (1) P.C.B. (Side A)

GUI (CB503)
No replacement part available.

OPERATION (2)

(CB452)

OPERATION (2)

(CB455)

OPERATION (2)

(CB458)

GUI

(CB500)


OPERATION (1)

(CB401)


DIGITAL (2)

(CB36)


POINT ④ XL20 (Pin 20 of IC20)




POINT ⑤ ① CB24 (+3.3M), ② CB24 (RESET)




POINT ⑥ XL41 (Pin 28 of IC40)




POINT ⑦ XL42 (Pin 29 of IC41)



POINT ⑧ XL70 (Pin 80 of IC70)



POINT ⑨ XL1 (Pin 5 of IC4)



POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)

VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

POWER ON
HDMI 1
HDMI 2
HDMI 3
HDMI 4

POWER OFF
HDMI 1
HDMI 2
HDMI 3
HDMI 4

VIDEO (1)
(CB34)

VIDEO (2)
(CB34)

VIDEO (3)
(CB34)

VIDEO (4)
(CB34)

VIDEO (5)
(CB34)

VIDEO (6)
(CB34)

VIDEO (7)
(CB34)

VIDEO (8)
(CB34)

VIDEO (9)
(CB34)

VIDEO (10)
(CB34)

VIDEO (11)
(CB34)

VIDEO (12)
(CB34)

VIDEO (13)
(CB34)

VIDEO (14)
(CB34)

VIDEO (15)
(CB34)

VIDEO (16)
(CB34)

VIDEO (17)
(CB34)

VIDEO (18)
(CB34)

VIDEO (19)
(CB34)

VIDEO (20)
(CB34)


VIDEO (21)
(CB34)

VIDEO (22)
(CB34)

VIDEO (23)
(CB34)

Ref no.	Location	Ref no.	Location
D150	C2	IC44	C4
D151	C2	IC45	C4
D152	C2	IC47	D5
D200	D5	IC49	C5
D400	C2	IC50	D4
D401	C2	IC51	D5
D402	C2	IC52	D4
D403	C2	IC61	C3
D406	D5	IC62	C4
D407	C5	IC63	C4
IC1	G3	IC65	C4
IC2	E3	IC66	C4
IC3	F4	IC67	B5
IC4	E4	IC68	B5
IC5	F4	IC70	G4
IC6	D3	IC71	F5
IC7	D3	IC72	G4
IC8	F6	IC73	G6
IC9	F6	IC74	G6
IC10	D3	IC75	G4
IC11	D3	IC76	E4
IC15	D3	IC77	E4
IC16	C2	IC78	D4
IC20	E5	IC80	D5
IC21	D5	IC81	C5
IC22	C6	IC82	C5
IC40	D3	IC83	G6
IC41	C4	IC84	D5
IC43	B3	IC85	G3

DIGITAL (1) P.C.B. (Side B)





• Semiconductor Location

Ref no.	Location
D62	D2
D153	D2
D201	E5
D202	E5
D203	E5
D204	E6
D404	C2
D600	C4
D602	C4
D603	C4
D702	G6
D703	G5
IC48	C5
Q3	G3
Q4	G3
Q5	F3
Q6	F3
Q7	F3
Q8	E3
Q9	E3
Q10	E3
Q201	E5
Q202	E5
Q203	E6
Q204	E6
Q205	D5
Q206	D5
Q207	D6
Q208	D6
Q209	D6
Q600	B5
Q601	B5
Q701	G6
Q703	B5

DIGITAL (2) P.C.B. (Side B)

DIGITAL (3) P.C.B.




U model

- Semiconductor Location


Ref no.	Location
D962	C3
D963	G4
D964	F4
Q95	C4
Q96	C4

OPERATION (1) P.C.B.



Ref no.	Location
D4008	F5
D4009	I3
D4011	D3
Q4005	D3


OPERATION (1) P.C.B.




- Semiconductor Location

Ref no.	Location
D4001	D5
D4002	D5
D4003	D4
D4004	C4
D4005	C4
D4006	H3
D4007	H3
IC401	D5
IC402	E3
Q4001	F3
Q4002	F3
Q4003	F3
Q4004	C4
Q4006	F3
Q4007	G3
Q4008	F3
Q4009	F3
Q4010	E5
Q4011	I3
Q4012	F3

OPERATION (2) P.C.B. (Side A)




OPERATION (2) P.C.B. (Side B)





• Semiconductor Location

Ref no.	Location
IC451	E4
IC452	F4
IC453	F4
IC454	G4


(Side A)



(Side A)



R SURROUND BACK/ L




Semiconductor Location

Ref no.	Location
D3201	E5
D3202	E5
D3202	O6
D3304	E6
D3307	E6
D3314	O6
IC331	O6
IC332	D6
IC333	O6
IC334	D6
Q3201	E5
Q3202	E5
Q3302	E6
Q3303	E6
Q3304	E6
Q3305	F6

AM/FM TUNER
C. R. T. K. A. B. G. E. F. L. models


VIDEO (1) P.C.B. (Side B)




• Semiconductor Location

Ref no.	Location
D3309	B6
D3310	D6
D3311	C6
D3313	C6
D3320	F4
D3403	G3
D3404	I3
D3405	H3
D3406	H3
IC301	D3
IC302	E4
IC303	B4
IC305	D3
IC306	E3
IC307	C3
IC308	C3
IC310	C4
IC321	E4
Q3001	C3
Q3405	F4
Q3406	F4
Q3407	G3
Q3408	G3
Q3409	I3
Q3410	I3
Q3411	H3
Q3412	H3
Q3413	H3
Q3414	H3


VIDEO (4) P.C.B.



VIDEO (6) P.C.B.




VIDEO (9) P.C.B.




- Semiconductor Location

Ref no.	Location
D3306	C6
D3308	C6
Q3301	D6
Q3801	D3
Q3802	E3

VIDEO (3) P.C.B.




VIDEO (4) P.C.B.




VIDEO (9) P.C.B.

B, G, E, F models



VIDEO (6) P.C.B.




- Semiconductor Location

Ref no.	Location
D3601	H2
D3602	H2
D3801	D3
D3802	D3
D3803	D3
D3804	D3
D3805	D3
D3901	H6
D3902	H6
IC391	H6
Q3803	D3

GUI P.C.B. (Side A)

NETWORK

No replacement part available.




No replacement part available.

- SCPU_N_RST
- SCPU_CTS
- SCPU_SCK
- SCPU_RST
- IPD_MISO_BF
- SCPU_MISO_BF
- SCPU_MISO_RST
- HDMI_SCL
- HDMI_SDA
- VE
- GUI_CBS_SY
- VE
- GUI_SC

DIGITAL (1)
(CB28)


GUI P.C.B. (Side B)



• Semiconductor Location

Ref no.	Location	Ref no.	Location	Ref no.	Location
IC501	D4	IC509	C4	IC523	C4
IC502	D4	IC510	B5	IC524	D4
IC503	D4	IC511	B5	IC525	C4
IC504	D4	IC512	B5	IC526	C4
IC505	C5	IC513	B4	IC551	C3
IC506	D5	IC514	A4	IC552	D2
IC507	B4	IC521	D5	IC553	B3
IC508	C4	IC522	D5	Q5000	D5


ACDC (1) P.C.B.



Notes)

Safety measures

- Some internal parts in this product contain high voltages and are dangerous. Be sure to take safety measures during servicing, such as wearing insulating gloves.
- Note that positions indicated below are dangerous even after the power is turned off because an electric charge remains and a high voltage continues to exist there. Before starting any repair work, perform discharge by connecting a discharge resistor (5k-ohms/10W) between terminals at following positions. The time required for discharging is about 30 seconds.
G6006 on ACDC (1) PC B.



- Semiconductor Location

Ref no.	Location
D6001	D3
D6002	E4
D6003	C4
D6004	D4
D6005	C4
D6006	D4
D6007	C5
D6008	C5
D6009	J2
IC601	D4
IC602	E4
IC603	E5
IC604	C5

1

2

3


4

5

6

7


ACDC (2) P.C.B. (Side A)
U, C, T, K, A, B, G, E, F models




ACDC (2) P.C.B. (Side B)
U, C, T, K, A, B, G, E, F models



ACDC (3) P.C.B. (Side A)




ACDC (3) P.C.B. (Side B)



• Semiconductor Location


Ref no.	Location
IC611	C6






IC1, 2: SI9195ACTU

HDMI switch




IC3: TC7SH40UTEEL

Inverter



IC4: SI9195ACTU


HDMI receiver




NOTICE (continued)

REMARK	REMARK
1. All voltages are measured with a 10MΩV DC electronic voltmeter.	
2. Components having special characteristics are marked Δ and must be replaced with parts having special characteristics.	
3. Schematic diagram is subject to change without notice.	


REMARK	REMARK
1. All voltages are measured with a 10MΩV DC electronic voltmeter.	
2. Components having special characteristics are marked Δ and must be replaced with parts having special characteristics.	
3. Schematic diagram is subject to change without notice.	






* All voltages are measured with a 10MΩV DC electronic voltmeter.
* Components having special characteristics are marked Δ and must be replaced with parts having the same characteristics as the original part.
* Schematic diagram is subject to change without notice.

- ★ All voltages are measured with a 10M Ω V DC electronic voltmeter.
- ★ Components having special characteristics are marked Δ , and must with parts having specifications equal to those originally installed.
- ★ Schematic diagram is subject to change without notice.



RECEIVER SPEC. 1/2			
ITEM	UNIT	VALUE	REMARK
1	POWER	100W	
2	INPUT	100V	
3	OUTPUT	100V	
4	INPUT	100V	
5	OUTPUT	100V	
6	INPUT	100V	
7	OUTPUT	100V	
8	INPUT	100V	
9	OUTPUT	100V	
10	INPUT	100V	
11	OUTPUT	100V	
12	INPUT	100V	
13	OUTPUT	100V	
14	INPUT	100V	
15	OUTPUT	100V	
16	INPUT	100V	
17	OUTPUT	100V	
18	INPUT	100V	
19	OUTPUT	100V	
20	INPUT	100V	
21	OUTPUT	100V	
22	INPUT	100V	
23	OUTPUT	100V	
24	INPUT	100V	
25	OUTPUT	100V	
26	INPUT	100V	
27	OUTPUT	100V	
28	INPUT	100V	
29	OUTPUT	100V	
30	INPUT	100V	
31	OUTPUT	100V	
32	INPUT	100V	
33	OUTPUT	100V	
34	INPUT	100V	
35	OUTPUT	100V	
36	INPUT	100V	
37	OUTPUT	100V	
38	INPUT	100V	
39	OUTPUT	100V	
40	INPUT	100V	
41	OUTPUT	100V	
42	INPUT	100V	
43	OUTPUT	100V	
44	INPUT	100V	
45	OUTPUT	100V	
46	INPUT	100V	
47	OUTPUT	100V	
48	INPUT	100V	
49	OUTPUT	100V	
50	INPUT	100V	
51	OUTPUT	100V	
52	INPUT	100V	
53	OUTPUT	100V	
54	INPUT	100V	
55	OUTPUT	100V	
56	INPUT	100V	
57	OUTPUT	100V	
58	INPUT	100V	
59	OUTPUT	100V	
60	INPUT	100V	
61	OUTPUT	100V	
62	INPUT	100V	
63	OUTPUT	100V	
64	INPUT	100V	
65	OUTPUT	100V	
66	INPUT	100V	
67	OUTPUT	100V	
68	INPUT	100V	
69	OUTPUT	100V	
70	INPUT	100V	
71	OUTPUT	100V	
72	INPUT	100V	
73	OUTPUT	100V	
74	INPUT	100V	
75	OUTPUT	100V	
76	INPUT	100V	
77	OUTPUT	100V	
78	INPUT	100V	
79	OUTPUT	100V	
80	INPUT	100V	
81	OUTPUT	100V	
82	INPUT	100V	
83	OUTPUT	100V	
84	INPUT	100V	
85	OUTPUT	100V	
86	INPUT	100V	
87	OUTPUT	100V	
88	INPUT	100V	
89	OUTPUT	100V	
90	INPUT	100V	
91	OUTPUT	100V	
92	INPUT	100V	
93	OUTPUT	100V	
94	INPUT	100V	
95	OUTPUT	100V	
96	INPUT	100V	
97	OUTPUT	100V	
98	INPUT	100V	
99	OUTPUT	100V	
100	INPUT	100V	
101	OUTPUT	100V	
102	INPUT	100V	
103	OUTPUT	100V	
104	INPUT	100V	
105	OUTPUT	100V	
106	INPUT	100V	
107	OUTPUT	100V	
108	INPUT	100V	
109	OUTPUT	100V	
110	INPUT	100V	
111	OUTPUT	100V	
112	INPUT	100V	
113	OUTPUT	100V	
114	INPUT	100V	
115	OUTPUT	100V	
116	INPUT	100V	
117	OUTPUT	100V	
118	INPUT	100V	
119	OUTPUT	100V	
120	INPUT	100V	
121	OUTPUT	100V	
122	INPUT	100V	
123	OUTPUT	100V	
124	INPUT	100V	
125	OUTPUT	100V	
126	INPUT	100V	
127	OUTPUT	100V	
128	INPUT	100V	
129	OUTPUT	100V	
130	INPUT	100V	
131	OUTPUT	100V	
132	INPUT	100V	
133	OUTPUT	100V	
134	INPUT	100V	
135	OUTPUT	100V	
136	INPUT	100V	
137	OUTPUT	100V	
138	INPUT	100V	
139	OUTPUT	100V	
140	INPUT	100V	
141	OUTPUT	100V	
142	INPUT	100V	
143	OUTPUT	100V	
144	INPUT	100V	
145	OUTPUT	100V	
146	INPUT	100V	
147	OUTPUT	100V	
148	INPUT	100V	
149	OUTPUT	100V	
150	INPUT	100V	
151	OUTPUT	100V	
152	INPUT	100V	
153	OUTPUT	100V	
154	INPUT	100V	
155	OUTPUT	100V	
156	INPUT	100V	
157	OUTPUT	100V	
158	INPUT	100V	
159	OUTPUT	100V	
160	INPUT	100V	
161	OUTPUT	100V	
162	INPUT	100V	
163	OUTPUT	100V	
164	INPUT	100V	
165	OUTPUT	100V	
166	INPUT	100V	
167	OUTPUT	100V	
168	INPUT	100V	
169	OUTPUT	100V	
170	INPUT	100V	
171	OUTPUT	100V	
172	INPUT	100V	
173	OUTPUT	100V	
174	INPUT	100V	
175	OUTPUT	100V	
176	INPUT	100V	
177	OUTPUT	100V	
178	INPUT	100V	
179	OUTPUT	100V	
180	INPUT	100V	
181	OUTPUT	100V	
182	INPUT	100V	
183	OUTPUT	100V	
184	INPUT	100V	
185	OUTPUT	100V	
186	INPUT	100V	
187	OUTPUT	100V	
188	INPUT	100V	
189	OUTPUT	100V	
190	INPUT	100V	
191	OUTPUT	100V	
192	INPUT	100V	
193	OUTPUT	100V	
194	INPUT	100V	
195	OUTPUT	100V	
196	INPUT	100V	
197	OUTPUT	100V	
198	INPUT	100V	
199	OUTPUT	100V	
200	INPUT	100V	
201	OUTPUT	100V	
202	INPUT	100V	
203	OUTPUT	100V	
204	INPUT	100V	
205	OUTPUT	100V	
206	INPUT	100V	
207	OUTPUT	100V	
208	INPUT	100V	
209	OUTPUT	100V	
210	INPUT	100V	
211	OUTPUT	100V	
212	INPUT	100V	
213	OUTPUT	100V	
214	INPUT	100V	
215	OUTPUT	100V	
216	INPUT	100V	
217	OUTPUT	100V	
218	INPUT	100V	
219	OUTPUT	100V	
220	INPUT	100V	
221	OUTPUT	100V	
222	INPUT	100V	
223	OUTPUT	100V	
224	INPUT	100V	
225	OUTPUT	100V	
226	INPUT	100V	
227	OUTPUT	100V	
228	INPUT	100V	
229	OUTPUT	100V	
230	INPUT	100V	
231	OUTPUT	100V	
232	INPUT	100V	
233	OUTPUT	100V	
234	INPUT	100V	
235	OUTPUT	100V	
236	INPUT	100V	
237	OUTPUT	100V	
238	INPUT	100V	
239	OUTPUT	100V	
240	INPUT	100V	
241	OUTPUT	100V	
242	INPUT	100V	
243	OUTPUT	100V	
244	INPUT	100V	
245	OUTPUT	100V	
246	INPUT	100V	
247	OUTPUT	100V	
248	INPUT	100V	
249	OUTPUT	100V	
250	INPUT	100V	
251	OUTPUT	100V	
252	INPUT	100V	
253	OUTPUT	100V	
254	INPUT	100V	
255	OUTPUT	100V	
256	INPUT	100V	
257	OUTPUT	100V	
258	INPUT	100V	
259	OUTPUT	100V	
260	INPUT	100V	
261	OUTPUT	100V	
262	INPUT	100V	
263	OUTPUT	100V	
264	INPUT	100V	
265	OUTPUT	100V	
266	INPUT	100V	
267	OUTPUT	100V	
268	INPUT	100V	
269	OUTPUT	100V	
270	INPUT	100V	
271	OUTPUT	100V	
272	INPUT	100V	
273	OUTPUT	100V	
274	INPUT	100V	
275	OUTPUT	100V	
276	INPUT	100V	
277	OUTPUT	100V	
278	INPUT	100V	
279	OUTPUT	100V	
280	INPUT	100V	
281	OUTPUT	100V	
282	INPUT	100V	
283	OUTPUT	100V	
284	INPUT	100V	
285	OUTPUT	100V	
286	INPUT	100V	
287	OUTPUT	100V	
288	INPUT	100V	
289	OUTPUT	100V	
290	INPUT	100V	
291	OUTPUT	100V	
292	INPUT	100V	
293	OUTPUT	100V	
294	INPUT	100V	
295	OUTPUT	100V	
296	INPUT	100V	
297	OUTPUT	100V	
298	INPUT	100V	
299	OUTPUT	100V	
300	INPUT	100V	
301	OUTPUT	100V	
302	INPUT	100V	
303	OUTPUT	100V	
304	INPUT	100V	
305	OUTPUT	100V	
306	INPUT	100V	
307	OUTPUT	100V	
308	INPUT	100V	
309	OUTPUT	100V	
310	INPUT	100V	
311	OUTPUT	100V	
312	INPUT	100V	
313	OUTPUT	100V	
314	INPUT	100V	
315	OUTPUT	100V	
316	INPUT	100V	
317	OUTPUT	100V	
318	INPUT	100V	
319	OUTPUT	100V	
320	INPUT	100V	
321	OUTPUT	100V	
322	INPUT	100V	
323	OUTPUT	100V	
324	INPUT	100V	
325	OUTPUT	100V	
326	INPUT	100V	
327	OUTPUT	100V	
328	INPUT	100V	
329	OUTPUT	100V	
330	INPUT	100V	
331	OUTPUT	100V	
332	INPUT	100V	
333	OUTPUT	100V	
334	INPUT	100V	
335	OUTPUT	100V	
336	INPUT	100V	
337	OUTPUT	100V	
338	INPUT	100V	
339	OUTPUT	100V	
340	INPUT	100V	
341	OUTPUT	100V	
342	INPUT	100V	
343	OUTPUT	100V	
344	INPUT	100V	
345	OUTPUT	100V	
346	INPUT	100V	
347	OUTPUT	100V	
348	INPUT	100V	
349	OUTPUT	100V	
350	INPUT	100V	
351	OUTPUT	100V	
352	INPUT	100V	
353	OUTPUT	100V	
354	INPUT	100V	
355	OUTPUT	100V	
356	INPUT	100V	
357	OUTPUT	100V	
358	INPUT	100V	
359	OUTPUT	100V	
360	INPUT	100V	
361	OUTPUT	100V	
362	INPUT	100V	
363	OUTPUT	100V	
364	INPUT	100V	
365	OUTPUT	100V	
366	INPUT	100V	
367	OUTPUT	100V	
368	INPUT	100V	
369	OUTPUT	100V	
370	INPUT	100V	
371	OUTPUT	100V	
372	INPUT	100V	
373	OUTPUT	100V	
374	INPUT	100V	
375	OUTPUT	100V	
376	INPUT	100V	
377	OUTPUT	100V	
378	INPUT	100V	
379	OUTPUT	100V	
380	INPUT	100V	
381	OUTPUT	100V	
382	INPUT	100V	
383	OUTPUT	100V	
384	INPUT	100V	
385	OUTPUT	100V	
386	INPUT	100V	
387	OUTPUT	100V	
388	INPUT	100V	



Page 134 [134]
to DIGITAL (1) CB29

Page 131 [131]
to OPERATION (2) CB49






Page 127 [127]
to DIGITAL (1) CB71

To Digital



IC	FUNCTION	MANUFACTURER	REMARKS
1	VIDEO PROCESSOR	SONY	IC101
2	VIDEO PROCESSOR	SONY	IC102
3	VIDEO PROCESSOR	SONY	IC103
4	VIDEO PROCESSOR	SONY	IC104
5	VIDEO PROCESSOR	SONY	IC105
6	VIDEO PROCESSOR	SONY	IC106
7	VIDEO PROCESSOR	SONY	IC107
8	VIDEO PROCESSOR	SONY	IC108
9	VIDEO PROCESSOR	SONY	IC109
10	VIDEO PROCESSOR	SONY	IC110
11	VIDEO PROCESSOR	SONY	IC111
12	VIDEO PROCESSOR	SONY	IC112
13	VIDEO PROCESSOR	SONY	IC113
14	VIDEO PROCESSOR	SONY	IC114
15	VIDEO PROCESSOR	SONY	IC115
16	VIDEO PROCESSOR	SONY	IC116
17	VIDEO PROCESSOR	SONY	IC117
18	VIDEO PROCESSOR	SONY	IC118
19	VIDEO PROCESSOR	SONY	IC119
20	VIDEO PROCESSOR	SONY	IC120

IC	FUNCTION	MANUFACTURER	REMARKS
21	VIDEO PROCESSOR	SONY	IC201
22	VIDEO PROCESSOR	SONY	IC202
23	VIDEO PROCESSOR	SONY	IC203
24	VIDEO PROCESSOR	SONY	IC204
25	VIDEO PROCESSOR	SONY	IC205
26	VIDEO PROCESSOR	SONY	IC206
27	VIDEO PROCESSOR	SONY	IC207
28	VIDEO PROCESSOR	SONY	IC208
29	VIDEO PROCESSOR	SONY	IC209
30	VIDEO PROCESSOR	SONY	IC210
31	VIDEO PROCESSOR	SONY	IC211
32	VIDEO PROCESSOR	SONY	IC212
33	VIDEO PROCESSOR	SONY	IC213
34	VIDEO PROCESSOR	SONY	IC214
35	VIDEO PROCESSOR	SONY	IC215
36	VIDEO PROCESSOR	SONY	IC216
37	VIDEO PROCESSOR	SONY	IC217
38	VIDEO PROCESSOR	SONY	IC218
39	VIDEO PROCESSOR	SONY	IC219
40	VIDEO PROCESSOR	SONY	IC220

IC	FUNCTION	MANUFACTURER	REMARKS
41	VIDEO PROCESSOR	SONY	IC301
42	VIDEO PROCESSOR	SONY	IC302
43	VIDEO PROCESSOR	SONY	IC303
44	VIDEO PROCESSOR	SONY	IC304
45	VIDEO PROCESSOR	SONY	IC305
46	VIDEO PROCESSOR	SONY	IC306
47	VIDEO PROCESSOR	SONY	IC307
48	VIDEO PROCESSOR	SONY	IC308
49	VIDEO PROCESSOR	SONY	IC309
50	VIDEO PROCESSOR	SONY	IC310
51	VIDEO PROCESSOR	SONY	IC311
52	VIDEO PROCESSOR	SONY	IC312
53	VIDEO PROCESSOR	SONY	IC313
54	VIDEO PROCESSOR	SONY	IC314
55	VIDEO PROCESSOR	SONY	IC315
56	VIDEO PROCESSOR	SONY	IC316
57	VIDEO PROCESSOR	SONY	IC317
58	VIDEO PROCESSOR	SONY	IC318
59	VIDEO PROCESSOR	SONY	IC319
60	VIDEO PROCESSOR	SONY	IC320




* All voltages are measured with a 10MΩV DC electronic voltmeter.
* Components having special characteristics are marked Δ and must be replaced with components having the same characteristics as the original.
* Schematic diagram is subject to change without notice.



REMARKS		PARTS NAME	
1	REPAIR	1	REPAIR
2	REPAIR	2	REPAIR
3	REPAIR	3	REPAIR
4	REPAIR	4	REPAIR
5	REPAIR	5	REPAIR
6	REPAIR	6	REPAIR
7	REPAIR	7	REPAIR
8	REPAIR	8	REPAIR
9	REPAIR	9	REPAIR
10	REPAIR	10	REPAIR
11	REPAIR	11	REPAIR
12	REPAIR	12	REPAIR
13	REPAIR	13	REPAIR
14	REPAIR	14	REPAIR
15	REPAIR	15	REPAIR
16	REPAIR	16	REPAIR
17	REPAIR	17	REPAIR
18	REPAIR	18	REPAIR
19	REPAIR	19	REPAIR
20	REPAIR	20	REPAIR
21	REPAIR	21	REPAIR
22	REPAIR	22	REPAIR
23	REPAIR	23	REPAIR
24	REPAIR	24	REPAIR
25	REPAIR	25	REPAIR
26	REPAIR	26	REPAIR
27	REPAIR	27	REPAIR
28	REPAIR	28	REPAIR
29	REPAIR	29	REPAIR
30	REPAIR	30	REPAIR
31	REPAIR	31	REPAIR
32	REPAIR	32	REPAIR
33	REPAIR	33	REPAIR
34	REPAIR	34	REPAIR
35	REPAIR	35	REPAIR
36	REPAIR	36	REPAIR
37	REPAIR	37	REPAIR
38	REPAIR	38	REPAIR
39	REPAIR	39	REPAIR
40	REPAIR	40	REPAIR
41	REPAIR	41	REPAIR
42	REPAIR	42	REPAIR
43	REPAIR	43	REPAIR
44	REPAIR	44	REPAIR
45	REPAIR	45	REPAIR
46	REPAIR	46	REPAIR
47	REPAIR	47	REPAIR
48	REPAIR	48	REPAIR
49	REPAIR	49	REPAIR
50	REPAIR	50	REPAIR
51	REPAIR	51	REPAIR
52	REPAIR	52	REPAIR
53	REPAIR	53	REPAIR
54	REPAIR	54	REPAIR
55	REPAIR	55	REPAIR
56	REPAIR	56	REPAIR
57	REPAIR	57	REPAIR
58	REPAIR	58	REPAIR
59	REPAIR	59	REPAIR
60	REPAIR	60	REPAIR
61	REPAIR	61	REPAIR
62	REPAIR	62	REPAIR
63	REPAIR	63	REPAIR
64	REPAIR	64	REPAIR
65	REPAIR	65	REPAIR
66	REPAIR	66	REPAIR
67	REPAIR	67	REPAIR
68	REPAIR	68	REPAIR
69	REPAIR	69	REPAIR
70	REPAIR	70	REPAIR
71	REPAIR	71	REPAIR
72	REPAIR	72	REPAIR
73	REPAIR	73	REPAIR
74	REPAIR	74	REPAIR
75	REPAIR	75	REPAIR
76	REPAIR	76	REPAIR
77	REPAIR	77	REPAIR
78	REPAIR	78	REPAIR
79	REPAIR	79	REPAIR
80	REPAIR	80	REPAIR
81	REPAIR	81	REPAIR
82	REPAIR	82	REPAIR
83	REPAIR	83	REPAIR
84	REPAIR	84	REPAIR
85	REPAIR	85	REPAIR
86	REPAIR	86	REPAIR
87	REPAIR	87	REPAIR
88	REPAIR	88	REPAIR
89	REPAIR	89	REPAIR
90	REPAIR	90	REPAIR
91	REPAIR	91	REPAIR
92	REPAIR	92	REPAIR
93	REPAIR	93	REPAIR
94	REPAIR	94	REPAIR
95	REPAIR	95	REPAIR
96	REPAIR	96	REPAIR
97	REPAIR	97	REPAIR
98	REPAIR	98	REPAIR
99	REPAIR	99	REPAIR
100	REPAIR	100	REPAIR

Description of Item (Part 1) of 145									
1	2	3	4	5	6	7	8	9	10
4341	4341.1	4341.10	4341.10	X	X		4341.10	X	4341.10
4342	4342.1	4342.10	4342.10	X	X		4342.10	X	4342.10
4343	4343.1	4343.10	4343.10	X	X		4343.10	X	4343.10
4344	4344.1	4344.10	4344.10	X	X		4344.10	X	4344.10
4345	4345.1	4345.10	4345.10	X	X		4345.10	X	4345.10
4346	4346.1	4346.10	4346.10	X	X		4346.10	X	4346.10
4347	4347.1	4347.10	4347.10	X	X		4347.10	X	4347.10
4348	4348.1	4348.10	4348.10	X	X		4348.10	X	4348.10
4349	4349.1	4349.10	4349.10	X	X		4349.10	X	4349.10
4350	4350.1	4350.10	4350.10	X	X		4350.10	X	4350.10
4351	4351.1	4351.10	4351.10	X	X		4351.10	X	4351.10
4352	4352.1	4352.10	4352.10	X	X		4352.10	X	4352.10
4353	4353.1	4353.10	4353.10	X	X		4353.10	X	4353.10
4354	4354.1	4354.10	4354.10	X	X		4354.10	X	4354.10
4355	4355.1	4355.10	4355.10	X	X		4355.10	X	4355.10
4356	4356.1	4356.10	4356.10	X	X		4356.10	X	4356.10
4357	4357.1	4357.10	4357.10	X	X		4357.10	X	4357.10
4358	4358.1	4358.10	4358.10	X	X		4358.10	X	4358.10
4359	4359.1	4359.10	4359.10	X	X		4359.10	X	4359.10
4360	4360.1	4360.10	4360.10	X	X		4360.10	X	4360.10

- ★ All voltages are measured with a 10M Ω /V DC electronic voltmeter.
- ★ Components having special characteristics are marked Δ , and must be replaced with parts having specifications equal to those originally installed.
- ★ Schematic diagram is subject to change without notice.



IC501, 502 SN74V16BWPWR
4-bit synchronous binary counters

IC503 SN74V16BWPWR
Dual positive edge triggered D-type flip flop

IC504 PCM1781DBQR
Auto signal-to-analog converter

IC505 A0910B25K4C
Microprocessor

IC506 AK5581AVQ
17-bit/16-bit digital-to-analog converter

IC507 5M4-K4556032-LCT5000
256 M synchronous DRAM

IC508 74VLC1G360W
Single 2 input AND gate

IC509-512 74VLC245APW, 118
Octal bus transceiver with direction pin
with 3.1 current sink/source (0-50mA)

IC513 K8P6416UB3P14B000
64-Mb page mode NOR flash

IC514 TC7VH14FK
Tri-state inverter

IC515 516 74VLC02APW
Quad 2 input OR gate

IC516 517 74VLC02APW
Quad 2 input AND gate

IC518 519 74VLC02APW
Quad 2 input OR gate

IC519 520 74VLC02APW
Quad 2 input AND gate

IC521 522 TC7VH14FK
Tri-state inverter

IC523 524 74VLC02APW
Quad 2 input OR gate

IC525 526 74VLC02APW
Quad 2 input AND gate

IC527 528 74VLC02APW
Quad 2 input OR gate

IC529 530 74VLC02APW
Quad 2 input AND gate

IC531 532 TC7VH14FK
Tri-state inverter

IC533 534 74VLC02APW
Quad 2 input OR gate

IC535 536 74VLC02APW
Quad 2 input AND gate

IC537 538 74VLC02APW
Quad 2 input OR gate

IC539 540 74VLC02APW
Quad 2 input AND gate

IC541 542 TC7VH14FK
Tri-state inverter

IC543 544 74VLC02APW
Quad 2 input OR gate

IC545 546 74VLC02APW
Quad 2 input AND gate

IC547 548 74VLC02APW
Quad 2 input OR gate

IC549 550 74VLC02APW
Quad 2 input AND gate

IC551 552 TC7VH14FK
Tri-state inverter

IC553 554 74VLC02APW
Quad 2 input OR gate

IC555 556 74VLC02APW
Quad 2 input AND gate

IC557 558 74VLC02APW
Quad 2 input OR gate

IC559 560 74VLC02APW
Quad 2 input AND gate

IC561 562 TC7VH14FK
Tri-state inverter

IC563 564 74VLC02APW
Quad 2 input OR gate

IC565 566 74VLC02APW
Quad 2 input AND gate

IC567 568 74VLC02APW
Quad 2 input OR gate

IC569 570 74VLC02APW
Quad 2 input AND gate

IC571 572 TC7VH14FK
Tri-state inverter

IC573 574 74VLC02APW
Quad 2 input OR gate

IC575 576 74VLC02APW
Quad 2 input AND gate

IC577 578 74VLC02APW
Quad 2 input OR gate

IC579 580 74VLC02APW
Quad 2 input AND gate

IC581 582 TC7VH14FK
Tri-state inverter

IC583 584 74VLC02APW
Quad 2 input OR gate

IC585 586 74VLC02APW
Quad 2 input AND gate

IC587 588 74VLC02APW
Quad 2 input OR gate

IC589 590 74VLC02APW
Quad 2 input AND gate

IC591 592 TC7VH14FK
Tri-state inverter

IC593 594 74VLC02APW
Quad 2 input OR gate

IC595 596 74VLC02APW
Quad 2 input AND gate

IC597 598 74VLC02APW
Quad 2 input OR gate

IC599 600 74VLC02APW
Quad 2 input AND gate

IC601 602 TC7VH14FK
Tri-state inverter

IC603 604 74VLC02APW
Quad 2 input OR gate

IC605 606 74VLC02APW
Quad 2 input AND gate

IC607 608 74VLC02APW
Quad 2 input OR gate

IC609 610 74VLC02APW
Quad 2 input AND gate

IC611 612 TC7VH14FK
Tri-state inverter

IC613 614 74VLC02APW
Quad 2 input OR gate

IC615 616 74VLC02APW
Quad 2 input AND gate

IC617 618 74VLC02APW
Quad 2 input OR gate

IC619 620 74VLC02APW
Quad 2 input AND gate

IC621 622 TC7VH14FK
Tri-state inverter

IC623 624 74VLC02APW
Quad 2 input OR gate

IC625 626 74VLC02APW
Quad 2 input AND gate

IC627 628 74VLC02APW
Quad 2 input OR gate

IC629 630 74VLC02APW
Quad 2 input AND gate

IC631 632 TC7VH14FK
Tri-state inverter

IC633 634 74VLC02APW
Quad 2 input OR gate

IC635 636 74VLC02APW
Quad 2 input AND gate

IC637 638 74VLC02APW
Quad 2 input OR gate

IC639 640 74VLC02APW
Quad 2 input AND gate

IC641 642 TC7VH14FK
Tri-state inverter

IC643 644 74VLC02APW
Quad 2 input OR gate

IC645 646 74VLC02APW
Quad 2 input AND gate

IC647 648 74VLC02APW
Quad 2 input OR gate

IC649 650 74VLC02APW
Quad 2 input AND gate

IC651 652 TC7VH14FK
Tri-state inverter

IC653 654 74VLC02APW
Quad 2 input OR gate

IC655 656 74VLC02APW
Quad 2 input AND gate

IC657 658 74VLC02APW
Quad 2 input OR gate

IC659 660 74VLC02APW
Quad 2 input AND gate

IC661 662 TC7VH14FK
Tri-state inverter

IC663 664 74VLC02APW
Quad 2 input OR gate

IC665 666 74VLC02APW
Quad 2 input AND gate

IC667 668 74VLC02APW
Quad 2 input OR gate

IC669 670 74VLC02APW
Quad 2 input AND gate

IC671 672 TC7VH14FK
Tri-state inverter

IC673 674 74VLC02APW
Quad 2 input OR gate

IC675 676 74VLC02APW
Quad 2 input AND gate

IC677 678 74VLC02APW
Quad 2 input OR gate

IC679 680 74VLC02APW
Quad 2 input AND gate

IC681 682 TC7VH14FK
Tri-state inverter

IC683 684 74VLC02APW
Quad 2 input OR gate

IC685 686 74VLC02APW
Quad 2 input AND gate

IC687 688 74VLC02APW
Quad 2 input OR gate

IC689 690 74VLC02APW
Quad 2 input AND gate

IC691 692 TC7VH14FK
Tri-state inverter

IC693 694 74VLC02APW
Quad 2 input OR gate

IC695 696 74VLC02APW
Quad 2 input AND gate

IC697 698 74VLC02APW
Quad 2 input OR gate

IC699 700 74VLC02APW
Quad 2 input AND gate

IC701 702 TC7VH14FK
Tri-state inverter

IC703 704 74VLC02APW
Quad 2 input OR gate

IC705 706 74VLC02APW
Quad 2 input AND gate

IC707 708 74VLC02APW
Quad 2 input OR gate

IC709 710 74VLC02APW
Quad 2 input AND gate

IC711 712 TC7VH14FK
Tri-state inverter

IC713 714 74VLC02APW
Quad 2 input OR gate

IC715 716 74VLC02APW
Quad 2 input AND gate

IC717 718 74VLC02APW
Quad 2 input OR gate

IC719 720 74VLC02APW
Quad 2 input AND gate

IC721 722 TC7VH14FK
Tri-state inverter

IC723 724 74VLC02APW
Quad 2 input OR gate

IC725 726 74VLC02APW
Quad 2 input AND gate

IC727 728 74VLC02APW
Quad 2 input OR gate

IC729 730 74VLC02APW
Quad 2 input AND gate

IC731 732 TC7VH14FK
Tri-state inverter

IC733 734 74VLC02APW
Quad 2 input OR gate

IC735 736 74VLC02APW
Quad 2 input AND gate

IC737 738 74VLC02APW
Quad 2 input OR gate

IC739 740 74VLC02APW
Quad 2 input AND gate

IC741 742 TC7VH14FK
Tri-state inverter

IC743 744 74VLC02APW
Quad 2 input OR gate

IC745 746 74VLC02APW
Quad 2 input AND gate

IC747 748 74VLC02APW
Quad 2 input OR gate

IC749 750 74VLC02APW
Quad 2 input AND gate

IC751 752 TC7VH14FK
Tri-state inverter

IC753 754 74VLC02APW
Quad 2 input OR gate

IC755 756 74VLC02APW
Quad 2 input AND gate

IC757 758 74VLC02APW
Quad 2 input OR gate

IC759 760 74VLC02APW
Quad 2 input AND gate

IC761 762 TC7VH14FK
Tri-state inverter

IC763 764 74VLC02APW
Quad 2 input OR gate

IC765 766 74VLC02APW
Quad 2 input AND gate

IC767 768 74VLC02APW
Quad 2 input OR gate

IC769 770 74VLC02APW
Quad 2 input AND gate

IC771 772 TC7VH14FK
Tri-state inverter

IC773 774 74VLC02APW
Quad 2 input OR gate

IC775 776 74VLC02APW
Quad 2 input AND gate

IC777 778 74VLC02APW
Quad 2 input OR gate

IC779 780 74VLC02APW
Quad 2 input AND gate

IC781 782 TC7VH14FK
Tri-state inverter

IC783 784 74VLC02APW
Quad 2 input OR gate

IC785 786 74VLC02APW
Quad 2 input AND gate

IC787 788 74VLC02APW
Quad 2 input OR gate

IC789 790 74VLC02APW
Quad 2 input AND gate

IC791 792 TC7VH14FK
Tri-state inverter

IC793 794 74VLC02APW
Quad 2 input OR gate

IC795 796 74VLC02APW
Quad 2 input AND gate

IC797 798 74VLC02APW
Quad 2 input OR gate

IC799 800 74VLC02APW
Quad 2 input AND gate

IC801 802 TC7VH14FK
Tri-state inverter

IC803 804 74VLC02APW
Quad 2 input OR gate

IC805 806 74VLC02APW
Quad 2 input AND gate

IC807 808 74VLC02APW
Quad 2 input OR gate

IC809 810 74VLC02APW
Quad 2 input AND gate

IC811 812 TC7VH14FK
Tri-state inverter

IC813 814 74VLC02APW
Quad 2 input OR gate

IC815 816 74VLC02APW
Quad 2 input AND gate

IC817 818 74VLC02APW
Quad 2 input OR gate

IC819 820 74VLC02APW
Quad 2 input AND gate

IC821 822 TC7VH14FK
Tri-state inverter

IC823 824 74VLC02APW
Quad 2 input OR gate

IC825 826 74VLC02APW
Quad 2 input AND gate

IC827 828 74VLC02APW
Quad 2 input OR gate

IC829 830 74VLC02APW
Quad 2 input AND gate

IC831 832 TC7VH14FK
Tri-state inverter

IC833 834 74VLC02APW
Quad 2 input OR gate

IC835 836 74VLC02APW
Quad 2 input AND gate

IC837 838 74VLC02APW
Quad 2 input OR gate

IC839 840 74VLC02APW
Quad 2 input AND gate

IC841 842 TC7VH14FK
Tri-state inverter

IC843 844 74VLC02APW
Quad 2 input OR gate

IC845 846 74VLC02APW
Quad 2 input AND gate

IC847 848 74VLC02APW
Quad 2 input OR gate

IC849 850 74VLC02APW
Quad 2 input AND gate

IC851 852 TC7VH14FK
Tri-state inverter

IC853 854 74VLC02APW
Quad 2 input OR gate

IC855 856 74VLC02APW
Quad 2 input AND gate

IC857 858 74VLC02APW
Quad 2 input OR gate

IC859 860 74VLC02APW
Quad 2 input AND gate

IC861 862 TC7VH14FK
Tri-state inverter

IC863 864 74VLC02APW
Quad 2 input OR gate

IC865 866 74VLC02APW
Quad 2 input AND gate

IC867 868 74VLC02APW
Quad 2 input OR gate

IC869 870 74VLC02APW
Quad 2 input AND gate

IC871 872 TC7VH14FK
Tri-state inverter

IC873 874 74VLC02APW
Quad 2 input OR gate

IC875 876 74VLC02APW
Quad 2 input AND gate

IC877 878 74VLC02APW
Quad 2 input OR gate

IC879 880 74VLC02APW
Quad 2 input AND gate

IC881 882 TC7VH14FK
Tri-state inverter

IC883 884 74VLC02APW
Quad 2 input OR gate

IC885 886 74VLC02APW
Quad 2 input AND gate

IC887 888 74VLC02APW
Quad 2 input OR gate

IC889 890 74VLC02APW
Quad 2 input AND gate

IC891 892 TC7VH14FK
Tri-state inverter

IC893 894 74VLC02APW
Quad 2 input OR gate

IC895 896 74VLC02APW
Quad 2 input AND gate

IC897 898 74VLC02APW
Quad 2 input OR gate

IC899 900 74VLC02APW
Quad 2 input AND gate

IC901 902 TC7VH14FK
Tri-state inverter

IC903 904 74VLC02APW
Quad 2 input OR gate

IC905 906 74VLC02APW
Quad 2 input AND gate

IC907 908 74VLC02APW
Quad 2 input OR gate

IC909 910 74VLC02APW
Quad 2 input AND gate

IC911 912 TC7VH14FK
Tri-state inverter

IC913 914 74VLC02APW
Quad 2 input OR gate


IC915 916 74VLC02APW
Quad 2 input AND gate

IC917 918 74VLC02APW
Quad 2 input OR gate

IC919 920 74VLC02APW
Quad 2 input AND gate

IC921 922 TC7VH14FK
Tri-state inverter

IC923




USB: ETHER
08/7C/AL/PN-999
OTHER

GUI 1/2


Page 130

to OPERATION (5) V4407

POINT ① V4.550 (Pin 11 of IC551)




POINT ② V4.550 (Pin 5 of IC553)




RESISTOR		CAPACITOR	
REFERENCE	PART NAME	REFERENCE	PART NAME
1	10K OHM RESISTOR	1	100N F CAPACITOR
2	10K OHM RESISTOR	2	100N F CAPACITOR
3	10K OHM RESISTOR	3	100N F CAPACITOR
4	10K OHM RESISTOR	4	100N F CAPACITOR
5	10K OHM RESISTOR	5	100N F CAPACITOR
6	10K OHM RESISTOR	6	100N F CAPACITOR
7	10K OHM RESISTOR	7	100N F CAPACITOR
8	10K OHM RESISTOR	8	100N F CAPACITOR
9	10K OHM RESISTOR	9	100N F CAPACITOR
10	10K OHM RESISTOR	10	100N F CAPACITOR
11	10K OHM RESISTOR	11	100N F CAPACITOR
12	10K OHM RESISTOR	12	100N F CAPACITOR
13	10K OHM RESISTOR	13	100N F CAPACITOR
14	10K OHM RESISTOR	14	100N F CAPACITOR
15	10K OHM RESISTOR	15	100N F CAPACITOR
16	10K OHM RESISTOR	16	100N F CAPACITOR
17	10K OHM RESISTOR	17	100N F CAPACITOR
18	10K OHM RESISTOR	18	100N F CAPACITOR
19	10K OHM RESISTOR	19	100N F CAPACITOR
20	10K OHM RESISTOR	20	100N F CAPACITOR
21	10K OHM RESISTOR	21	100N F CAPACITOR
22	10K OHM RESISTOR	22	100N F CAPACITOR
23	10K OHM RESISTOR	23	100N F CAPACITOR
24	10K OHM RESISTOR	24	100N F CAPACITOR
25	10K OHM RESISTOR	25	100N F CAPACITOR
26	10K OHM RESISTOR	26	100N F CAPACITOR
27	10K OHM RESISTOR	27	100N F CAPACITOR
28	10K OHM RESISTOR	28	100N F CAPACITOR
29	10K OHM RESISTOR	29	100N F CAPACITOR
30	10K OHM RESISTOR	30	100N F CAPACITOR
31	10K OHM RESISTOR	31	100N F CAPACITOR
32	10K OHM RESISTOR	32	100N F CAPACITOR
33	10K OHM RESISTOR	33	100N F CAPACITOR
34	10K OHM RESISTOR	34	100N F CAPACITOR
35	10K OHM RESISTOR	35	100N F CAPACITOR
36	10K OHM RESISTOR	36	100N F CAPACITOR
37	10K OHM RESISTOR	37	100N F CAPACITOR
38	10K OHM RESISTOR	38	100N F CAPACITOR
39	10K OHM RESISTOR	39	100N F CAPACITOR
40	10K OHM RESISTOR	40	100N F CAPACITOR
41	10K OHM RESISTOR	41	100N F CAPACITOR
42	10K OHM RESISTOR	42	100N F CAPACITOR
43	10K OHM RESISTOR	43	100N F CAPACITOR
44	10K OHM RESISTOR	44	100N F CAPACITOR
45	10K OHM RESISTOR	45	100N F CAPACITOR
46	10K OHM RESISTOR	46	100N F CAPACITOR
47	10K OHM RESISTOR	47	100N F CAPACITOR
48	10K OHM RESISTOR	48	100N F CAPACITOR
49	10K OHM RESISTOR	49	100N F CAPACITOR
50	10K OHM RESISTOR	50	100N F CAPACITOR
51	10K OHM RESISTOR	51	100N F CAPACITOR
52	10K OHM RESISTOR	52	100N F CAPACITOR
53	10K OHM RESISTOR	53	100N F CAPACITOR
54	10K OHM RESISTOR	54	100N F CAPACITOR
55	10K OHM RESISTOR	55	100N F CAPACITOR
56	10K OHM RESISTOR	56	100N F CAPACITOR
57	10K OHM RESISTOR	57	100N F CAPACITOR
58	10K OHM RESISTOR	58	100N F CAPACITOR
59	10K OHM RESISTOR	59	100N F CAPACITOR
60	10K OHM RESISTOR	60	100N F CAPACITOR
61	10K OHM RESISTOR	61	100N F CAPACITOR
62	10K OHM RESISTOR	62	100N F CAPACITOR
63	10K OHM RESISTOR	63	100N F CAPACITOR
64	10K OHM RESISTOR	64	100N F CAPACITOR
65	10K OHM RESISTOR	65	100N F CAPACITOR
66	10K OHM RESISTOR	66	100N F CAPACITOR
67	10K OHM RESISTOR	67	100N F CAPACITOR
68	10K OHM RESISTOR	68	100N F CAPACITOR
69	10K OHM RESISTOR	69	100N F CAPACITOR
70	10K OHM RESISTOR	70	100N F CAPACITOR
71	10K OHM RESISTOR	71	100N F CAPACITOR
72	10K OHM RESISTOR	72	100N F CAPACITOR
73	10K OHM RESISTOR	73	100N F CAPACITOR
74	10K OHM RESISTOR	74	100N F CAPACITOR
75	10K OHM RESISTOR	75	100N F CAPACITOR
76	10K OHM RESISTOR	76	100N F CAPACITOR
77	10K OHM RESISTOR	77	100N F CAPACITOR
78	10K OHM RESISTOR	78	100N F CAPACITOR
79	10K OHM RESISTOR	79	100N F CAPACITOR
80	10K OHM RESISTOR	80	100N F CAPACITOR
81	10K OHM RESISTOR	81	100N F CAPACITOR
82	10K OHM RESISTOR	82	100N F CAPACITOR
83	10K OHM RESISTOR	83	100N F CAPACITOR
84	10K OHM RESISTOR	84	100N F CAPACITOR
85	10K OHM RESISTOR	85	100N F CAPACITOR
86	10K OHM RESISTOR	86	100N F CAPACITOR
87	10K OHM RESISTOR	87	100N F CAPACITOR
88	10K OHM RESISTOR	88	100N F CAPACITOR
89	10K OHM RESISTOR	89	100N F CAPACITOR
90	10K OHM RESISTOR	90	100N F CAPACITOR
91	10K OHM RESISTOR	91	100N F CAPACITOR
92	10K OHM RESISTOR	92	100N F CAPACITOR
93	10K OHM RESISTOR	93	100N F CAPACITOR
94	10K OHM RESISTOR	94	100N F CAPACITOR
95	10K OHM RESISTOR	95	100N F CAPACITOR
96	10K OHM RESISTOR	96	100N F CAPACITOR
97	10K OHM RESISTOR	97	100N F CAPACITOR
98	10K OHM RESISTOR	98	100N F CAPACITOR
99	10K OHM RESISTOR	99	100N F CAPACITOR
100	10K OHM RESISTOR	100	100N F CAPACITOR

NOTICE (Note 1)
(1) : U.S.A.
(2) : JAPAN
(3) : EUROPE
(4) : CHINA
(5) : INDIA
(6) : SOUTH AMERICA
(7) : AFRICA
(8) : MIDDLE EAST
(9) : AUSTRALIA
(10) : NEW ZEALAND
(11) : SINGAPORE
(12) : MALAYSIA
(13) : THAILAND
(14) : PHILIPPINES
(15) : VIETNAM
(16) : LAOS
(17) : CAMBODIA
(18) : MYANMAR
(19) : BURMA
(20) : NEPAL
(21) : BANGLADESH
(22) : PAKISTAN
(23) : AFGHANISTAN
(24) : UZBEKISTAN
(25) : KAZAKHSTAN
(26) : KYRGYZSTAN
(27) : TAJIKISTAN
(28) : TURKMENISTAN
(29) : ARMENIA
(30) : GEORGIA
(31) : ARMENIA
(32) : GEORGIA
(33) : ARMENIA
(34) : GEORGIA
(35) : ARMENIA
(36) : GEORGIA
(37) : ARMENIA
(38) : GEORGIA
(39) : ARMENIA
(40) : GEORGIA
(41) : ARMENIA
(42) : GEORGIA
(43) : ARMENIA
(44) : GEORGIA
(45) : ARMENIA
(46) : GEORGIA
(47) : ARMENIA
(48) : GEORGIA
(49) : ARMENIA
(50) : GEORGIA
(51) : ARMENIA
(52) : GEORGIA
(53) : ARMENIA
(54) : GEORGIA
(55) : ARMENIA
(56) : GEORGIA
(57) : ARMENIA
(58) : GEORGIA
(59) : ARMENIA
(60) : GEORGIA
(61) : ARMENIA
(62) : GEORGIA
(63) : ARMENIA
(64) : GEORGIA
(65) : ARMENIA
(66) : GEORGIA
(67) : ARMENIA
(68) : GEORGIA
(69) : ARMENIA
(70) : GEORGIA
(71) : ARMENIA
(72) : GEORGIA
(73) : ARMENIA
(74) : GEORGIA
(75) : ARMENIA
(76) : GEORGIA
(77) : ARMENIA
(78) : GEORGIA
(79) : ARMENIA
(80) : GEORGIA
(81) : ARMENIA
(82) : GEORGIA
(83) : ARMENIA
(84) : GEORGIA
(85) : ARMENIA
(86) : GEORGIA
(87) : ARMENIA
(88) : GEORGIA
(89) : ARMENIA
(90) : GEORGIA
(91) : ARMENIA
(92) : GEORGIA
(93) : ARMENIA
(94) : GEORGIA
(95) : ARMENIA
(96) : GEORGIA
(97) : ARMENIA
(98) : GEORGIA
(99) : ARMENIA
(100) : GEORGIA


IC551: ISP1760BE
Enhanced In-Signal USB Host Controller



IC552: RS523N01A/TR-F
High side switch IC



IC553: LAN8217-MT
Digital IC



* All voltages are measured with a 100MΩ VDC electronic voltmeter.
* Components having special characteristics are marked Δ, and must be replaced with parts having special characteristics equal to or better than the original installed.
* Schematic diagrams are subject to change without notice.

■ REPLACEMENT PARTS LIST

• ELECTRICAL COMPONENT PARTS

WARNING

- Components having special characteristics are marked Δ and must be replaced with parts having specifications equal to those originally installed.

ABBREVIATIONS IN THIS LIST ARE AS FOLLOWS:

C.A.EL.CHP	: CHIP ALUMI.ELECTROLYTIC CAP	L.EMIT	: LIGHT EMITTING MODULE
C.CE	: CERAMIC CAP	LED.DSPLY	: LED DISPLAY
C.CE.ARRAY	: CERAMIC CAP ARRAY	LED.INFRD	: LED,INFRARED
C.CE.CHP	: CHIP CERAMIC CAP	MODUL.RF	: MODULATOR,RF
C.CE.ML	: MULTILAYER CERAMIC CAP	PHOT.CPL	: PHOTO COUPLER
C.CE.M.CHP	: CHIP MULTILAYER CERAMIC CAP	PHOT.INTR	: PHOTO INTERRUPTER
C.CE.SAFTY	: RECOGNIZED CERAMIC CAP	PHOT.RFLCT	: PHOTO REFLECTOR
C.CE.TUBLR	: CERAMIC TUBULAR CAP	PIN.TEST	: PIN,TEST POINT
C.CE.SMI	: SEMI CONDUCTIVE CERAMIC CAP	PLST.RIVET	: PLASTIC RIVET
C.EL	: ELECTROLYTIC CAP	R.ARRAY	: RESISTOR ARRAY
C.MICA	: MICA CAP	R.CAR.	: CARBON RESISTOR
C.ML.FLM	: MULTILAYER FILM CAP	R.CAR.CHP	: CHIP RESISTOR
C.MP	: METALLIZED PAPER CAP	R.CAR.FP	: FLAME PROOF CARBON RESISTOR
C.MYLAR	: MYLAR FILM CAP	R.FUS	: FUSABLE RESISTOR
C.MYLAR.ML	: MULTILAYER MYLAR FILM CAP	R.MTL.CHP	: CHIP METAL FILM RESISTOR
C.PAPER	: PAPER CAPACITOR	R.MTL.FLM	: METAL FILM RESISTOR
C.PLS	: POLYSTYRENE FILM CAP	R.MTL.OXD	: METAL OXIDE FILM RESISTOR
C.POL	: POLYESTER FILM CAP	R.MTL.PLAT	: METAL PLATE RESISTOR
C.POLY	: POLYETHYLENE FILM CAP	RSNR.CE	: CERAMIC RESONATOR
C.PP	: POLYPROPYLENE FILM CAP	RSNR.CRYS	: CRYSTAL RESONATOR
C.TNTL	: TANTALUM CAP	R.TW.CEM	: TWIN CEMENT FIXED RESISTOR
C.TNTL.CHP	: CHIP TANTALUM CAP	R.CEMENT	: CEMENT RESISTOR
C.TRIM	: TRIMMER CAP	SCR.BND.HD	: BIND HEAD B-TIGHT SCREW
CN	: CONNECTOR	SCR.BW.HD	: BW HEAD TAPPING SCREW
CN.BS.PIN	: CONNECTOR,BASE PIN	SCR.CUP	: CUP TIGHT SCREW
CN.CANNON	: CONNECTOR,CANNON	SCR.TERM	: SCREW TERMINAL
CN.DIN	: CONNECTOR,DIN	SCR.TR	: SCREW,TRANSISTOR
CN.FLAT	: CONNECTOR,FLAT CABLE	SUPRT.PCB	: SUPPORT,P.C.B.
CN.POST	: CONNECTOR,BASE POST	SURG.PRTCT	: SURGE PROTECTOR
COIL.MX.AM	: COIL,AM MIX	SW.TACT	: TACT SWITCH
COIL.AT.FM	: COIL,FM ANTENNA	SW.LEAF	: LEAF SWITCH
COIL.DT.FM	: COIL,FM DETECT	SW.LEVER	: LEVER SWITCH
COIL.MX.FM	: COIL,FM MIX	SW.MICRO	: MICRO SWITCH
COIL.OUTPT	: OUTPUT COIL	SW.PUSH	: PUSH SWITCH
DIOD.ARRAY	: DIODE ARRAY	SW.RT.ENC	: ROTARY ENCODER
DIODE.BRG	: DIODE BRIDGE	SW.RT.MTR	: ROTARY SWITCH WITH MOTOR
DIODE.CHP	: CHIP DIODE	SW.RT	: ROTARY SWITCH
DIODE.VAR	: VARACTOR DIODE	SW.SLIDE	: SLIDE SWITCH
DIOD.Z.CHP	: CHIP ZENER DIODE	TERM.SP	: SPEAKER TERMINAL
DIODE.ZENR	: ZENER DIODE	TERM.WRAP	: WRAPPING TERMINAL
DSCR.CE	: CERAMIC DISCRIMINATOR	THRMST.CHP	: CHIP THERMISTOR
FER.BEAD	: FERRITE BEADS	TR.CHP	: CHIP TRANSISTOR
FER.CORE	: FERRITE CORE	TR.DGT	: DIGITAL TRANSISTOR
FET.CHP	: CHIP FET	TR.DGT.CHP	: CHIP DIGITAL TRANSISTOR
FL.DSPLY	: FLUORESCENT DISPLAY	TRANS	: TRANSFORMER
FLTR.CE	: CERAMIC FILTER	TRANS.PULS	: PULSE TRANSFORMER
FLTR.COMB	: COMB FILTER MODULE	TRANS.PWR	: POWER TRANSFORMER ASS'Y
FLTR.LC.RF	: LC FILTER,EMI	TUNER.AM	: TUNER PACK,AM
GND.MTL	: GROUND PLATE	TUNER.FM	: TUNER PACK,FM
GND.TERM	: GROUND TERMINAL	TUNER.PK	: FRONT-ENDTUNER PACK
HOLDER.FUS	: FUSE HOLDER	VR	: ROTARY POTENTIOMETER
IC.PRTCT	: IC PROTECTOR	VR.MTR	: POTENTIOMETER WITH MOTOR
JUMPER.CN	: JUMPER CONNECTOR	VR.SW	: POTENTIOMETER WITH ROTARY SW
JUMPER.TST	: JUMPER,TEST POINT	VR.SLIDE	: SLIDE POTENTIOMETER
L.DTCT	: LIGHT DETECTING MODULE	VR.TRIM	: TRIMMER POTENTIOMETER

P.C.B. DIGITAL

Ref No.	Part No.	Description	Markets
*	WS305800	P. C. B.	DIGITAL
*	WS305900	P. C. B.	DIGITAL
*	WS306700	P. C. B.	DIGITAL
*	WS306000	P. C. B.	DIGITAL
CB1	WD295600	CN. BS. PIN	20P SE
CB3-6	WH641400	CN. HDMI	19P SE
CB7	LB919040	CN. BS. PIN	4P
CB9	WH641400	CN. HDMI	19P SE
CB15	WH641400	CN. HDMI	19P SE
CB20	VP082900	CN. BS. PIN	25P
CB21	VB389800	CN. BS. PIN	2P
CB22	VK024700	CN. BS. PIN	3P
CB23	VK025600	CN. BS. PIN	12P
CB24	VK026500	CN. BS. PIN	6P
CB25	VQ045200	CN. BS. PIN	22P
CB27	VQ047200	CN. BS. PIN	9P
CB28	VM859700	CN. BS. PIN	16P
CB29	VK026300	CN. BS. PIN	4P
CB31	LB918020	CN. BS. PIN	2P
CB31	LB918020	CN. BS. PIN	2P
CB40	WJ458700	CN. XM	4P, CAM-D96
CB61-63	V9356900	CN. JE	19P SE
CB71	VF982200	CN. BS. PIN	14P
CB73	VQ044100	CN. BS. PIN	5P
CB80	VK026400	CN. BS. PIN	5P
CB81	VK027000	CN. BS. PIN	11P
CB84	V3768800	SOCKET	17LE-23090-28
CB95	WH641400	CN. HDMI	19P SE
CB96	WC197000	CN. FMN	20P TE
C1	US135100	C. CE. CHP	0. 1uF 16V
C2	UF438100	C. EL. CHP	100uF 16V
C3	US135100	C. CE. CHP	0. 1uF 16V
C4-6	US064100	C. CE. CHP	0. 01uF 50V B
C7	WG888300	C. CE. M. CHP	10uF 6. 3V
C8-9	US135100	C. CE. CHP	0. 1uF 16V
C10-12	US064100	C. CE. CHP	0. 01uF 50V B
C13	US135100	C. CE. CHP	0. 1uF 16V
C14-16	US064100	C. CE. CHP	0. 01uF 50V B
C17-18	US135100	C. CE. CHP	0. 1uF 16V
C19-22	US064100	C. CE. CHP	0. 01uF 50V B
C23-25	US135100	C. CE. CHP	0. 1uF 16V
C26-28	WG888300	C. CE. M. CHP	10uF 6. 3V
C29-32	US135100	C. CE. CHP	0. 1uF 16V
C33-45	US064100	C. CE. CHP	0. 01uF 50V B
C46-48	US135100	C. CE. CHP	0. 1uF 16V
C50-51	US135100	C. CE. CHP	0. 1uF 16V
C53	WG888300	C. CE. M. CHP	10uF 6. 3V
C54-57	US135100	C. CE. CHP	0. 1uF 16V
C58	WG888300	C. CE. M. CHP	10uF 6. 3V
C59-60	US135100	C. CE. CHP	0. 1uF 16V
C61-62	WD758300	C. CE. CHP	10uF 10V
C63-72	US135100	C. CE. CHP	0. 1uF 16V
C73-82	US064100	C. CE. CHP	0. 01uF 50V B
C83	US135100	C. CE. CHP	0. 1uF 16V
C84	US060700	C. CE. CHP	7pF 50V B
C85	US060500	C. CE. CHP	5pF 50V B
C86	US135100	C. CE. CHP	0. 1uF 16V

* New Parts

Ref No.	Part No.	Description	Markets
C87	US062470	C. CE. CHP	470pF 50V B
C88	WD758300	C. CE. CHP	10uF 10V
C89-90	US135100	C. CE. CHP	0. 1uF 16V
C91	US063100	C. CE. CHP	1000pF 50V B
C92-93	US135100	C. CE. CHP	0. 1uF 16V
C94	US063100	C. CE. CHP	1000pF 50V B
C97-99	US063100	C. CE. CHP	1000pF 50V B
C100-102	US135100	C. CE. CHP	0. 1uF 16V
C103	WD758300	C. CE. CHP	10uF 10V
C104	US135100	C. CE. CHP	0. 1uF 16V
C105	WD758300	C. CE. CHP	10uF 10V
C106	US135100	C. CE. CHP	0. 1uF 16V
C107	WD758300	C. CE. CHP	10uF 10V
C108	US135100	C. CE. CHP	0. 1uF 16V
C109	WD758300	C. CE. CHP	10uF 10V
C110-112	US064100	C. CE. CHP	0. 01uF 50V B
C113-114	WD758300	C. CE. CHP	10uF 10V
C115	US135100	C. CE. CHP	0. 1uF 16V
C116	WD758300	C. CE. CHP	10uF 10V
C117-124	US064100	C. CE. CHP	0. 01uF 50V B
C125	WD758300	C. CE. CHP	10uF 10V
C126	US064100	C. CE. CHP	0. 01uF 50V B
C127	WD758300	C. CE. CHP	10uF 10V
C128	US064100	C. CE. CHP	0. 01uF 50V B
C129	US062470	C. CE. CHP	470pF 50V B
C130	WD758300	C. CE. CHP	10uF 10V
C131-133	US064100	C. CE. CHP	0. 01uF 50V B
C134-135	WD758300	C. CE. CHP	10uF 10V
C136	US135100	C. CE. CHP	0. 1uF 16V
C137	WD758300	C. CE. CHP	10uF 10V
C138-145	US064100	C. CE. CHP	0. 01uF 50V B
C146	WD758300	C. CE. CHP	10uF 10V
C147	US064100	C. CE. CHP	0. 01uF 50V B
C148	WD758300	C. CE. CHP	10uF 10V
C149	US064100	C. CE. CHP	0. 01uF 50V B
C150	US062470	C. CE. CHP	470pF 50V B
C151-152	US135100	C. CE. CHP	0. 1uF 16V
C153-154	WG251600	C. CE. CHP	4. 7uF 6. 3V
* C155	UF027470	C. EL. CHP	47uF 10V
C156	WJ344400	C. CE. CHP	22uF 6. 3V
C157	US062220	C. CE. CHP	220pF 50V B
C158	US135100	C. CE. CHP	0. 1uF 16V
C159	US063330	C. CE. CHP	3300pF 50V B
C160	US063120	C. CE. CHP	1200pF 50V B
C161	US135100	C. CE. CHP	0. 1uF 16V
C162	WD758300	C. CE. CHP	10uF 10V
C163	WJ344400	C. CE. CHP	22uF 6. 3V
C164	US062220	C. CE. CHP	220pF 50V B
C165	US135100	C. CE. CHP	0. 1uF 16V
C166	US063470	C. CE. CHP	4700pF 50V B
C167	US063120	C. CE. CHP	1200pF 50V B
C168	US135100	C. CE. CHP	0. 1uF 16V
C169	WD758300	C. CE. CHP	10uF 10V
C170	WH772100	C. EL.	1000uF 10V
C171	US135100	C. CE. CHP	0. 1uF 16V
C173-184	US135100	C. CE. CHP	0. 1uF 16V
C190-192	US135100	C. CE. CHP	0. 1uF 16V

* New Parts

P.C.B. DIGITAL

Ref No.	Part No.	Description	Markets
C193	US064100	C. CE. CHP 0.01uF 50V B	
C194	US135100	C. CE. CHP 0.1uF 16V	
C200	UR837330	C. EL 33uF 16V	
C202	US064100	C. CE. CHP 0.01uF 50V B	
C204-205	US064100	C. CE. CHP 0.01uF 50V B	
C207-211	US064100	C. CE. CHP 0.01uF 50V B	
C212	US135100	C. CE. CHP 0.1uF 16V	
C214	US135100	C. CE. CHP 0.1uF 16V	
C215-216	US064100	C. CE. CHP 0.01uF 50V B	
C217	US135100	C. CE. CHP 0.1uF 16V	
C218-219	US064100	C. CE. CHP 0.01uF 50V B	
C220-225	US135100	C. CE. CHP 0.1uF 16V	
C226	WG251600	C. CE. CHP 4.7uF 6.3V	
C228-229	WG251600	C. CE. CHP 4.7uF 6.3V	
C231	US135100	C. CE. CHP 0.1uF 16V	
C232-238	US064100	C. CE. CHP 1uF 25V	
C239-242	US062100	C. CE. CHP 100pF 50V B	
C243	US064100	C. CE. CHP 0.01uF 50V B	
C400-401	WD758300	C. CE. CHP 10uF 10V	U
C402	US064100	C. CE. CHP 0.01uF 50V B	
C404	US061100	C. CE. CHP 10pF 50V B	U
C405-406	US035100	C. CE. CHP 0.1uF 16V B	U
C407	US061100	C. CE. CHP 10pF 50V B	U
C408-409	US035100	C. CE. CHP 0.1uF 16V B	U
C410	WG251600	C. CE. CHP 4.7uF 6.3V	
C411	US135100	C. CE. CHP 0.1uF 16V	
C412	US035100	C. CE. CHP 0.1uF 16V B	
C413-414	US135100	C. CE. CHP 0.1uF 16V	
C415	US044220	C. CE. CHP 0.022uF 25V B	
C416	US062100	C. CE. CHP 100pF 50V B	
C417	UR267470	C. EL 47uF 50V	
C418	US062220	C. CE. CHP 220pF 50V B	
C419	WG251600	C. CE. CHP 4.7uF 6.3V	
C420	US062220	C. CE. CHP 220pF 50V B	
C421	US035100	C. CE. CHP 0.1uF 16V B	U
C422	US062220	C. CE. CHP 220pF 50V B	
C423	US035100	C. CE. CHP 0.1uF 16V B	
C424-425	US135100	C. CE. CHP 0.1uF 16V	
C426	US062220	C. CE. CHP 220pF 50V B	
C427	US035100	C. CE. CHP 0.1uF 16V B	U
C428	US064100	C. CE. CHP 0.01uF 50V B	
C429	WD758300	C. CE. CHP 10uF 10V	
C430	UR067470	C. EL 47uF 50V	
C431	US062100	C. CE. CHP 100pF 50V B	
C432-433	US062220	C. CE. CHP 220pF 50V B	
C434-436	US135100	C. CE. CHP 0.1uF 16V	
C437-438	US062100	C. CE. CHP 100pF 50V B	
C439	US061100	C. CE. CHP 10pF 50V B	
C440	US060800	C. CE. CHP 8pF 50V B	
C441-442	US062390	C. CE. CHP 390pF 50V B	
C443-444	US035100	C. CE. CHP 0.1uF 16V B	U
C445-446	UR837100	C. EL 10uF 16V	
C447-448	US135100	C. CE. CHP 0.1uF 16V	
C449-450	UR237470	C. EL 47uF 16V	
C451	US062100	C. CE. CHP 100pF 50V B	
C452	UR067100	C. EL 10uF 50V	
C453	US126100	C. CE. CHP 1uF 10V	

* New Parts

Ref No.	Part No.	Description	Markets
C454-469	US135100	C. CE. CHP 0.1uF 16V	
C471-472	US135100	C. CE. CHP 0.1uF 16V	
C473	US062680	C. CE. CHP 680pF 50V B	
C474-476	US135100	C. CE. CHP 0.1uF 16V	
C477	WG251600	C. CE. CHP 4.7uF 6.3V	
C478-484	US135100	C. CE. CHP 0.1uF 16V	
C485	WG251600	C. CE. CHP 4.7uF 6.3V	
C486	US135100	C. CE. CHP 0.1uF 16V	
C488-489	UU297220	C. EL 22uF 100V	
C491-493	US135100	C. CE. CHP 0.1uF 16V	
C494-496	US063100	C. CE. CHP 1000pF 50V B	
C497-498	US135100	C. CE. CHP 0.1uF 16V	
C499-502	US063100	C. CE. CHP 1000pF 50V B	
C503-506	US135100	C. CE. CHP 0.1uF 16V	
C520	WG251600	C. CE. CHP 4.7uF 6.3V	
C521	US135100	C. CE. CHP 0.1uF 16V	
C600	WK041800	C. EL 10uF 16V	
C601-603	US135100	C. CE. CHP 0.1uF 16V	
C604-605	US064100	C. CE. CHP 0.01uF 50V B	
C606	UR067100	C. EL 10uF 50V	
C607	US064100	C. CE. CHP 0.01uF 50V B	U
C608-609	US135100	C. CE. CHP 0.1uF 16V	
C610	US126100	C. CE. CHP 1uF 10V	
C611	US062100	C. CE. CHP 100pF 50V B	
C612	UR067100	C. EL 10uF 50V	
C613-614	US126100	C. CE. CHP 1uF 10V	
C615	UR237100	C. EL 10uF 16V	U
C616-617	US135100	C. CE. CHP 0.1uF 16V	U
C618	US063100	C. CE. CHP 1000pF 50V B	
C619	US135100	C. CE. CHP 0.1uF 16V	
C620	UR348100	C. EL 100uF 25V	
C621	UR237470	C. EL 47uF 16V	U
C622	UR067100	C. EL 10uF 50V	
C623	US135100	C. CE. CHP 0.1uF 16V	
C624	WK041800	C. EL 10uF 16V	
C625	US135100	C. CE. CHP 0.1uF 16V	
C626	UR067100	C. EL 10uF 50V	
C627-628	WJ603600	C. MYLAR 820pF 50V J	
C629-630	UR837100	C. EL 10uF 16V	U
C633-634	UR067100	C. EL 10uF 50V	
C635-642	US062100	C. CE. CHP 100pF 50V B	
* C643-644	US663330	C. CE. CHP 3300pF 50V	U
C700-702	US135100	C. CE. CHP 0.1uF 16V	
C703-704	WD758300	C. CE. CHP 10uF 10V	
C705-706	US135100	C. CE. CHP 0.1uF 16V	
C707-708	WD758300	C. CE. CHP 10uF 10V	
C709-710	US135100	C. CE. CHP 0.1uF 16V	
C711-712	US064100	C. CE. CHP 0.01uF 50V B	
C713	UF037220	C. EL. CHP 22uF 16V	
C714-717	US135100	C. CE. CHP 0.1uF 16V	
C718	US034390	C. CE. CHP 0.039uF 16V B	
C719-721	US135100	C. CE. CHP 0.1uF 16V	
C722-723	US063100	C. CE. CHP 1000pF 50V B	
C724-725	US135100	C. CE. CHP 0.1uF 16V	
C726	US064100	C. CE. CHP 0.01uF 50V B	
C727	US135100	C. CE. CHP 0.1uF 16V	
C728	US064100	C. CE. CHP 0.01uF 50V B	

* New Parts

P.C.B. DIGITAL

Ref No.	Part No.	Description	Markets
C729	US135100	C. CE. CHP 0. 1uF 16V	
C730	VZ243400	C. CE. CHP 0. 33uF 16V	
C731	VZ281900	C. CE. CHP 0. 47uF 16V K	
C732	US034820	C. CE. CHP 0. 082uF 16V K	
C733	US064100	C. CE. CHP 0. 01uF 50V B	
C734	US135100	C. CE. CHP 0. 1uF 16V	
C735	US061100	C. CE. CHP 10pF 50V B	
C736	US060800	C. CE. CHP 8pF 50V B	
C737-742	US135100	C. CE. CHP 0. 1uF 16V	
C743	UF037220	C. EL. CHP 22uF 16V	
C744-746	US135100	C. CE. CHP 0. 1uF 16V	
C747	UF037100	C. EL. CHP 10uF 16V	
C748-749	US135100	C. CE. CHP 0. 1uF 16V	
* C750	WP092800	C. EL. CHP 22uF 16V	
C751	US135100	C. CE. CHP 0. 1uF 16V	
* C752	WP092800	C. EL. CHP 22uF 16V	
C753	US135100	C. CE. CHP 0. 1uF 16V	
C754	UF037100	C. EL. CHP 10uF 16V	
C755-757	US135100	C. CE. CHP 0. 1uF 16V	
* C758	WP092800	C. EL. CHP 22uF 16V	
C759	US135100	C. CE. CHP 0. 1uF 16V	
C760	UF037220	C. EL. CHP 22uF 16V	
C761	US062100	C. CE. CHP 100pF 50V B	
C762	US135100	C. CE. CHP 0. 1uF 16V	
C763	UF037220	C. EL. CHP 22uF 16V	
C764-766	US135100	C. CE. CHP 0. 1uF 16V	
C767-768	US064100	C. CE. CHP 0. 01uF 50V B	
C769	US135100	C. CE. CHP 0. 1uF 16V	
C770-771	US064100	C. CE. CHP 0. 01uF 50V B	
C772	US135100	C. CE. CHP 0. 1uF 16V	
C773	US064100	C. CE. CHP 0. 01uF 50V B	
C774-776	US135100	C. CE. CHP 0. 1uF 16V	
C777-778	US064100	C. CE. CHP 0. 01uF 50V B	
C779-780	US135100	C. CE. CHP 0. 1uF 16V	
C781	US064100	C. CE. CHP 0. 01uF 50V B	
C782-790	US135100	C. CE. CHP 0. 1uF 16V	
* C791	WP092800	C. EL. CHP 22uF 16V	
C792-794	US135100	C. CE. CHP 0. 1uF 16V	
C795	UF037100	C. EL. CHP 10uF 16V	
C796-797	US063100	C. CE. CHP 1000pF 50V B	
C798-799	US064100	C. CE. CHP 0. 01uF 50V B	
C806	US135100	C. CE. CHP 0. 1uF 16V	
C930	US135100	C. CE. CHP 0. 1uF 16V	
C950	UF438100	C. EL. CHP 100uF 16V	
C951	UF417220	C. EL. CHP 22uF 6. 3V	
C952	US135100	C. CE. CHP 0. 1uF 16V	
C953-954	US064100	C. CE. CHP 0. 01uF 50V B	
C955	WG888300	C. CE. M. CHP 10uF 6. 3V	
C956	US135100	C. CE. CHP 0. 1uF 16V	
C957-960	US064100	C. CE. CHP 0. 01uF 50V B	
C961	US135100	C. CE. CHP 0. 1uF 16V	
C962	WG888300	C. CE. M. CHP 10uF 6. 3V	
C963-964	US064100	C. CE. CHP 0. 01uF 50V B	
C965	US135100	C. CE. CHP 0. 1uF 16V	
C966	US064100	C. CE. CHP 0. 01uF 50V B	
C967-968	US135100	C. CE. CHP 0. 1uF 16V	
C972	WG888300	C. CE. M. CHP 10uF 6. 3V	

* New Parts

Ref No.	Part No.	Description	Markets
C973	WD758300	C. CE. CHP 10uF 10V	
C974-975	UR267470	C. EL 47uF 50V	U
* C976-977	WJ603700	C. MYLAR 1000pF 50V	U
C978-979	UR267100	C. EL 10uF 50V	U
* C980-981	WJ605600	C. MYLAR 0. 033uF 50V	U
* C982-983	WJ604900	C. MYLAR 9100pF 50V	U
C984-985	UR218220	C. EL 220uF 6. 3V	U
C986-989	WJ603100	C. MYLAR 220pF 50V	U
C990	US064100	C. CE. CHP 0. 01uF 50V B	U
C991-993	US135100	C. CE. CHP 0. 1uF 16V	
C994	UR237470	C. EL 47uF 16V	
C995-998	US135100	C. CE. CHP 0. 1uF 16V	
C999	US064100	C. CE. CHP 0. 01uF 50V B	
D23-25	WE674800	DIODE AVR161A1R1NTB	
D27	WE674800	DIODE AVR161A1R1NTB	
D36-37	WE674800	DIODE AVR161A1R1NTB	
D47-49	WE674800	DIODE AVR161A1R1NTB	
D59-61	WE674800	DIODE AVR161A1R1NTB	
D62	VV220700	DIODE. SHOT RB501V-40	
D63-64	V6267600	DIODE RB051L-40	
D67-68	WE674800	DIODE AVR161A1R1NTB	
D151-152	WE674800	DIODE AVR161A1R1NTB	
D153	VV220700	DIODE. SHOT RB501V-40	
D200-204	VU990900	DIODE. ZENR MAZ8033GHL 3. 4V	
D400-402	WE674800	DIODE AVR161A1R1NTB	U
D403-404	VT332900	DIODE 1SS355	
D406-407	VT332900	DIODE 1SS355	
D600	VT332900	DIODE 1SS355	
D602-603	VT332900	DIODE 1SS355	
D702-703	VT332900	DIODE 1SS355	
D950	WE674800	DIODE AVR161A1R1NTB	
* D951-958	WP385600	PESD PESD0603-240	
D959-961	WE674800	DIODE AVR161A1R1NTB	
D962	VT332900	DIODE 1SS355	
D963-964	VV659300	DIODE. ZENR RLZ7. 5B 7. 5V	U
IC3	XS775A00	IC TC7SH04FU	
IC5	X7195A00	IC R1172S121D-E2-F	
IC6	XZ287A00	IC SN74LVC245APWR	
IC10	X7741A00	IC NJM2867F3-05 (TE1)	
IC11	X0199B00	IC TC74VHC157FT (EL, K)	
IC16	X7741A00	IC NJM2867F3-05 (TE1)	
IC20	X8013A00	IC. CPU M3087BFKBGP CPU	(unwritten)
IC21	X8194A00	IC R1172H331D-T1-F	
* IC22	YA739A00	IC. MEMORY LE25LB2562M-TLM-E	U
* IC22	YC035A00	IC LE25LB643M-TLM-E	CRTKABGEFL
IC40	X8192A00	IC F2621E-01-TR	U
* IC41	YA399A00	IC LC89058WD-E	
IC43	X7378A00	IC NJM4565M (TE1)	
* IC45	X9798B00	IC CS230003-CZZR	
* IC47	YC008A00	IC R1173S001D-E2-F	
* IC48	X9626B00	IC. MEMORY K4S641632N-LC60000	
* IC49	YC016C00	IC. MEMORY F49L160BA-70TG2N	(written)
IC50	XR680A00	IC TC7SH08FU (TE85L, JF)	
* IC51	YA255A00	IC R1172H501D-T1-F	
IC52	XR680A00	IC TC7SH08FU (TE85L, JF)	
IC61	X7375A00	IC PCM1781DBQR	U
IC62	X0199B00	IC TC74VHC157FT (EL, K)	

* New Parts

P.C.B. DIGITAL and P.C.B. OPERATION

Ref No.	Part No.	Description	Markets
IC63	XS534A00	IC	NJM78M05DL1A
IC65	X7355A00	IC	PCM1680DBQR
IC66	X7357A00	IC	PCM1803DBR
IC67	X3586B00	IC	TC74VHCT08AFT EL, K
IC68	XR680A00	IC	TC7SH08FU (TE85L, JF)
IC70	X9393A00	IC	ADV7800BSTZ-80
* IC71	YA215A00	IC	ABT1012
IC72	X6671A00	IC	ADV7172KSTZ
IC73	X9460A00	IC	R1172H181B-T1-F
IC74	X8194A00	IC	R1172H331D-T1-F
IC75	X8531A00	IC	TC7WZ32FK
IC76-78	XZ283A00	IC	SN74LVTH245APW BUS
* IC80	YA844A00	IC	ISL83385E1BZ-T
IC81	X3505A00	IC	NJM2068MD-TE2
IC95	X8900A00	IC	CXB1442AR-T4
IC96	X8368A00	IC	PCA9517DP
IC97	X8897A00	IC	R1172S331B-E2-F
JK81-82	V9435700	JACK. MNI	MSJ-035-12APC
PJ80	VM725600	JACK. PIN	2P
Q3-10	VQ986700	TR	2SC4081 T106
Q80	iA101510	TR	2SA1015 Y
Q81	iC181510	TR	2SC1815 Y
Q82	WG538600	TR	KTA1046-Y-U/P
Q83	iC181510	TR	2SC1815 Y
Q84	iA101510	TR	2SA1015 Y
Q85	iC181510	TR	2SC1815 Y
Q86	WG538600	TR	KTA1046-Y-U/P
Q87	iC181510	TR	2SC1815 Y
Q95-96	VQ986700	TR	2SC4081 T106
* Q200	WQ381000	FET	MCH6336-TL-E
Q201-202	VV655300	TR. DGT	DTA144EKA
Q203-209	VR936300	TR	2SA1576A T106
* Q400	WQ381000	FET	MCH6336-TL-E
Q401	VV655300	TR. DGT	DTA144EKA
Q600	VV655200	TR. DGT	DTA143EKA
Q601	VV655700	TR. DGT	DTC144EKA
* Q700	WQ381000	FET	MCH6336-TL-E
Q701	VR936300	TR	2SA1576A T106
* Q702	WQ381000	FET	MCH6336-TL-E
Q703	VR936300	TR	2SA1576A T106
Q704	WE834500	FET	UPA672T-T1-A
R180	V8070100	R. MTL. FLM	2. 2Ω 1W
R189	WB784700	R. MTL. FLM	6. 8Ω 1W
R200	RD357100	R. CHP	10KΩ 1/16W
R466-467	HV753220	R. CAR. FP	2. 2Ω 1/4W
* R601	WQ072300	R. MTL. OXD	2. 2Ω 1W
R607	HV753220	R. CAR. FP	2. 2Ω 1/4W
R930	HV753560	R. CAR. FP	5. 6Ω 1/4W
R936	HV753560	R. CAR. FP	5. 6Ω 1/4W
* R967-968	WQ964700	R. MTL. OXD	470Ω 1W
ST1-2	V4040500	SCR. TERM	M3
ST80	V4040500	SCR. TERM	M3
ST80	V4040500	SCR. TERM	M3
ST81	V4040500	SCR. TERM	M3
* XL1	WR725300	RSNR. CRYST	27MHz SMD-49
XL20	WF997400	RSNR. CE	20MHz
* XL41	WR846900	RSNR. CRYST	45.1984MHz DSX321G

* New Parts

Ref No.	Part No.	Description	Markets
XL42	V3625700	RSNR. CRYST	24. 576MHz
XL70	VZ772700	RSNR. CRYST	28. 63636MHz
* WS305500	P. C. B.	OPERATION	U
* WS305600	P. C. B.	OPERATION	CRTA
* WS305700	P. C. B.	OPERATION	KBGEFL
CB401	VQ045400	CN. BS. PIN	25P
CB402	VQ044400	CN. BS. PIN	9P
CB451	VQ961100	CN. BS. PIN	8P
CB452	V9357000	CN	19P TE
CB454	VQ962100	CN. BS. PIN	18P
CB455	V9357000	CN	19P TE
CB456	VQ961800	CN. BS. PIN	15P
CB457	VQ961400	CN. BS. PIN	11P
CB458	V9357000	CN	19P TE
CB459	VQ963300	CN. BS. PIN	12P
CB460	VQ963100	CN. BS. PIN	10P
CB461	VQ044400	CN. BS. PIN	9P
CB462	VK026400	CN. BS. PIN	5P
CB463	VQ585700	CN. JUMPER	7P
CB464	VQ585500	CN. JUMPER	5P
* CB471	WQ680200	CN. USB	4P TE AAPVA004C0
CB475	VK024900	CN. BS. PIN	5P TE
CB477	VB858300	CN. BS. PIN	4P
C4001	US063100	C. CE. CHP	1000pF 50V B
C4002	US065100	C. CE. CHP	0. 1uF 50V B
C4003	UR067100	C. EL	10uF 50V
C4004	US064100	C. CE. CHP	0. 01uF 50V B
C4005	UR837220	C. EL	22uF 16V
C4006	US062100	C. CE. CHP	100pF 50V B
C4007	UR257470	C. EL	47uF 35V
C4008	US061330	C. CE. CHP	33pF 50V B
C4009-4010	UR267220	C. EL	22uF 50V
C4011	UR067100	C. EL	10uF 50V
C4012-4013	US135100	C. CE. CHP	0. 1uF 16V
C4015	UR268220	C. EL	220uF 50V
C4016	UM388330	C. EL	330uF 6. 3V
C4017	US135100	C. CE. CHP	0. 1uF 16V
C4018	US061680	C. CE. CHP	68pF 50V B
C4019	US065100	C. CE. CHP	0. 1uF 50V B
C4020-4021	US135100	C. CE. CHP	0. 1uF 16V
C4022	US064100	C. CE. CHP	0. 01uF 50V B
C4023-4024	US063100	C. CE. CHP	1000pF 50V B
C4025-4026	US065100	C. CE. CHP	0. 1uF 50V B
C4027	US135100	C. CE. CHP	0. 1uF 16V
C4028	US062100	C. CE. CHP	100pF 50V B
C4030	US062100	C. CE. CHP	100pF 50V B
C4031	US062470	C. CE. CHP	470pF 50V B
C4032	US135100	C. CE. CHP	0. 1uF 16V
C4033	US063100	C. CE. CHP	1000pF 50V B
C4034	UM417100	C. EL	10uF 50V
C4035	US135100	C. CE. CHP	0. 1uF 16V
C4036-4040	US063100	C. CE. CHP	1000pF 50V B
C4041-4046	US135100	C. CE. CHP	0. 1uF 16V
C4201	UR067470	C. EL	47uF 50V

* New Parts

P.C.B. OPERATION

Ref No.	Part No.	Description	Markets
C4202	US063100	C. CE. CHP	1000pF 50V B
C4203	US135100	C. CE. CHP	0. 1uF 16V
C4205-4211	US062220	C. CE. CHP	220pF 50V B
C4212	US062100	C. CE. CHP	100pF 50V B
C4213	UR267100	C. EL	10uF 50V
C4214	WKO41800	C. EL	10uF 16V
* C4215	WJ603500	C. MYLAR	680pF 50V
C4216	US135100	C. CE. CHP	0. 1uF 16V
C4217	UR267470	C. EL	47uF 50V
C4218	US135100	C. CE. CHP	0. 1uF 16V
C4219	UR267470	C. EL	47uF 50V
* C4220	WJ603500	C. MYLAR	680pF 50V
C4221	WKO41800	C. EL	10uF 16V
C4222	UR267100	C. EL	10uF 50V
C4223-4224	US062100	C. CE. CHP	100pF 50V B
C4225	UR267100	C. EL	10uF 50V
C4226	WKO41800	C. EL	10uF 16V
* C4227	WJ603500	C. MYLAR	680pF 50V
C4228-4229	US135100	C. CE. CHP	0. 1uF 16V
C4230	WJ605800	C. MYLAR	0. 047uF 50V J
C4231-4232	UR267100	C. EL	10uF 50V
* C4233	WJ604700	C. MYLAR	6800pF 50V
C4234	US062100	C. CE. CHP	100pF 50V B
C4235	UR267100	C. EL	10uF 50V
C4236	WKO41800	C. EL	10uF 16V
* C4237	WJ603500	C. MYLAR	680pF 50V
C4238-4239	US135100	C. CE. CHP	0. 1uF 16V
* C4240	WJ603500	C. MYLAR	680pF 50V
C4241	WKO41800	C. EL	10uF 16V
C4242	UR267100	C. EL	10uF 50V
C4243-4244	US062100	C. CE. CHP	100pF 50V B
C4245	UR267100	C. EL	10uF 50V
C4246	WKO41800	C. EL	10uF 16V
* C4247	WJ603500	C. MYLAR	680pF 50V
C4248-4249	US135100	C. CE. CHP	0. 1uF 16V
* C4250	WJ603500	C. MYLAR	680pF 50V
C4251	WKO41800	C. EL	10uF 16V
C4252	UR267100	C. EL	10uF 50V
C4253	US062100	C. CE. CHP	100pF 50V B
C4254-4255	UR067100	C. EL	10uF 50V
C4301	UR267470	C. EL	47uF 50V
C4302	UR267470	C. EL	47uF 50V
* C4303-4304	WJ603700	C. MYLAR	1000pF 50V
C4305	UR267100	C. EL	10uF 50V
C4306	UR267100	C. EL	10uF 50V
* C4307-4308	WJ605600	C. MYLAR	0. 033uF 50V
* C4309	WJ604900	C. MYLAR	9100pF 50V
* C4310	WJ604900	C. MYLAR	9100pF 50V
C4311	UR218220	C. EL	220uF 6. 3V
C4312	UR218220	C. EL	220uF 6. 3V
C4313	WJ603100	C. MYLAR	220pF 50V
C4314	WJ603100	C. MYLAR	220pF 50V
C4315	WJ603100	C. MYLAR	220pF 50V
C4316	WJ603100	C. MYLAR	220pF 50V
C4317	US064100	C. CE. CHP	0. 01uF 50V B
C4318-4325	WJ605000	C. MYLAR	0. 01uF 50V J
C4401	US062100	C. CE. CHP	100pF 50V B

* New Parts

Ref No.	Part No.	Description	Markets
C4402	US063100	C. CE. CHP	1000pF 50V B
* C4403	WJ604300	C. MYLAR	3300pF 50V
C4404-4405	US062220	C. CE. CHP	220pF 50V B
* C4406	WJ604300	C. MYLAR	3300pF 50V
C4407	US064100	C. CE. CHP	0. 01uF 50V B
C4410	US135100	C. CE. CHP	0. 1uF 16V
C4411	US060500	C. CE. CHP	5pF 50V B
C4413	US060500	C. CE. CHP	5pF 50V B
C4414	US063100	C. CE. CHP	1000pF 50V B
C4415	US135100	C. CE. CHP	0. 1uF 16V
C4417	US126100	C. CE. CHP	1uF 10V
C4418	US062220	C. CE. CHP	220pF 50V B
C4419	US063100	C. CE. CHP	1000pF 50V B
D4001-4002	VT332900	DIODE	1SS355
D4003	VU171900	DIODE. ZENR	UDZ5. 1B 5. 1V
D4004-4005	VT332900	DIODE	1SS355
D4006-4007	VU991000	DIODE. ZENR	MAZ8036GLL 3. 5V
D4008	WG760400	LED	SELK6E10C BLUE
* D4009	WR095700	LED	8224-10SDRD/S530A3
D4011	V2598200	LED	S1R-505ST
D4301	VV659300	DIODE. ZENR	RLZ7. 5B 7. 5V
D4302	VV659300	DIODE. ZENR	RLZ7. 5B 7. 5V
D4303	VT332900	DIODE	1SS355
D4305	VT332900	DIODE	1SS355
D4401-4402	VT332900	DIODE	1SS355
D4404-4405	VT332900	DIODE	1SS355
D4408	VT332900	DIODE	1SS355
D4410	VT332900	DIODE	1SS355
IC401	X7378A00	IC	NJM4565M (TE1)
IC402	X6386A00	IC	M66003-0131FP
IC451-454	X5482A00	IC	NE5532DR OP AMP
IC461	X3505A00	IC	NJM2068MD-TE2
JK401	WC814400	JACK. MNI	JY-3554-01-130
JK451	VV269500	CN	8P DIN
JK472	V9408200	JACK. PHONE	MSJ-064-05B GR
PJ461	WD599600	JACK. PIN	2P MSP-252V2-06 NI
PJ471	WJ117500	JACK. PIN	3P
Q4001-4003	WC529400	TR	KTC3875S Y GR RTK
Q4004	VV655400	TR. DGT	DTA114EKA
Q4005	WC397700	TR	2N5401C-AT
Q4006-4012	WC529400	TR	KTC3875S Y GR RTK
Q4301	VV655400	TR. DGT	DTA114EKA
Q4302	VV655000	TR. DGT	DTA114EKA
Q4305	VV655400	TR. DGT	DTA114EKA
Q4306	VV655000	TR. DGT	DTA114EKA
R4201	HV753100	R. CAR. FP	1 Ω 1/4W
* R4208-4209	WQ072300	R. MTL. OXD	2. 2 Ω 1W
* R4301	WQ964700	R. MTL. OXD	470 Ω 1W
* R4302	WQ964700	R. MTL. OXD	470 Ω 1W
R4320-4323	HV757100	R. CAR. FP	10K Ω 1/4W
R4413-4414	R8071300	R. MTL. FLM	470 Ω 1W
RY461	WJ122400	RELAY	981-2A-24DS-SP7
RY463	WJ122400	RELAY	981-2A-24DS-SP7
ST451	V4040500	SCR. TERM	M3
ST471	V4040500	SCR. TERM	M3
SW401-404	WD483100	SW. TACT	SKRGAAD010
SW406-407	WD483100	SW. TACT	SKRGAAD010

* New Parts

P.C.B. OPERATION and P.C.B. MAIN

* New Parts

147

P.C.B. MAIN and P.C.B. VIDEO

Ref No.	Part No.	Description	Markets
C1608	US044220	C. CE. CHP 0.022uF 25V	
C1609-1610	US064100	C. CE. CHP 0.01uF 50V B	
D1001-1016	VR496500	D1ODE. CHP MA111 FLAT TP	
△ D1017-1023	VG437500	D1ODE. ZENR MTZJ5. 1C 5. 1V	
D1024-1039	VR496500	D1ODE. CHP MA111 FLAT TP	
△ D1040	WK878000	D1ODE. BRG D15XBN20-7001 15A	
△ D1041	WH487300	D1ODE. BRG RS203M 2. 0A 200V	
D1042	VG440500	D1ODE. ZENR MTZJ13B 13V	
D1043	VR496500	D1ODE. CHP MA111 FLAT TP	
△ D1044-1045	VG435500	D1ODE. ZENR MTZJ2. 4B 2. 4V	
D1501-1502	VG438400	D1ODE. ZENR MTZJ6. 8C 6. 8V	
△ F100	KB000780	FUSE T5A 250V	R
G101	V5995800	PLATE. GND	
△ IC101	XJ608A00	IC NJM7812FA	
△ IC102	X4154A00	IC KIA7912PI	
IC152	XZ509A00	IC TC74VHC04FT INVER	
* IC153	YA361A00	IC R2A15220FP	
IC154	X7378A00	IC NJM4565M(Te1)	
PJ150	V5715300	JACK. PIN 2P OR/OR	
PJ151	V7046800	JACK. PIN 6P MSP-246V1-01NI	
PJ152-153	V7046700	JACK. PIN 4P MSP-244V1-01NI	
PJ154	WG674900	JACK. PIN 4P	
PJ156	V7046800	JACK. PIN 6P MSP-246V1-01NI	
PJ157	V7046700	JACK. PIN 4P MSP-244V1-01NI	
PJ158	WG674900	JACK. PIN 4P	
PJ159	V7189700	JACK. PIN 1P	
Q1001-1014	WF549900	TR 2SC3906K T146 R, S	
Q1015-1021	VE198700	TR 2SA1145 O, Y	
△ Q1022-1028	VK432900	TR 2SD1915F S, T	
△ Q1029-1035	VE198800	TR 2SC2705 O, Y	
Q1036-1042	WG408900	TR 2SC5291 S, T	
△ Q1043-1049	WG408800	TR 2SA2168 S, T	
Q1050-1056	WD281200	TR. PAIR A2151/C6011 O, P, Y	
Q1057-1063	WC139600	TR KTC3911S GR BL	
Q1064	WH372100	TR KTA1517S GR TP	
Q1065	WC139600	TR KTC3911S GR BL	
△ * Q1067-1068	WC292600	TR KTA1837-U	
△ Q1069-1070	WC398400	TR 2N5551C-AT	
△ Q1071	WC397700	TR 2N5401C-AT	
△ Q1072	VP872600	TR 2SA1708 S, T	
Q1073	WC398500	TR. DGT KRA102M-AT	
* Q1074	WS512800	TR. DGT KRC105M-AT/P	
Q1500-1504	VZ725900	TR 2SD1938F S, T	
Q1507-1527	VZ725900	TR 2SD1938F S, T	
R1001-1007	HF356100	R. CAR 1KΩ 1/2W	
R1008-1010	HF356180	R. CAR 1. 8KΩ 1/2W	
R1011-1014	HL006180	R. MTL. OXD 1. 8KΩ 1/2W	
R1022-1028	HF355330	R. CAR 330Ω 1/2W	
* R1029-1035	WA622000	R. MTL. OXD 1. 2KΩ 1W	
R1036-1042	V8070900	R. MTL. FLM 100Ω 1W	
R1043-1049	V8072600	R. MTL. OXD 33KΩ 1W	
R1079-1085	HL005120	R. MTL. OXD 120Ω 1/2W	
R1086-1092	WG727400	R. MTL. FLM 2. 7KΩ 1/4W	
R1093-1099	WG725600	R. MTL. FLM 470Ω 1/4W	
R1100-1106	WG726400	R. MTL. FLM 1KΩ 1/4W	
R1107-1112	WG726200	R. MTL. FLM 820Ω 1/4W	
△ R1113-1126	HV755120	R. CAR. FP 120Ω 1/4W	

* New Parts

Ref No.	Part No.	Description	Markets
R1127-1133	HF355470	R. CAR 470Ω 1/2W	
△ R1134-1147	HV754100	R. CAR. FP 10Ω 1/4W	
△ * R1148-1154	WP839400	R. WW 0. 22+0. 22 3W	
△ R1176-1182	V8070300	R. MTL. FLM 10Ω 1W	
△ R1197-1198	V8070200	R. MTL. FLM 4. 7Ω 1W	
△ R1211	HV754100	R. CAR. FP 10Ω 1/4W	
R1213	V8072100	R. MTL. OXD 5. 6KΩ 1W	
R1214	HV755560	R. CAR. FP 560Ω 1/4W	
R1219	V8072000	R. MTL. OXD 4. 7KΩ 1W	
△ R1222	HV756100	R. CAR. FP 1KΩ 1/4W	
△ R1234-1235	HV754100	R. CAR. FP 10Ω 1/4W	
R1236	WG726200	R. MTL. FLM 820Ω 1/4W	
△ R1238	V8070300	R. MTL. FLM 10Ω 1W	
R1504	HV753100	R. CAR. FP 1Ω 1/4W	
* R1573	WQ835700	R. MTL. OXD 82Ω 1W	
* R1575	WQ835700	R. MTL. OXD 82Ω 1W	
* R1664-1665	WQ835800	R. MTL. OXD 100Ω 1W	
△ RY101	WE648700	RELAY DC DH24D2-0-Q	
ST100	V4040500	SCR. TERM M3	
△ SW101	WB493700	VOLT. SELCT R8140246	R
△ SW101	WD073700	VOLT. SELCT R8140254	L
U1500-1501	WH169900	CN. PHOTO. R 1P GP1FAV51RKOF	
	WE774200	SCR. BND. HD 3x10 MFZN2W3	
* WS304700	P. C. B.	VIDEO	U
* WS304800	P. C. B.	VIDEO	C
* WS304900	P. C. B.	VIDEO	R
* WS305000	P. C. B.	VIDEO	T
* WS305100	P. C. B.	VIDEO	K
* WS305200	P. C. B.	VIDEO	A
* WS305300	P. C. B.	VIDEO	BGEF
* WS305400	P. C. B.	VIDEO	L
CB303	VQ961500	CN. BS. PIN 12P	
CB304	VN394900	CN. BS. PIN 14P	
CB321	VM859500	CN. BS. PIN 11P	CRTKABGEF
CB322	VM923600	CN. BS. PIN 13P	U
CB332	VQ961300	CN. BS. PIN 10P	
CB333	VK024700	CN. BS. PIN 3P	
CB340	LB918020	CN. BS. PIN 2P	
CB342	LB918040	CN. BS. PIN 4P	
CB343	VZ130900	CN. JUMPER 4P	
CB344	VQ585500	CN. JUMPER 5P	
CB346	VB390000	CN. BS. PIN 4P	
* CB349	VQ047700	CN. BS. PIN 22P	
CB381	VQ962800	CN. BS. PIN 7P	
CB391	VQ044100	CN. BS. PIN 5P	BGEF
C3001	US062100	C. CE. CHP 100pF 50V B	
C3002-3004	US060800	C. CE. CHP 8pF 50V B	
C3005	US062100	C. CE. CHP 100pF 50V B	
C3006	UR237470	C. EL 47uF 16V	
C3007-3008	US135100	C. CE. CHP 0. 1uF 16V	
C3009	UR237470	C. EL 47uF 16V	
C3011	US060300	C. CE. CHP 3pF 50V B	
C3012	UR837470	C. EL 47uF 16V	
C3013-3014	US060300	C. CE. CHP 3pF 50V B	

* New Parts

P.C.B. VIDEO

Ref No.	Part No.	Description	Markets
C3015-3017	US135100	C. CE. CHP	0. 1uF 16V
C3018	UR267100	C. EL	10uF 50V
C3019	US135100	C. CE. CHP	0. 1uF 16V
C3020	UR267100	C. EL	10uF 50V
C3021-3025	US135100	C. CE. CHP	0. 1uF 16V
C3026	UR267100	C. EL	10uF 50V
C3027	WD758300	C. CE. CHP	10uF 10V
C3029	WD758300	C. CE. CHP	10uF 10V
C3031	WD758300	C. CE. CHP	10uF 10V
C3033	UR837470	C. EL	47uF 16V
C3035-3037	WD758300	C. CE. CHP	10uF 10V
C3043-3044	US135100	C. CE. CHP	0. 1uF 16V
C3045	UR837470	C. EL	47uF 16V
C3047	US135100	C. CE. CHP	0. 1uF 16V
C3048	UR238220	C. EL	220uF 16V
C3049	UR837470	C. EL	47uF 16V
C3050	US135100	C. CE. CHP	0. 1uF 16V
C3051	UR238220	C. EL	220uF 16V
C3063	US135100	C. CE. CHP	0. 1uF 16V
C3065	UR237470	C. EL	47uF 16V
C3067	US135100	C. CE. CHP	0. 1uF 16V
C3072	US135100	C. CE. CHP	0. 1uF 16V
C3073	UR238220	C. EL	220uF 16V
C3077	US135100	C. CE. CHP	0. 1uF 16V
C3080-3085	WD758300	C. CE. CHP	10uF 10V
C3201	US061270	C. CE. CHP	27pF 50V B
C3202	UR237100	C. EL	10uF 16V
C3203	US061270	C. CE. CHP	27pF 50V B
C3204-3205	US135100	C. CE. CHP	0. 1uF 16V
C3206	US062560	C. CE. CHP	560pF 50V B
C3207-3208	US062330	C. CE. CHP	330pF 50V B
C3209	US135100	C. CE. CHP	0. 1uF 16V
C3211	UR237470	C. EL	47uF 16V
C3212	UR237470	C. EL	47uF 16V
C3213	UR237470	C. EL	47uF 16V
C3214	UR237470	C. EL	47uF 16V
C3215	US062100	C. CE. CHP	100pF 50V B
C3217	US062100	C. CE. CHP	100pF 50V B
C3218	US062100	C. CE. CHP	100pF 50V B
C3220	US064100	C. CE. CHP	0. 01uF 50V B
C3221	US062100	C. CE. CHP	100pF 50V B
C3303-3305	VR324900	C. MYLAR	0. 1uF 100V
C3307	WG601900	C. EL	10000uF 16V
C3308	UR278100	C. EL	100uF 63V
C3309	UR03A100	C. EL	10000uF 16V
C3310	UR039470	C. EL	4700uF 16V
C3311	UR266100	C. EL	1uF 50V
C3312	UR267220	C. EL	22uF 50V
C3313	UR266100	C. EL	1uF 50V
C3314	UR266100	C. EL	1uF 50V
C3315	UR267100	C. EL	10uF 50V
C3316	UR268100	C. EL	100uF 50V
C3317	UR266100	C. EL	1uF 50V
C3318	UR237470	C. EL	47uF 16V
C3319	UR266100	C. EL	1uF 50V
C3320-3321	UR267330	C. EL	33uF 50V
C3324	UR237470	C. EL	47uF 16V

* New Parts

Ref No.	Part No.	Description	Markets
C3403-3409	WJ605000	C. MYLAR	0. 01uF 50V J
* C3410-3416	WJ605200	C. MYLAR	0. 015uF 50V
C3603-3604	US063100	C. CE. CHP	1000pF 50V B
C3606	US064100	C. CE. CHP	0. 01uF 50V B
C3801	US064100	C. CE. CHP	0. 01uF 50V B
C3802	V7887800	C. EL	1uF 50V
C3803	WJ335500	C. EL	2. 2uF 50V
* C3804	WJ603700	C. MYLAR	1000pF 50V
C3805	US064100	C. CE. CHP	0. 01uF 50V B
C3806-3807	WD758300	C. CE. CHP	10uF 10V
C3901	US064100	C. CE. CHP	0. 01uF 50V B
C3902	US062120	C. CE. CHP	120pF 50V B
C3903	US062220	C. CE. CHP	220pF 50V B
C3904	US135100	C. CE. CHP	0. 1uF 16V
C3905	UR837470	C. EL	47uF 16V
C3906	UR837100	C. EL	10uF 16V
C3907	UR818470	C. EL	470uF 6. 3V
C3908	US064100	C. CE. CHP	0. 01uF 50V B
D3201	VG436100	DIODE. ZENR	MTZJ3. 3B 3. 3V
△ D3202	VG439500	DIODE. ZENR	MTZJ10B 10V
D3302	WH487300	DIODE. BRG	RS203M 2. 0A 200V
△ D3304	WH487300	DIODE. BRG	RS203M 2. 0A 200V
D3306	VV307700	DIODE	1N4002S
D3307	VG440200	DIODE. ZENR	MTZJ12B 12V
* D3308	VG444700	DIODE. ZENR	MTZ J 39D 39. 0V TP
D3309	VT332900	DIODE	1SS355
D3310	VT332900	DIODE	1SS355
D3311	VT332900	DIODE	1SS355
D3313-3314	VT332900	DIODE	1SS355
D3320	VG437400	DIODE. ZENR	MTZJ5. 1B 5. 1V
D3403-3407	VT332900	DIODE	1SS355
D3601-3602	VT332900	DIODE	1SS355
D3801-3805	VT332900	DIODE	1SS355
D3901-3902	VT332900	DIODE	1SS355
IC301-303	XY879A00	IC	TC74HC4053AF (EL)
IC305	X6742A00	IC	LA73050-TLM-E
IC306	X2904A00	IC	NJM2581M VIDEO AMP
IC307	XY549A00	IC	TC74HC4051AFEL
IC308	X7779A00	IC	LC709004A-TLM-E
IC310	X8875A00	IC	FHP33501M14X
IC321	X8235A00	IC	LC72725KM
IC331	X8276A00	IC	NJM2396F05
IC332-333	X8035A00	IC	BA00JC5WT-V5
IC334	X6143A00	IC	NJM2388F05 5. 0V
IC391	XZ509A00	IC	TC74VHC04FT INVER
JK361-362	V9435700	JACK. MN1	MSJ-035-12APC
JK391	V6931000	CN. DIN	1P YKF51-5506
PJ301	WG505100	JACK. PIN	6P
PJ302	V7189800	JACK. PIN	1P
* PJ303	WH381400	JACK. PIN	3P JACK G, B, R
PJ304	V7189800	JACK. PIN	1P
PJ305-306	V7190000	JACK. PIN	2P
Q3001	VR936300	TR	2SA1576A T106
Q3201	iC174020	TR	2SC1740S QRS
Q3203	iC181510	TR	2SC1815 Y
△ Q3301	VP872600	TR	2SA1708 S, T
Q3302	iA101510	TR	2SA1015 Y

* New Parts

P.C.B. VIDEO and P.C.B. GUI

Ref No.	Part No.	Description	Markets
Q3303	WG538600	TR	KTA1046-Y-U/P
Q3304	iA101510	TR	2SA1015 Y
Q3305	iC181510	TR	2SC1815 Y
Q3405	VV655400	TR. DGT	DTC114EKA
Q3406	VV655000	TR. DGT	DTA114EKA
Q3407	VV655400	TR. DGT	DTC114EKA
Q3408	VV655000	TR. DGT	DTA114EKA
Q3409	VV655400	TR. DGT	DTC114EKA
Q3410	VV655000	TR. DGT	DTA114EKA
Q3411	VV655400	TR. DGT	DTC114EKA
Q3412	VV655000	TR. DGT	DTA114EKA
Q3413	VV655400	TR. DGT	DTC114EKA
Q3414	VV655000	TR. DGT	DTA114EKA
Q3801-3802	iC181510	TR	2SC1815 Y
Q3803	VV655700	TR. DGT	DTC144EKA
R3021	HV753100	R. CAR. FP	1 Ω 1/4W
R3025	HV753100	R. CAR. FP	1 Ω 1/4W
R3046-3049	HV753100	R. CAR. FP	1 Ω 1/4W
R3060-3061	HV753100	R. CAR. FP	1 Ω 1/4W
R3208	HV755680	R. CAR. FP	680 Ω 1/4W
R3210	HV754180	R. CAR. FP	18 Ω 1/4W
R3301	HV753220	R. CAR. FP	2. 2 Ω 1/4W
R3306	HV756100	R. CAR. FP	1K Ω 1/4W
R3315-3316	HV756470	R. CAR. FP	4. 7K Ω 1/4W
R3403-3406	HV757100	R. CAR. FP	10K Ω 1/4W
R3910	HV753220	R. CAR. FP	2. 2 Ω 1/4W
RY341-345	WJ122400	RELAY	981-2A-24DS-SP7
ST331-332	V4040500	SCR. TERM	M3
ST361-362	V4040500	SCR. TERM	M3
ST381-383	V4040500	SCR. TERM	M3
TE341	WK560800	TERM. SP	4P MST-204V1-01 NC
TE341	WK560900	TERM. SP	4P MST-204V1-01 WC
TE342	WK561000	TERM. SP	6P MST-207V1-01 NC
TE342	WK561100	TERM. SP	6P MST-207V1-01 WC
TE343	WK560800	TERM. SP	4P MST-204V1-01 NC
TE343	WK560900	TERM. SP	4P MST-204V1-01 WC
XL321	V2731100	RSNR. CRYST	4. 332M HC-49/U
	WE774200	SCR. BND. HD	3x10 MFZN2W3
* WS306800	P. C. B.	GUI	
CB500	VK026600	CN. BS. PIN	7P
CB501	VQ044700	CN. BS. PIN	16P
CB503	VK026300	CN. BS. PIN	4P
CB550	VB858500	CN. BS. PIN	6P
* CB551	WM297100	CN. LAN	6P 08B1-1X1T-06-F
* C5000-5001	US625100	C. CE. CHP	0. 100uF 10V
C5002-5003	US061120	C. CE. CHP	12pF 50V B
* C5004	US625100	C. CE. CHP	0. 100uF 10V
C5005-5008	US135100	C. CE. CHP	0. 1uF 16V
C5009-5010	US061180	C. CE. CHP	18pF 50V B
C5012	US135100	C. CE. CHP	0. 1uF 16V
C5013	US663100	C. CE. CHP	1000pF 50V
* C5014-5016	US625100	C. CE. CHP	0. 100uF 10V
C5017	US135100	C. CE. CHP	0. 1uF 16V
C5018	US063100	C. CE. CHP	1000pF 50V B

* New Parts

Ref No.	Part No.	Description	Markets
* C5019	US625100	C. CE. CHP	0. 100uF 10V
C5020	US063100	C. CE. CHP	1000pF 50V B
C5021-5024	US135100	C. CE. CHP	0. 1uF 16V
C5025	US063100	C. CE. CHP	1000pF 50V B
C5026	US064100	C. CE. CHP	0. 01uF 50V B
C5027	US063100	C. CE. CHP	1000pF 50V B
C5028	US135100	C. CE. CHP	0. 1uF 16V
* C5029	US625100	C. CE. CHP	0. 100uF 10V
C5030	US663100	C. CE. CHP	1000pF 50V
C5031	US061220	C. CE. CHP	22pF 50V B
C5032	UF037100	C. EL. CHP	10uF 16V
* C5033-5034	US625100	C. CE. CHP	0. 100uF 10V
C5035	US663100	C. CE. CHP	1000pF 50V
C5036	US061220	C. CE. CHP	22pF 50V B
C5037	UF018100	C. EL. CHP	100uF 6. 3V
C5038-5039	UF037100	C. EL. CHP	10uF 16V
C5040	UF037220	C. EL. CHP	22uF 16V
* C5041-5042	US663330	C. CE. CHP	3300pF 50V
C5043	US135100	C. CE. CHP	0. 1uF 16V
C5044-5049	US063100	C. CE. CHP	1000pF 50V B
C5050-5054	US135100	C. CE. CHP	0. 1uF 16V
C5055	UF037220	C. EL. CHP	22uF 16V
* C5056-5058	US625100	C. CE. CHP	0. 100uF 10V
C5059	UF037100	C. EL. CHP	10uF 16V
C5060	US135100	C. CE. CHP	0. 1uF 16V
* C5061	US625100	C. CE. CHP	0. 100uF 10V
C5062	UF037100	C. EL. CHP	10uF 16V
* C5063-5065	US625100	C. CE. CHP	0. 100uF 10V
C5066-5067	US135100	C. CE. CHP	0. 1uF 16V
* C5068-5069	US625100	C. CE. CHP	0. 100uF 10V
C5070	UF037100	C. EL. CHP	10uF 16V
* C5071	US625100	C. CE. CHP	0. 100uF 10V
C5072	US663100	C. CE. CHP	1000pF 50V
C5073-5076	US063100	C. CE. CHP	1000pF 50V B
* C5077-5078	US625100	C. CE. CHP	0. 100uF 10V
C5079	US135100	C. CE. CHP	0. 1uF 16V
* C5080-5081	US625100	C. CE. CHP	0. 100uF 10V
C5082	US135100	C. CE. CHP	0. 1uF 16V
* C5083	WP882000	C. CE. CHP	10uF 6. 3V
* C5084	US625100	C. CE. CHP	0. 100uF 10V
C5085-5086	US135100	C. CE. CHP	0. 1uF 16V
* C5087	US625100	C. CE. CHP	0. 100uF 10V
C5088	US062220	C. CE. CHP	220pF 50V B
* C5089-5095	US625100	C. CE. CHP	0. 100uF 10V
C5096-5107	US135100	C. CE. CHP	0. 1uF 16V
C5108	US663100	C. CE. CHP	1000pF 50V
C5109-5112	US063100	C. CE. CHP	1000pF 50V B
C5113-5114	US135100	C. CE. CHP	0. 1uF 16V
* C5115	WP882000	C. CE. CHP	10uF 6. 3V
C5116-5119	US662100	C. CE. CHP	100pF 50V
* C5501	US625100	C. CE. CHP	0. 100uF 10V
C5502	US062220	C. CE. CHP	220pF 50V B
C5503	UF018100	C. EL. CHP	100uF 6. 3V
* C5504	US625100	C. CE. CHP	0. 100uF 10V
C5505-5506	US135100	C. CE. CHP	0. 1uF 16V
C5507-5508	US634100	C. CE. CHP	0. 01uF 16V
C5509	UF037220	C. EL. CHP	22uF 16V

* New Parts

P.C.B. GUI

Ref No.	Part No.	Description	Markets
C5510~5511	US135100 C.CE CHIP	0.1uF	16V
* C5512~5513	US625100 C.CE CHIP	0.100uF	10V
C5514	US135100 C.CE CHIP	0.1uF	16V
C5515	W0758300 C.CE CHIP	10uF	10V
C5516	US061150 C.CE CHIP	15pF	50V B
C5517	US135100 C.CE CHIP	0.1uF	16V
C5518	UF018100 C.EL CHIP	100uF	6.3V
C5519	US135100 C.CE CHIP	0.1uF	16V
C5520	US061180 C.CE CHIP	18pF	50V B
C5521	US135100 C.CE CHIP	0.1uF	16V
C5522	W0758300 C.CE CHIP	10uF	10V
C5523	US135100 C.CE CHIP	0.1uF	16V
C5524~5525	US634100 C.CE CHIP	0.01uF	16V
C5527~5532	US135100 C.CE CHIP	0.1uF	16V
* C5533~5534	US625100 C.CE CHIP	0.100uF	10V
C5535	US135100 C.CE CHIP	0.1uF	16V
C5536~5537	US631300 C.CE CHIP	1000pF	50V
C5538	W0758300 C.CE CHIP	10uF	10V
C5539	W044220 C.CE CHIP	0.02uF	50V
* C5540	US625100 C.CE CHIP	0.100uF	10V
C5541	US631300 C.CE CHIP	1000pF	50V
C5542	US135100 C.CE CHIP	0.1uF	16V
* C5543	US625100 C.CE CHIP	0.100uF	10V
C5544~5545	US135100 C.CE CHIP	0.1uF	16V
* C5546~5548	US625100 C.CE CHIP	0.100uF	10V
C5549	US66220 C.CE CHIP	220pF	50V B
C5550~5551	US135100 C.CE CHIP	0.01uF	16V
C5552~5553	US064100 C.CE CHIP	0.1uF	50V B
C5554~5555	W0758300 C.CE CHIP	10uF	10V
* C5556	US625100 C.CE CHIP	0.100uF	10V
C5557~5558	US061120 C.CE CHIP	12pF	50V B
C5559	UF018100 C.EL CHIP	100uF	6.3V
I0501~502	X7678400 IC	SN74LV163APWR ONT	
I0503	X6534400 IC	SN74LV14APWR D+FF	
I0504	X7375400 IC	PON17810BQR	
* I0506	X4322400 IC	A68814VQ	
* I0507	X4478400 IC	K45S60832-JC75000	
* I0508	X4350400 IC	74LV01508BW AND	
* I0509~512	XZ286400 IC	74LV0245APW18	
* I0513	Y0017000 IC. MEMORY	K6P641500B-P1	(wr tten)
* I0514	X4478400 IC	K45S60832-JC75000	
I0521~522	X4063400 IC	TC7WH04UFU	
I0523	X4354400 IC	74LV08BAPW AND	
I0524	X6386400 IC	TC7WH14FK (TE8SL F)	
* I0525~526	X4356400 IC	74LV022APW OR	
I0552	X6096400 IC	R5523N001A-TR-F	
I0553	X4477400 IC	LA9217-MT	
* Q0500	WE834500 FEET	UP46721-T1-A	
S1550~551	V4040500 SCR. TERM	M3	
XL500	V6825700 RSNR CRY5	24.57MHz	
XL501	W6625000 RSNR CRY5	27MHz	
XL502	W6551700 RSNR CRY5	16.66MHz SMD-49	
XL550	W6538400 RSNR CRY5	12MHz	
* XL551	W6864600 RSNR CRY5	25MHz SMD-49	

※ : New Parts

P.C.B. ACDC

Ref No.	Part No.	Description	Markets
* W3306200	P.C.B.	ACDC	UC
* W3306300	P.C.B.	ACDC	R
* W3306400	P.C.B.	ACDC	TK48REF
* W3306500	P.C.B.	ACDC	L
C6601~602	WNI03000 Q.L.P. FUSE	TP00051~31	
C6603	V6879900 CN.BS P1N	2P	RL
C6604	V0961000 CN.BS P1N	7P	
* C6601	W6852400 C.POL.MTL	0.022uF 630V	
* C6602~6003	W6902300 C.CE.SAFETY	1000pF 250V	
* C6604	W6256400 C.CE.SAFETY	0.1uF 275V	
* C6606	W3068600 C.EL	150uF 400V	
* C6607	W0939400 C.CE.SAFETY	0.01uF 250V	
* C6608	WRI82800 C.CE.CHP	2200pF 250V	
C6609	US065100 C.CE.CHP	50V B	
C6610	UR837470 C.EL	47uF 16V	
C6611	UR867100 C.EL	10uF 50V	
* C6612	W0902300 C.CE.SAFETY	1000pF 250V	
* C6613	W0852400 C.POL.MTL	0.022uF 630V	
C6616~6017	UR866100 C.EL	1uF 50V	
* C6618~6019	W0777900 C.EL	35V	
C6620	US046100 C.CE.CHP	1uF 25V	
C6621	US135100 C.CE.CHP	0.1uF 16V	
C6622	W0771300 C.EL	100uF 10V	
C6101	US173100 C.CE.CHP	0.1uF 16V	
* C6601	W5071800 D10DE.BRG	SNR650 1A 600V	
* C6602	V644220 D10DE.ZENR	MT2J22C 22V	
* C6603~6004	W5071700 D10DE.ZENR	PXKE100A 100V	
* C6605	W0647500 D10DE	HT186	
* C6606	V0631600 D10DE	ISS133, 176	
* C6607	W0607000 D10DE.SCHO	10A 40V S810SCAM	
* C6608	V0631600 D10DE	ISS133, 176	
C6609	V7332900 D10DE	ISS355	
* F6001	W944000 FUSE	2A 250V	
* F6002	W0211200 FUSE	10A 125V	
* F6002	W0633100 FUSE	75A 250V	
* I0601	Y4851A00 IC	TOP255WN	
* I0602	W0867100 PHOT.CPL	EL816 (M) (C)	
* I0603	Y4276A00 IC	TL431AC 2.5~36V	
* I0604	W0867100 PHOT.CPL	EL816 (M) (C)	
* I0611	Y4381A00 IC	LM1961Z/LF THERMAL	
* RY601	W0604100 RELAY	DC DLS501-0 (M) 0.25	
* ST611	V4040500 SCR. TERM	M3	
* T6001	W4246200 SCR. TERM	3.5	
* T6001	W4507A00 TRANS.PWR	R-30190 (26)	
* T6001	W6782800 AC INLET	3x10 MF2N0K3	
* W6774200	SCR.BND.HD	3x10	


※ : New Parts

Carbon Resistors

Value	1/4W Type Part No.	1/6W Type Part No.	Value	1/4W Type Part No.	1/6W Type Part No.
1.0 Ω	HJ35 3100	HF85 3100	11 kΩ	HF45 7110	HF45 7110
1.8 Ω	HJ35 3180	*	12 kΩ	HJ35 7120	HF85 7120
2.2 Ω	HJ35 3220	HF85 3220	13 kΩ	HF45 7130	HF45 7130
3.3 Ω	HJ35 3300	HF85 3300	15 kΩ	HF45 7150	HF45 7150
3.7 Ω	HJ35 3370	HF85 3370	18 kΩ	HF45 7180	HF45 7180
5.6 Ω	HJ35 3560	HF85 3560	22 kΩ	HF45 7220	HF45 7220
10 Ω	HF45 4100	HF45 4100	24 kΩ	HF45 7240	HF45 7240
15 Ω	HJ35 4150	HF85 4150	27 kΩ	HF85 7270	HF85 7270
22 Ω	HF45 4220	HF45 4220	30 kΩ	HF45 7300	HF45 7300
27 Ω	HJ35 4270	HF85 4270	33 kΩ	HF45 7330	HF45 7330
33 Ω	HF45 4330	HF45 4330	36 kΩ	HF45 7360	HF45 7360
39 Ω	HJ35 4470	HF85 4390	39 kΩ	HF45 7390	HF45 7390
47 Ω	HF45 4470	HF45 4470	47 kΩ	HF45 7470	HF45 7470
56 Ω	HF45 4560	HF45 4560	51 kΩ	HF45 7510	HF45 7510
68 Ω	HF45 4680	HF45 4680	56 kΩ	HF45 7560	HF45 7560
75 Ω	HF45 4750	HF45 4750	62 kΩ	HF45 7620	HF45 7620
82 Ω	HF45 4820	HF45 4820	68 kΩ	HF45 7680	HF45 7680
91 Ω	HF45 4910	HF45 4910	82 kΩ	HF45 7820	HF45 7820
100 Ω	HF45 5100	HF45 5100	91 kΩ	HF45 7910	HF45 7910
110 Ω	HJ35 5110	HF85 5110	100 kΩ	HF45 8100	HF45 8100
120 Ω	HF45 5120	HF45 5120	110 kΩ	HF45 8110	HF45 8110
150 Ω	HF45 5150	HF45 5150	120 kΩ	HF45 8120	HF45 8120
160 Ω	HJ35 5160	*	130 kΩ	HF45 8130	*
180 Ω	HF45 5180	HF45 5180	150 kΩ	HF45 8150	HF45 8150
200 Ω	HF45 5200	HF45 5200	180 kΩ	HF45 8180	HF45 8180
220 Ω	HF45 5220	HF45 5220	220 kΩ	HF45 8220	HF45 8220
270 Ω	HF45 5270	HF45 5270	270 kΩ	HF45 8270	HF45 8270
330 Ω	HF45 5330	HF45 5330	300 kΩ	HF45 8300	HF45 8300
390 Ω	HF45 5390	HF45 5390	330 kΩ	HF45 8330	HF45 8330
430 Ω	HF45 5430	HF45 5430	390 kΩ	HJ35 8390	HF85 8390
470 Ω	HF45 5470	HF45 5470	470 kΩ	HF45 8470	HF45 8470
510 Ω	HF45 5510	HF45 5510	560 kΩ	HJ35 8560	HF85 8560
560 Ω	HF45 5560	HF45 5560	680 kΩ	HJ35 8680	HF85 8680
680 Ω	HF45 5680	HF45 5680	820 kΩ	HJ35 8820	HF85 8820
820 Ω	HF45 5820	HF45 5820	1.0 MΩ	HF45 9100	HF45 9100
910 Ω	HF45 5910	HF45 5910	1.2 MΩ	HJ35 9120	*
1.0 kΩ	HF45 6100	HF45 6100	1.5 MΩ	HJ35 9150	HF85 9150
1.2 kΩ	HF45 6120	HF45 6120	1.8 MΩ	HJ35 9180	HF85 9180
1.5 kΩ	HF45 6150	HF45 6150	2.2 MΩ	HJ35 9220	HF85 9220
1.8 kΩ	HF45 6180	HF45 6180	3.3 MΩ	HJ35 9330	HF85 9330
2.0 kΩ	HJ35 6200	HF85 6200	3.9 MΩ	HJ35 9390	*
2.2 kΩ	HF45 6220	HF45 6220	4.7 MΩ	HJ35 9470	HF85 9470
2.4 kΩ	HJ35 6240	HF85 6240			
2.7 kΩ	HF45 6270	HF45 6270			
3.0 kΩ	HF45 6300	HF45 6300			
3.3 kΩ	HF45 6330	HF45 6330			
3.6 kΩ	HJ35 6360	HF85 6360			
3.9 kΩ	HF45 6390	HF45 6390			
4.7 kΩ	HF45 6470	HF45 6470			
5.1 kΩ	HF45 6510	HF45 6510			
5.6 kΩ	HF45 6560	HF45 6560			
6.8 kΩ	HF45 6680	HF45 6680			
8.2 kΩ	HF45 6820	HF45 6820			
9.1 kΩ	HF45 6910	HF45 6910			
10 kΩ	HF45 7100	HF45 7100			

※ : Not available

• OVERALL ASSY




Ref No.	Part No.	Description	Remarks	Markets
* 2-1	WR913000	P.C.B. ASS'Y		R
* 2-1	WR913200	P.C.B. ASS'Y		L
* 2-2	NS304700	P.C.B. ASS'Y		U
* 2-2	NS304800	P.C.B. ASS'Y		C
* 2-2	NS304900	P.C.B. ASS'Y		R
* 2-2	NS305000	P.C.B. ASS'Y		T
* 2-2	NS305100	P.C.B. ASS'Y		K
* 2-2	NS305200	P.C.B. ASS'Y		A
* 2-2	NS305300	P.C.B. ASS'Y		BGEF
* 2-2	NS305400	P.C.B. ASS'Y		L
* 2-4	NS306200	P.C.B. ASS'Y		UC
* 2-4	NS306300	P.C.B. ASS'Y		R
* 2-4	NS306400	P.C.B. ASS'Y		TKABGEF
* 2-4	NS306500	P.C.B. ASS'Y		L
* 3-1	NS305800	P.C.B. ASS'Y	V2065	U
* 3-1	NS305900	P.C.B. ASS'Y	V2065	CRTAKL
* 3-1	NS306700	P.C.B. ASS'Y	6295	C
* 3-1	NS306800	P.C.B. ASS'Y	V2065	BGEF
* 3-2	NS305500	P.C.B. ASS'Y		U
* 3-2	NS305600	P.C.B. ASS'Y		CRTA
* 3-2	NS305700	P.C.B. ASS'Y		KBGEFL
* 3-18	WD083500	FLEXIBLE FLAT CABLE	20P 180mm P=1.0	
* 9	NS306800	P.C.B. ASS'Y	GU1	
* 12	WT510100	HD RADIO TUNER	2023-ORA	U
* 12	WD756600	AM/FM TUNER	FAEH06-A	CRTL
* 12	WD756700	AM/FM TUNER	FAEH06-E	KABGEF
Δ 15	YC001A00	POWER TRANSFORMER		UC
Δ 15	YA955A00	POWER TRANSFORMER		RL
Δ 15	YA956A00	POWER TRANSFORMER		TK
Δ 15	YA957A00	POWER TRANSFORMER		A
Δ 15	YA958A00	POWER TRANSFORMER		BGEF
27	MF113180	FLEXIBLE FLAT CABLE	13P 180mm P=1.25	U
* 27	WR284900	FLEXIBLE FLAT CABLE	11P 100mm P=1.25	CRTKABGEFL
* 29	WS162400	FLEXIBLE FLAT CABLE	5P 250mm P=1.25	BGEF
* 30	WS162500	FLEXIBLE FLAT CABLE	16P 60mm P=1.25	
* 101	WD665500	TOP COVER	BL	
* 101	WD665700	TOP COVER	T1	
* 103	NS042200	REAR PANEL		U
* 103	NS042300	REAR PANEL	V2065	C
* 103	NS043000	REAR PANEL	6295	C
* 103	NS042400	REAR PANEL		R
* 103	NS042500	REAR PANEL		T
* 103	NS042600	REAR PANEL		K
* 103	NS042700	REAR PANEL		A
* 103	NS042800	REAR PANEL		BGEF
* 103	NS042900	REAR PANEL		L
104	WB870100	DAMPER		BGEF
* 105	WR004900	PLATE SIDE	BL	
* 105	WR005000	PLATE SIDE	T1	
* 107	WR946700	BARRIER FFC		
* 108	WS000800	SPACER SUPPORT		
* 109	WD664500	SUPPORT H8		
120	VS025000	LEG	LCA4-29M PIN	
		D60xH21 HS		

※ New Parts

Ref No.	Part No.	Description	Remarks	Markets
121	WJ181300	KNOB		BL
121	WJ181500	KNOB	D50	D50
* 122	NS039800	KNOB	D21	T1
* 122	NS039900	KNOB	D21	BL
152	WG879000	DAMPER	D21	T1
* 153	WR377400	DAMPER	SCREW MASK	
155	VG368600	PUSH RIVET	14x10x10	
156	WK667900	SHEET TOP	P3555-B	L
157	WJ053800	RIVET TOP		L
160	WE774100	BIND HEAD BONDING B-T. SCREW	3x8 MFZM2B3	
163	WE774300	BIND HEAD B-TIGHT SCREW	3x8 MFZM2W3	
164	WE877900	BIND HEAD S-TIGHT SCREW	3x6 MFZM2W3	
167	WF002600	PM HEAD B-TIGHT SCREW	3x8 MFZM2W3	
168	WE774600	SCREW 1C	3x18 MFZM2W3	
170	WE774700	BIND HEAD S-TIGHT SCREW	4x10 MFZM2W3	
171	VH313200	PM HEAD S-TIGHT SCREW	4x8-10 MFN13BL	BL
171	VD069600	PM HEAD S-TIGHT SCREW	4x8-10 MFN133	T1
172	WE200500	DISH HEAD B-TIGHT SCREW	3x6 MFN13BL	BL
172	WE200400	DISH HEAD B-TIGHT SCREW	3x6 MFN133	T1
175	V6509600	JACK SCREW	SS6-A47511848	
176	AA627310	GROUND TERMINAL		
		SERVICE TOOLS		
	WR492800	RS232C CONVERSION ADAPTOR	3.3Vtype with FFC9P	
	MF125400	FLEXIBLE FLAT CABLE	25P 400mm P=1.25	
	MF109400	FLEXIBLE FLAT CABLE	9P 400mm P=1.25	
	MF420250	FLEXIBLE FLAT CABLE	20P 250mm P=1.0	

※ New Parts

• ACCESSORIES




Ref No.	Part No.	Description	Remarks	Markets
* 200	WS317100	REMOTE CONTROL	RAV296	U
* 200	WS317200	REMOTE CONTROL	RAV297	CRAL
* 200	WS317300	REMOTE CONTROL	RAV298	TKGGEF
200-1	AA82380	BATTERY COVER	CG-2209	
* 201	WS317400	SIMPLIFIED REMOTE CONTROL	RAV38	
201-1	AA71770	BATTERY HOLDER	CG-4335 Black	UC
202	V7704800	POWER CABLE	2m 1pc	R
202	WK391000	POWER CABLE	2m 1pc	T
202	V9359400	POWER CABLE	2m 1pc	K
202	WH641300	POWER CABLE	2m 1pc	A
202	WB750900	POWER CABLE	2m 1pc	B
202	WB751000	POWER CABLE	2m 1pc	GEFL
202	V7704900	POWER CABLE	2m 1pc	L
203	WB751000	POWER CABLE	1.4m 1pc	UCRTL
204	V6267000	INDOOR FM ANTENNA	1.4m 1pc	KABGEF
204	V0147100	INDOOR FM ANTENNA	1.2m 1pc	U
205	WE746800	AM LOOP ANTENNA	1.0m 1pc	CRTKABGEFL
205	VR246500	AM LOOP ANTENNA	1.0m 1pc	
206	WN649600	OPTIMIZER MICROPHONE	6.0m 1pc	
* 207	WS039400	VIDEO AUX INPUT COVER	1pc	BL
* 207	WS039500	BATTERY LITHIUM BATTERY	1pc	TI
			RC03 AAA UM-4 2pcs	
			CR2025 1pc	

*: New Parts

RX-V2065/HTR-6295

• AMP UNIT



Ref No.	Part No.	Description	Remarks	Markets
* 2-1	WR912900	P. C. B. ASS'Y	MAIN	UC
* 2-1	WR913000	P. C. B. ASS'Y	MAIN	R
* 2-1	WR913100	P. C. B. ASS'Y	MAIN	TKABGEF
* 2-1	WR913200	P. C. B. ASS'Y	MAIN	L
* 2-2	WS304700	P. C. B. ASS'Y	VIDEO	U
* 2-2	WS304800	P. C. B. ASS'Y	VIDEO	C
* 2-2	WS304900	P. C. B. ASS'Y	VIDEO	R
* 2-2	WS305000	P. C. B. ASS'Y	VIDEO	T
* 2-2	WS305100	P. C. B. ASS'Y	VIDEO	K
* 2-2	WS305200	P. C. B. ASS'Y	VIDEO	A
* 2-2	WS305300	P. C. B. ASS'Y	VIDEO	BGEF
* 2-2	WS305400	P. C. B. ASS'Y	VIDEO	L
* 2-4	WS306200	P. C. B. ASS'Y	ADOC	UC
* 2-4	WS306300	P. C. B. ASS'Y	ADOC	R
* 2-4	WS306400	P. C. B. ASS'Y	ADOC	TKABGEF
* 2-4	WS306500	P. C. B. ASS'Y	ADOC	L
* 2-11	W0753200	MICA SHEET	TB-1021 40x23x0.06	
* 2-20	WS000800	SPACER SUPPORT	LC44-29M PIN	
* 2-25	WS162200	FLEXIBLE FLAT CABLE	22P 160mm P=1.25	
* 2-26	WR285300	FLEXIBLE FLAT CABLE	14P 200mm P=1.25	
* 2-28	WJ788600	ELECTROLYTIC CAPACITOR	12000uF 71V	
* 2-35	WS341600	THERMAL PROTECTOR	OP62G-90	C1084, C1085
* 2-36	WS545600	SUPPORT THW		
* 2-103	WM220800	HEXAGONAL HEAD B-TIGHT SCREW	3x15 SP MFZN2W3	CRTKABGEFL
* 2-104	WF002600	PH HEAD B-TIGHT SCREW	3x8 MFZN2W3	CRTKABGEFL
* 2-105	WE774300	BIND HEAD B-TIGHT SCREW	3x8 MFZN2W3	
* 2-106	V0368600	PUSH RIVET	P3555-B	
* 3-2	WS305500	P. C. B. ASS'Y	OPERATION	U
* 3-2	WS305600	P. C. B. ASS'Y	OPERATION	CRTA
* 3-2	WS305700	P. C. B. ASS'Y	OPERATION	K08EFL

*: New Parts


(Note) Those parts marked with "*" are not included in the P.C.B. ass'y.

REMOTE CONTROL


- RAV296: U model / RAV297: C, R, A, L models / RAV298: T, K, B, G, E, F models

SCHEMATIC DIAGRAMS

RAV296/RAV297




RAV298




PANELS


RAV296
(U model)




RAV297
(C, R, A, L models)



RAV298
(T, K, B, G, E, F models)



KEY NO. LAYOUT



KEY CODE

GROUP	PRE SET	Key No.	FUNCTION	ID1	ID2
	-	SW1	MAIN / ZONE2 / ZONE3	MAIN [MAIN]	ZONE2 [ZONE2]
		D2	TRANSMIT	-	-
		SW2	CODE SET	-	-
POWER	-	K2	SLEEP	7A-30	7A-31CF
INPUT 1	O	K3	POWER /	7E-2A	7A-4638
		K4	HDMI-1 (Default setting)	7A-4738	7A-4837
		K5	HDMI-2	7A-4A35	7A-4B34
		K6	HDMI-3	7A-4D32	7A-4E31
	O	K7	HDMI-4	7A-502F	7A-512E
		K8	AV-1	7A-532C	7A-542B
		K9	AV-2	7A-5629	7A-5728
		K10	AV-3	7A-5826	7A-5A25
	O	K11	AV-4	7A-5C23	7A-5D22
		K12	AV-5	7A-5F20	7A-601F
		K13	AV-6	7A-621D	7A-631C
		K14	AUDIO-1	7A-651A	7A-6619
	O	K15	AUDIO-2	7A-6817	7A-6916
		K16	HDMI / V-AUX	7A-55	7A-D8
		K17	PHONO	7A-14	7A-D0
		K18	MULTI	7A-87	-
INPUT 2	-	K19	DOCK	7F01-4A	7F01-4B
		K20	TUNER	7A-16	7A-D2
		K21	SIRIUS (U model, RAV296)	7A-39	7A-3A
		K22	XM (U model, RAV296)	7A-B4	7A-B8
RADIO	-	K23	USB/NET	7F01-3F	7F01-40
		K24	CATEGORY / FM (RAV296)	7F01-3827	7F01-5926
		K25	CATEGORY / AM (RAV296)	7F01-582A	7F01-5829
		K26	PRESET	7F01-5B24	7F01-5C23
	-	K27	TUNING	7F01-611E	7F01-621D
		K28	INFO	7A-2758	7A-2857
		K29	MEMORY	7F01-6718	7F01-6817
		K30	PRESET	7F01-5E21	7F01-5F20
DSP	-	K31	TUNING/CH	7F01-641B	7F01-651A
		K33	MUSIC	7A-89	-
		K34	ENHANCER / STEREO	7A-94	-
		K35	SUR. DECODE	7A-8D	-
	-	K36	HDMI OUT	7A-35	-
		K37	MOVIE	7A-88	-
		K38	STRAIGHT	7A-56	-
		K39	PURE DIRECT	7A-DD	-

GROUP	PRE SET	COM	Key No.	FUNCTION	ID1	ID2
SCENE	-	O	K40	BD/DVD	MAIN	ZONE2
		O	K41	TV	7A-007F	7A-007E
		O	K42	CD	7A-037C	7A-047B
		O	K43	RADIO	7A-0679	7A-0778
MENU	-	O	K44	ON SCREEN	7A-0976	7A-0A75
		O	K46	OPTION	7A-84	-
		-	K45	▲ (UP)	7A-8B14	-
		-	K48	▼ (DOWN)	7A-8B15	-
CURSOR	-	-	K49	ENTER	7A-9D	-
		-	K50	► (RIGHT)	7A-9F	-
		-	K51	◄ (LEFT)	7A-9E	-
		-	K52	RETURN	7A-AA	-
VOLUME	-	O	K47	VOLUME +	7A-9C	-
		O	K54	VOLUME -	7F01-80	7F01-807E
		O	K57	MUTE	7A-1A	7A-1AE4
		-	K55	POWER / SOURCE	7A-1B	7A-1BE5
SOURCE	-	-	K61	TOP MENU	7A-1C	7A-1CE2
		-	K56	POP-UP MENU (RAV296)	-	-
		-	K58	MENU (RAV297, RAV298)	-	-
		-	K59	REC	-	-
	-	-	K60	▷ (PLAY)	-	-
		-	K61	□ (STOP)	-	-
		-	K62	◀ (PAUSE)	-	-
		-	K63	◀ (REW)	-	-
	-	-	K64	TAG / (FF) (RAV296)	-	-
		-	K65	PRG SELECT / (FF) (RAV297, RAV298)	-	-
		-	K66	PRG SELECT / (FF) (RAV299)	-	-
		-	K67	PRG SELECT / (FF) (RAV296)	-	-
10 key	-	-	K68	USB / 1	-	-
		-	K69	NET RADIO / 2	-	-
		-	K70	PC / 3	-	-
		-	K71	RHAPSODY / 4 (RAV296)	-	-
	-	-	K72	4 (RAV297, RAV298)	-	-
		-	K73	5	-	-
		-	K74	6	-	-
		-	K75	7	-	-
TV	-	-	K76	8	-	-
		-	K77	9	-	-
		-	K78	0	-	-
		-	K79	+10	-	-
	-	-	K80	ENT	-	-
		-	K81	INPUT	-	-
		-	K82	TV VOL +	-	-
		-	K83	TV VOL -	-	-
	-	-	K84	POWER	-	-
		-	K85	MUTE	-	-
		-	K86	TV CH -	-	-
		-	K87	TV CH +	-	-

FUNCTION CODE


Key No.	Brand	Yamaha-1	BD	Yamaha-1	DVD	Yamaha-2	Yamaha-3	T	DVR	LD	Yamaha	Brand	Yamaha-1	CD	Yamaha-2	Brand	CD-R	Yamaha	Brand	Yamaha-1	MD	Yamaha-2	Yamaha-3	
	Preset Number	Function	Code	Code	Code	Code	Code	2136	Preset Number	Code	2011	Preset Number	Code	5013	5000	Preset Number	Function	Code	Preset Number	Function	Code	5002	5003	5004
K45	K45	UP	7C-84	7C-84	2002 BD 00 85 35	004 088	4856 60	MENU UP	048 068	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088	048 088
K46	K46	LEFT	7C-85	7C-85	2002 BD 00 87 37	004 090	4856 51	MENU LEFT	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090	048 090
K49	K49	ENTER	7C-86	7C-86	2002 BD 00 82 32	004 092	4856 21	MENU ENTER	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092
K50	K50	RIGHT	7C-86	7C-86	2002 BD 00 86 38	004 091	4856 40	MENU RIGHT	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091	048 091
K51	K51	RETURN	7C-87	7C-87	2002 BD 00 81 31	004 131	4856 22	RETURN	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131	048 131
K52	K52	DOWN	7C-83	7C-83	2002 BD 00 86 38	004 089	4856 81	MENU DOWN	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089	048 089
K53	K53	DISPLAY	7C-86	7C-86	2002 BD 00 82 32	004 092	4856 21	DISPLAY	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092	048 092
K1	K1	SOURCE POWER	7C-80	7C-80	2002 BD 00 30 80	004 072	4853 12	AV POWER	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072	048 072
K54	K54	TOP MENU	7C-81	7C-81	2002 BD 00 80 30	004 084	4856 64	TOP MENU	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084
K55	K55	MENU	7C-82	7C-82	2002 BD 00 80 30	004 084	4856 64	MENU	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084	048 084
K58	K58	DISC SKIP	7C-83	7C-83	2002 BD 00 82 32	004 127	77	REC	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055	048 055
K59	K59	PLAY	7C-82	7C-82	2002 BD 00 80 30	004 044	4853 15	PLAY	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044	048 044
K60	K60	STOP	7C-85	7C-85	2002 BD 00 80 30	004 049	4853 14	STOP	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049	048 049
K61	K61	PAUSE	7C-83	7C-83	2002 BD 00 80 30	004 048	4853 06	PAUSE	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048	048 048
K62	K62	REW	7C-86	7C-86	2002 BD 00 80 30	004 041	4853 19	REW	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041	048 041
K63	K63	FF	7C-87	7C-87	2002 BD 00 80 30	004 040	4853 13	FF	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040	048 040
K64	K64	SKIP (-)	7C-89	7C-89	2002 BD 00 84 34	004 093	4856 23	CHANGEPREP (-)	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093
K65	K65	SKIP (+)	7C-89	7C-89	2002 BD 00 84 34	004 093	4856 23	CHANGEPREP (+)	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093	048 093
K66	K66	1	7C-94	7C-94	2002 BD 00 10 40	004 003	4856 01	1	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003
K67	K67	2	7C-95	7C-95	2002 BD 00 11 41	004 002	4856 02	2	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002	048 002
K68	K68	3	7C-96	7C-96	2002 BD 00 12 42	004 003	4856 03	3	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003	048 003
K69	K69	4	7C-97	7C-97	2002 BD 00 13 43	004 004	4856 04	4	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004	048 004
K70	K70	5	7C-98	7C-98	2002 BD 00 14 44	004 005	4856 05	5	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005	048 005
K71	K71	6	7C-99	7C-99	2002 BD 00 15 45	004 006	4856 06	6	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006	048 006
K72	K72	7	7C-9A	7C-9A	2002 BD 00 16 46	004 007	4856 07	7	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007	048 007
K73	K73	8	7C-9B	7C-9B	2002 BD 00 17 47	004 008	4856 08	8	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008	048 008
K74	K74	9	7C-9C	7C-9C	2002 BD 00 18 48	004 009	4856 09	9	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009	048 009
K75	K75	0	7C-9D	7C-9D	2002 BD 00 19 49	004 000	4856 0A	0	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000	048 000
K76	K76	+10	7C-9E	7C-9E	2002 BD 00 89 39	004 120	4856 20	+10	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120
K77	K77	TITLE INDEX	7C-9E	7C-9E	2002 BD 00 89 39	004 120	4856 20	TITLE INDEX	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120	048 120
K78	K78	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT	TV INPUT
K79	K79	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)	TV VOL (+)
K80	K80	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)	TV CH (+)
K81	K81	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER	TV POWER
K82	K82	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE	TV MUTE
K83	K83	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)	TV VOL (-)
K84	K84	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)	TV CH (-)

Key No.	Brand	Yamaha-2	Yamaha-3	Yamaha-4	Yamaha-5	Yamaha-6	Yamaha-7	Yamaha-11	Yamaha-12	Yamaha-9	Yamaha-10	Yamaha-1	Yamaha-2	Yamaha-3	Yamaha-4	Yamaha-5	Yamaha-6	Yamaha-7	Yamaha-8	Yamaha-9	Yamaha-10	Yamaha-11	Yamaha-12	Yamaha-13	Yamaha-14	Yamaha-15	Yamaha-16	Yamaha-17	Yamaha-18	Yamaha-19	Yamaha-20	Yamaha-21	Yamaha-22	Yamaha-23	Yamaha-24	Yamaha-25	Yamaha-26	Yamaha-27	Yamaha-28	Yamaha-29	Yamaha-30	Yamaha-31	Yamaha-32	Yamaha-33	Yamaha-34	Yamaha-35	Yamaha-36	Yamaha-37	Yamaha-38	Yamaha-39	Yamaha-40	Yamaha-41	Yamaha-42	Yamaha-43	Yamaha-44	Yamaha-45	Yamaha-46	Yamaha-47	Yamaha-48	Yamaha-49	Yamaha-50	Yamaha-51	Yamaha-52	Yamaha-53	Yamaha-54	Yamaha-55	Yamaha-56	Yamaha-57	Yamaha-58	Yamaha-59	Yamaha-60	Yamaha-61	Yamaha-62	Yamaha-63	Yamaha-64	Yamaha-65	Yamaha-66	Yamaha-67	Yamaha-68	Yamaha-69	Yamaha-70	Yamaha-71	Yamaha-72	Yamaha-73	Yamaha-74	Yamaha-75	Yamaha-76	Yamaha-77	Yamaha-78	Yamaha-79	Yamaha-80	Yamaha-81	Yamaha-82	Yamaha-83	Yamaha-84	Yamaha-85	Yamaha-86	Yamaha-87	Yamaha-88	Yamaha-89	Yamaha-90	Yamaha-91	Yamaha-92	Yamaha-93	Yamaha-94	Yamaha-95	Yamaha-96	Yamaha-97	Yamaha-98	Yamaha-99	Yamaha-100	Yamaha-101	Yamaha-102	Yamaha-103	Yamaha-104	Yamaha-105	Yamaha-106	Yamaha-107	Yamaha-108	Yamaha-109	Yamaha-110	Yamaha-111	Yamaha-112	Yamaha-113	Yamaha-114	Yamaha-115	Yamaha-116	Yamaha-117	Yamaha-118	Yamaha-119	Yamaha-120	Yamaha-121	Yamaha-122	Yamaha-123	Yamaha-124	Yamaha-125	Yamaha-126	Yamaha-127	Yamaha-128	Yamaha-129	Yamaha-130	Yamaha-131	Yamaha-132	Yamaha-133	Yamaha-134	Yamaha-135	Yamaha-136	Yamaha-137	Yamaha-138	Yamaha-139	Yamaha-140	Yamaha-141	Yamaha-142	Yamaha-143	Yamaha-144	Yamaha-145	Yamaha-146	Yamaha-147	Yamaha-148	Yamaha-149	Yamaha-150	Yamaha-151	Yamaha-152	Yamaha-153	Yamaha-154	Yamaha-155	Yamaha-156	Yamaha-157	Yamaha-158	Yamaha-159	Yamaha-160	Yamaha-161	Yamaha-162	Yamaha-163	Yamaha-164	Yamaha-165	Yamaha-166	Yamaha-167	Yamaha-168	Yamaha-169	Yamaha-170	Yamaha-171	Yamaha-172	Yamaha-173	Yamaha-174	Yamaha-175	Yamaha-176	Yamaha-177	Yamaha-178	Yamaha-179	Yamaha-180	Yamaha-181	Yamaha-182	Yamaha-183	Yamaha-184	Yamaha-185	Yamaha-186	Yamaha-187	Yamaha-188	Yamaha-189	Yamaha-190	Yamaha-191	Yamaha-192	Yamaha-193	Yamaha-194	Yamaha-195	Yamaha-196	Yamaha-197	Yamaha-198	Yamaha-199	Yamaha-200	Yamaha-201	Yamaha-202	Yamaha-203	Yamaha-204	Yamaha-205	Yamaha-206	Yamaha-207	Yamaha-208	Yamaha-209	Yamaha-210	Yamaha-211	Yamaha-212	Yamaha-213	Yamaha-214	Yamaha-215	Yamaha-216	Yamaha-217	Yamaha-218	Yamaha-219	Yamaha-220	Yamaha-221	Yamaha-222	Yamaha-223	Yamaha-22
---------	-------	----------	----------	----------	----------	----------	----------	-----------	-----------	----------	-----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	-----------


■ REMOTE CONTROL

- RAV38


SCHEMATIC DIAGRAM







PANEL



KEY NO. LAYOUT



KEY CODE

Key No.	Key name	Code									
		ID1					ID2				
		ZONE2	ZONE3	ZONE4	MAIN	ZONE2	ZONE3	ZONE4			
1	SLEEP	7A-30	7A-31	7A-32	7A-33	7A-30C2	7A-30C3	7A-30C4	7A-30C5	7A-30C6	7A-30C7
2	POWER / 	7E-2A	7A-433A	7A-4639	7A-6F10	7E-2A04	7A-433B	7A-4638	7A-6F11	7A-4639	7A-6F11
6	SCENE / BD/DVD	7A-007F	7A-017E	7A-027D	7A-1B87	7A-007E	7A-017F	7A-027C	7A-1B86	7A-007E	7A-017F
7	SCENE / TV	7A-037C	7A-047B	7A-057A	7A-1966	7A-037D	7A-047A	7A-057B	7A-1967	7A-037D	7A-047A
8	SCENE / CD	7A-067B	7A-077F	7A-0877	7A-1A65	7A-067B	7A-0779	7A-0876	7A-1A1A	7A-067B	7A-0779
9	SCENE / RADIO	7A-0976	7A-0A75	7A-0B7A	7A-1B84	7A-0977	7A-0A74	7A-0B75	7A-1B85	7A-0977	7A-0A74
11	INPUT <	7A-2B5C	7A-245B	7A-255A	7A-2B59	7A-2B5D	7A-245A	7A-255B	7A-2B58	7A-2B5C	7A-245B
13	INPUT >	7A-1F60	7A-265F	7A-215E	7A-255D	7A-1F61	7A-265E	7A-215F	7A-255C	7A-1F60	7A-265E
15	ON SCREEN	7A-84	7A-3B44	7A-443B	7A-413E	7A-847A	7A-3B45	7A-443A	7A-413F	7A-84	7A-3B44
16	 (UP)	7A-3D	7A-2B54	7A-304F	7A-354A	7A-3D3C	7A-2B55	7A-304E	7A-354B	7A-3D	7A-2B54
17	OPTION	7A-6B14	7A-6C13	7A-6D12	7A-6E11	7A-6B15	7A-6C12	7A-6D13	7A-6E10	7A-6B14	7A-6C13
18	VOLUME +	7A-1A	7A-DA	7A-FD	7A-2B	7A-1A1E	7A-DA24	7A-FD24	7A-2B05	7A-1A	7A-DA
19	< (LEFT)	7A-9F	7A-2D52	7A-3D4D	7A-374B	7A-9F61	7A-2D53	7A-3D4C	7A-3749	7A-9F	7A-2D52
20	ENTER	7A-DE	7A-2F50	7A-3A4B	7A-3946	7A-DI20	7A-2F51	7A-3A4A	7A-3947	7A-DE	7A-2F50
21	 (RIGHT)	7A-9E	7A-2E51	7A-334C	7A-3847	7A-9E60	7A-2E50	7A-334D	7A-3846	7A-9E	7A-2E51
22	VOLUME -	7A-1B	7A-DB	7A-FE	7A-3C	7A-1B05	7A-DB05	7A-FE00	7A-3C02	7A-1B	7A-DB
23	RETURN	7A-AA	7A-3C43	7A-3F4D	7A-423D	7A-AA54	7A-3C42	7A-3F41	7A-423C	7A-AA	7A-3C43
24	 (DOWN)	7A-9C	7A-2C53	7A-314E	7A-3649	7A-9C62	7A-2C52	7A-314F	7A-3648	7A-9C	7A-2C53
25	PLAY	7F01-60	7F01-40	7F01-4D	7F01-C0	7F01-60B2	7F01-407E	7F01-A05E	7F01-C0B2	7F01-60	7F01-40
26	MUTE	7A-1C	7A-DC	7A-FF	7A-2D	7A-1C1E	7A-DC22	7A-FF01	7A-2D03	7A-1C	7A-DC
27	TAG / >	7F01-68	7F01-48	7F01-A8	7F01-C8	7F01-68B6	7F01-487E	7F01-A85E	7F01-C8B6	7F01-68	7F01-48
28	PRG SELECT /	7F01-6C	7F01-4C	7F01-AC	7F01-CC	7F01-6C92	7F01-4C72	7F01-A05E	7F01-C092	7F01-6C	7F01-4C
29	PRG SELECT /	7F01-6D	7F01-4D	7F01-AD	7F01-CD	7F01-6D93	7F01-4D73	7F01-A05F	7F01-C093	7F01-6D	7F01-4D
30		7F01-6B	7F01-4B	7F01-A9	7F01-C9	7F01-6B97	7F01-4B77	7F01-A95F	7F01-C9B7	7F01-6B	7F01-4B
31	PRESET <	7F01-5E21	7F01-5F20	7F01-401F	7F01-6B14	7F01-5E20	7F01-5F21	7F01-401E	7F01-6B15	7F01-5E21	7F01-5F20
32	PRESET >	7F01-5B24	7F01-5C23	7F01-5D22	7F01-6A15	7F01-5B25	7F01-5C22	7F01-5D23	7F01-6A16	7F01-5B24	7F01-5C23

Default: ID1/MAIN

ID setting	[K19] + [K6] = ID1				[K19] + [K7] = ID2			
	[K21] + [K6] = MAIN	[K21] + [K7] = ZONE2	[K21] + [K9] = ZONE3	[K21] + [K9] = ZONE4	[K21] + [K6] = MAIN	[K21] + [K7] = ZONE2	[K21] + [K9] = ZONE3	[K21] + [K9] = ZONE4
ID setting								

■ ADVANCED SETUP

In the advanced setup menu, you can set basic operations of this unit, such as on and off of a bi-amp connection, or initialize user settings.

1 Set this unit to standby.

2 While holding down **Ⓢ**STRAIGHT on the front panel, press **Ⓛ**MAIN ZONE ON/OFF.

Keep holding down **Ⓢ**STRAIGHT until "ADVANCED SETUP" appears on the front panel display.

ADVANCED SETUP

3 Rotate the **Ⓟ**PROGRAM selector to select the parameter you want to change.

The default setting are marked with "*".



- Set values are placed in XXX of the following parameters on an actual display screen.

SP IMP. -XXX

Choices: 6ΩMIN, 8ΩMIN*

Selects output impedance of this unit according to connected speakers. When you connect 4-ohm speakers to the FRONT speaker terminals, set "SP IMP:" to "6ΩMIN".

RS232C STBY -X

Choices: Y (Yes)*, N (No)

Selects whether or not to transmit data via the RS-232C terminal when this unit is in the standby mode.

REMOTE ID -XXX

Choices: ID1*, ID2

Sets a remote control ID. When using multiple Yamaha AV receivers, you can operate them with a single remote control by setting the receiver IDs to the same setting.

SR PIN -XXX

Choices: RESET, CANCEL*

Resets Parental lock cord when using SIRIUS Satellite tuner.

BI AMP - XXX

Choices: ON, OFF*

Switches on and off of bi-amp connection of main speakers.

SCENE IR -XXX

Choices: ON*, OFF

Selects whether or not to transmit the control signals to an external component connected to the REMOTE OUT jack on this unit when BD/DVD or CD SCENE function is selected.

MON.CHK - XXXX

Choices: YES*, SKIP

Adds upscaling limitation on output signals to a video monitor connected to this unit via the HDMI OUT jack.

INIT-XXXXXXXXXX

Choices: DSP PARAM, VIDEO, NETWORK, ALL, CANCEL*

Initializes various settings stored in this unit. You can select an initialization method from the following.

DSP PARAM: All parameters of sound field

programs

VIDEO Video conversion settings (resolution/aspect) in the Setup menu and the GUI display position

NETWORK Network settings in the Setup menu

ALL All

CANCEL Cancellation of initialization

USB FirmUpdate

NET FirmUpdate

Updates the firmware of this unit. For details on how to update the firmware, refer to information supplied with updates.

Notes

- Do not use this feature unless you need to update the firmware.
- Be sure to read information supplied with updates before updating the firmware.

VERXXX.XXX.XXX

Displays the firmware of this unit.

4 Press **Ⓢ**STRAIGHT repeatedly to change the selected parameter setting.

To change other settings, repeat steps 3 and 4.

5 Press **Ⓛ**MAIN ZONE ON/OFF to set this unit to standby.

The settings you made are reflected next time you turn on this unit.


Setting a remote control ID

Two IDs are provided for the remote control of this unit. If another Yamaha amplifier is in the same room, setting a different remote control ID to this unit prevents unwanted operation of the other amplifier.

“ID1” is set for both the main unit and remote control by default. If you have changed the remote control ID, make sure that you select the same ID for the main unit in the advanced setup menu.



- For details on how to set the remote control ID of the simplified remote control.

1 Press  **CODE SET on the remote control using a pointed object such as the tip of a ballpoint pen.**

 **TRANSMIT** blinks twice.

2 Press  **ON SCREEN.**

3 Enter the desired remote control ID code.

To switch to ID1, press  **Numeric keys** to enter “5019”.

To switch to ID2, press  **Numeric keys** to enter “5020”.

Once the remote control code is registered,

 **TRANSMIT** blinks twice.

If it fails,  **TRANSMIT** blinks six times. Repeat from step 1.



- If you initialize the settings of this unit, “REMOTE ID” (remote control code of this unit) is set to “ID1”.

MEMO

RX-V2065/HTR-6295

