AV RECEIVER/AV AMPLIFIER

RX-V661/HTR-6060/DSP-AX761

SERVICE MANUAL

IMPORTANT NOTICE

This manual has been provided for the use of authorized YAMAHA Retailers and their service personnel.
It has been assumed that basic service procedures inherent to the industry, and more specifically YAMAHA Products, are already known and understood by the users, and have therefore not been restated.

WARNING: Failure to follow appropriate service and safety procedures when servicing this product may result in personal injury, destruction of expensive components, and failure of the product to perform as specified. For these reasons, we advise all YAMAHA product owners that any service required should be performed by an authorized YAMAHA Retailer or the appointed service representative.

IMPORTANT: The presentation or sale of this manual to any individual or firm does not constitute authorization, certification or recognition of any applicable technical capabilities, or establish a principle-agent relationship of any form.

The data provided is believed to be accurate and applicable to the unit(s) indicated on the cover. The research, engineering, and service departments of YAMAHA are continually striving to improve YAMAHA products. Modifications are, therefore, inevitable and specifications are subject to change without notice or obligation to retrofit. Should any discrepancy appear to exist, please contact the distributor's Service Division.

WARNING: Static discharges can destroy expensive components. Discharge any static electricity your body may have accumulated by grounding yourself to the ground buss in the unit (heavy gauge black wires connect to this buss).

IMPORTANT: Turn the unit OFF during disassembly and part replacement. Recheck all work before you apply power to the unit.

■ CONTENTS

TO SERVICE PERSONNEL 2
FRONT PANELS 3–4
REAR PANELS 5–8
REMOTE CONTROL PANELS 9
SPECIFICATIONS / 参考仕様 10–12
INTERNAL VIEW 13
DISASSEMBLY PROCEDURES / 分解手順 14–17
UPDATING FIRMWARE /
ファームウェアの書き込み 18–25
SELF DIAGNOSIS FUNCTION (DIAG) /
自己診断機能（ダイアグ） 26–52
AMP ADJUSTMENT / アンプ部調整 53
DISPLAY DATA 54–55
IC DATA 56–70
BLOCK DIAGRAMS 71–75
PRINTED CIRCUIT BOARDS 76–88
PIN CONNECTION DIAGRAMS 89–91
SCHEMATIC DIAGRAMS 93–101
REPLACEMENT PARTS LIST 103–129
REMOTE CONTROL 130–133
ADVANCED SETUP / 本機の設定を変更する 134–136
SCENE CONTROL 137

このサービスマニュアルは、エコマーク認定の再生紙を使用しています。
This Service Manual uses recycled paper.

101042

© 2007 YAMAHA CORPORATION All rights reserved.
This manual is copyrighted by YAMAHA and may not be copied or redistributed either in print or electronically without permission.

YAMAHA
YAMAHA CORPORATION
P.O.Box 1, Hamamatsu, Japan
'07.03

■ FRONT PANELS

RX-V661 (U, C models)



RX-V661 (R, T, K, A, G, E, L models)



HTR-6060 (U, C models)



HTR-6060 (G model)



DSP-AX761 (B model)



DSP-AX761 (J model)



■ REAR PANELS

RX-V661 (U, C models)



RX-V661 (R model)



RX-V661 (T model)



RX-V661 (K model)



RX-V661 (A model)



RX-V661 (G, E models)



RX-V661 (L model)



HTR-6060 (U, C models)



HTR-6060 (G model)



DSP-AX761 (B model)



DSP-AX761 (J model)



■ REMOTE CONTROL PANELS

- **RAV326**
  RX-V661 (U, C models)
  HTR-6060 (U, C models)



- **RAV327**
  RX-V661 (R, T, A, L models)
  DSP-AX761 (J model)



- **RAV364**
  RX-V661 (K, G, E models)
  HTR-6060 (G model)
  DSP-AX761 (B model)